



## Multifunctional Gear Oil Additive Package Price

### ●Introduction

The product is formulated with selected high quality Corrosion Inhibitor ZDDP, High Temperature Antioxidant, Antiwear EP Additive and other Lubricant Additive Component. Oils blended with T4208 have excellent high-temp antioxidant, anti-corrosion, antifoaming, demulsibility. It can prolong the service life of gear teeth and bearings, lower filter blocking. This product is suitable for blending gear oils that conform to the API GL-5, GL-4.



Similar to Hydraulic Oil Additive Package, Air Compressor Oil Additive Package, Railway Oil Additive Package, ect., Gear Oil Additive Package is also a industrial Additive Package.

### ●Recommended Treat Rate

APL GL-5	4.2
APL GL-4	2.1
High Load Carrying	1.6
Low/Mid Load Carrying	1.2

Net Weight: 200 Kgs/Drum

Storage and Transportation:Non-dangerous goods, store in dry, cool ventilated area.

### ●Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Kinematic Viscosity, 100℃, mm <sup>2</sup> /s	Report	ASTMD445
Appearance	Yellow Liquid	Visual
Sulfur, wt%	30-35	ASTMD5185
Phosphorus, wt%	1.2-1.6	ASTMD5185