



ZHENGZHOU CHORUS COMMERCE AND TRADE CO.,LTD

Email: [eilin@cn-lubricantadditive.com](mailto:eilin@cn-lubricantadditive.com); Web: [www.cn-lubricantadditive.com](http://www.cn-lubricantadditive.com)

Add: No. 11 Changchun Road, Zhengzhou, China; Tel: +86-371-58651986, 18339818406

---

### Automotive GL-4 GL-5 Gear Oil Additive Package

#### ●Product Introduction

T4206 have excellent high-temp antioxidant, anti-corrosion, antifoaming, demulsibility. It can prolong the service life of gear teeth and bearing, lower filter blocking. This product is suitable for blending gear oils that conform to the API GL-4, GL-5. Contains no metallic elements, soluble in I, II base oils and PAO.

#### ●Recommended Dosage:

API Performance Level	Treating Rate (mass%)
GL-5	4.2%
GL-4	2.1%
High Load-carrying	1.6%
Low, Mid Load-carrying	1.2%

#### ●Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Yellow Liquid	Visual
Kinematic Viscosity (100°C), mm <sup>2</sup> /s	Report	ASTM D445
Sulphur, wt%	31	ASTM D5185
Phosphorus, wt%	1.69	ASTM D5185

#### ●Product Storage/Handling/Transportation/Package

It is packed 200KG in each drum.

The storage, transport and production should meet the requirement of SH/T0164.

The maximum temperature should not exceed 75°C, for long-term storage, the maximum temperature should not exceed 45°C. The product is not flammable, explosive, and corrosive. Its safety cause, environmental protection and usage may refer the general procedures for the common petroleum products.