

Prop(inch)	Voltage(V)	Current(A)	Input power(W)	Speed (rpm)	Torque (N.m)	Output power(W)	Thrust(gf)	Efficiency (%)	Force effect(g/W)	Load temperature in 100% throttle
EOLO CN26* 8	44.66	1.396	62.76	1371.7	0.34	48.83	1012.55	77.8	16.13	107°C 5min
	44.64	1.798	80.8	1513.33	0.41	64.97	1239.36	80.4	15.33	
	44.65	2.307	103.69	1648.82	0.49	84.59	1486.46	81.57	14.33	
	44.63	2.856	128.32	1778.05	0.57	106.12	1721.64	82.69	13.41	
	44.63	3.547	159.36	1917.27	0.65	130.49	2006.76	81.88	12.59	
	44.6	4.267	191.58	2060.4	0.75	161.81	2258.68	84.46	11.78	
	44.59	4.975	223.32	2176.73	0.83	189.18	2526.15	84.71	11.31	
	44.57	5.724	256.83	2275.5	0.91	216.82	2705.68	84.42	10.53	
	44.58	6.509	292.12	2380.24	0.98	244.25	2875.59	83.61	9.84	
	44.54	8.218	368.49	2565.54	1.14	306.25	3530.98	83.1	9.58	
	44.51	10.118	453.38	2741.82	1.3	373.23	4046.63	82.32	8.92	
	44.49	12.244	548.4	2904.5	1.46	444.03	4542.35	80.96	8.28	
	44.35	17.466	779.85	3248.22	1.85	629.23	5676.27	80.68	7.27	
	50.05	1.208	60.46	1341.34	0.34	47.75	996.08	78.97	16.47	
	50	1.615	80.75	1509.44	0.42	66.38	1220.66	82.2	15.11	
	50.02	2.111	105.59	1645.06	0.49	84.4	1501.6	79.93	14.22	
	49.99	2.68	133.97	1807.19	0.58	109.75	1757.31	81.92	13.11	
	50.01	3.301	165.08	1948.83	0.68	138.76	2033.85	84.05	12.32	
	49.97	3.87	193.38	2067.73	0.75	162.38	2278.3	83.96	11.78	
	49.99	4.578	228.85	2186.8	0.83	190.05	2617.88	83.04	11.43	
	49.94	5.317	265.53	2305.27	0.92	222.07	2787.91	83.63	10.49	
	49.94	5.917	295.49	2385.61	0.99	247.3	3040.01	83.69	10.28	
	49.9	7.412	369.85	2555.72	1.16	310.43	3528.12	83.93	9.53	
	49.88	8.721	435	2687.2	1.28	360.16	3949.78	82.79	9.07	
49.8	10.813	538.48	2874.73	1.47	442.49	4513.45	82.17	8.38		
49.79	12.719	633.27	3028.38	1.63	516.88	5013	81.62	7.91		
49.75	15.379	765.1	3187.66	1.8	600.81	5613.5	78.52	7.33		
49.65	20.306	1008.19	3472.22	2.1	763.52	6545.98	75.73	6.49		
EOLO CN28* 9.5	44.83	1.28	57.51	1223.64	0.33	42.28	985.9	73.51	17.14	112°C 2min
	44.8	1.787	80.21	1385.21	0.42	60.92	1285.99	75.95	16.03	
	44.8	2.234	100.3	1509.11	0.49	77.43	1476.41	77.19	14.71	
	44.78	2.814	126.29	1636.88	0.58	99.41	1733.4	78.71	13.72	
	44.76	3.45	154.76	1761.23	0.67	123.56	2032.73	79.83	13.13	
	44.76	4.207	188.72	1899.66	0.77	153.16	2328.36	81.15	12.33	
	44.75	4.858	217.88	2002.31	0.83	174.02	2548.5	79.86	11.69	
	44.74	5.414	242.76	2070.08	0.9	195.08	2774.19	80.35	11.42	
	44.74	6.254	280.42	2166.42	0.99	224.58	2952.98	80.08	10.53	
	44.78	7.906	354.03	2355.18	1.15	283.6	3572.07	80.1	10.08	
	44.74	9.889	442.43	2522.69	1.34	353.96	4137.48	80	9.35	
	44.62	11.575	517.63	2657.8	1.48	411.88	4536.04	79.57	8.76	
	44.57	13.679	611.04	2793.54	1.64	479.72	5078.24	78.5	8.31	
	44.48	18.602	829.27	3078.58	1.95	628.61	6061.29	75.8	7.3	
	50.04	1.157	57.89	1225.71	0.31	39.78	1001.41	68.71	17.29	
	50.04	1.565	78.31	1372.4	0.4	57.48	1248.16	73.4	15.93	
	50.04	2.037	101.93	1517.65	0.49	77.86	1503.75	76.38	14.75	
	50.04	2.61	130.6	1649.86	0.57	98.47	1758.38	75.39	13.46	
	50.03	3.281	164.14	1799.62	0.67	126.25	2095.5	76.91	12.76	
	50.03	4.278	214.02	1976.47	0.81	167.63	2551.07	78.32	11.91	
	50.01	5.245	262.3	2128.04	0.91	202.77	2883.37	77.3	10.99	
	49.99	5.803	290.09	2199.29	1.02	234.89	3131.66	80.97	10.79	
	49.96	7.041	351.76	2347.56	1.16	285.14	3595.02	81.06	10.22	
	49.91	8.665	432.47	2515.02	1.32	347.62	4030.16	80.38	9.31	
49.9	10.458	521.85	2658.37	1.49	414.76	4570.38	79.47	8.75		
49.84	12.376	616.81	2806.14	1.64	481.89	5030.17	78.12	8.15		
49.85	14.451	720.38	2940.35	1.79	551.12	5538.5	76.5	7.68		
49.74	16.771	834.18	3071.45	1.97	633.58	6080.33	75.95	7.28		
49.62	21.135	1048.71	3309.74	2.23	772.85	6845.47	73.69	6.52		
	44.67	1.378	61.83	1230	0.38	48.94	1029.93	79.15	16.65	
	44.65	1.757	78.8	1361.2	0.45	64.14	1234.68	81.39	15.66	
	44.66	2.245	100.71	1491.21	0.52	81.19	1479.67	80.61	14.69	
	44.63	2.783	124.76	1615.16	0.6	101.47	1731.59	81.33	13.87	
	44.64	3.437	154.11	1746.41	0.7	128	2009.56	83.05	13.03	
	44.61	4.218	189	1875.79	0.79	155.17	2307.17	82.1	12.2	
	44.59	4.904	219.65	1976.28	0.89	184.17	2630.75	83.84	11.97	

EOLO 28*9.5	44.58	5.347	239.43	2046.73	0.92	197.17	2706.65	82.34	11.3	117°C 2min
	44.57	6.177	276.54	2145.41	1.01	226.89	3100.94	82.04	11.21	
	44.51	8.175	365.5	2369.72	1.23	305.21	3557.85	83.5	9.73	
	44.5	9.555	427.1	2483.76	1.36	353.7	4047.16	82.81	9.47	
	44.58	11.618	519.09	2633.52	1.51	416.39	4555.87	80.21	8.77	
	44.53	13.669	610.04	2769.9	1.65	478.56	4989.85	78.44	8.17	
	44.41	19.106	850.4	3070.98	2.03	652.78	6142.68	76.76	7.22	
	50.08	1.255	62.85	1238.28	0.39	50.56	1033.08	80.44	16.43	
	50.13	1.677	84.06	1387.08	0.47	68.26	1303.44	81.2	15.5	
	50.18	2.164	108.58	1533.88	0.55	88.33	1565.02	81.35	14.41	
	50.15	2.607	130.74	1644.31	0.63	108.47	1767.28	82.96	13.51	
	50.16	3.11	155.99	1749.71	0.7	128.25	2020.94	82.21	12.95	
	50.13	3.632	182.07	1846.42	0.77	148.87	2257.08	81.76	12.39	
	50.13	4.282	214.65	1958.66	0.87	178.43	2508.2	83.12	11.68	
	50.06	4.942	247.39	2070.11	0.95	205.92	2799.72	83.23	11.31	
	50.05	5.817	291.14	2178.73	1.04	237.26	3067.7	81.49	10.53	
	50.03	6.986	349.5	2324.8	1.18	287.25	3695.4	82.18	10.57	
	50.02	8.665	433.42	2492.12	1.36	354.89	4045.07	81.88	9.33	
	50.01	10.422	521.2	2639.23	1.5	414.53	4486.28	79.53	8.6	
	49.96	11.944	596.72	2760.65	1.66	479.86	4958.56	80.41	8.3	
49.94	14.101	704.2	2898.73	1.8	546.35	5458.84	77.58	7.75		
49.85	16.3	812.55	3028.28	1.98	627.85	5924.99	77.26	7.29		
49.79	22.117	1101.2	3289.02	2.31	795.56	6964.63	72.24	6.32		

Prop(inch)	Voltage (V)	Current(A)	Input power (W)	Speed (rpm)	Torque (N.m)	Output power(W)	Thrust(gf)	Efficiency (%)	Force effect(g/W)	Load temperature in 100% throttle
EOLO CN26*8	45	1.478	66.51	1389.53	0.29	42.19	1028.83	63.43	15.46	117°C 30s
	45.01	1.89	85.06	1534.65	0.35	56.24	1249.14	66.11	14.68	
	44.96	2.455	110.37	1684.98	0.44	77.63	1504.3	70.33	13.62	
	44.97	3.104	139.58	1837.06	0.52	100.02	1773.42	71.65	12.7	
	44.95	3.7	166.31	1964.13	0.61	125.45	2014.84	75.43	12.11	
	44.93	4.358	195.8	2088.05	0.68	148.67	2288.63	75.92	11.68	
	44.9	5.111	229.48	2206.16	0.76	175.56	2563.9	76.5	11.17	
	44.9	6.041	271.24	2327.96	0.89	216.95	2938.1	79.98	10.83	
	44.81	8.187	366.85	2559.89	1.1	294.85	3539.27	80.37	9.64	
	44.78	9.634	431.41	2708.46	1.23	348.83	3934.55	80.85	9.12	
	44.71	12.017	537.28	2914.24	1.42	433.32	4488.91	80.65	8.35	
	44.69	14.371	642.23	3070.79	1.58	508.04	5044.96	79.1	7.85	
	44.63	16.77	748.44	3220.77	1.75	590.19	5526.16	78.85	7.38	
	44.55	20.15	897.68	3382.52	1.95	690.67	6160.69	76.93	6.86	
	44.45	26.3	1169.03	3622.61	2.25	853.49	7093.13	73	6.06	
	50.05	1.331	66.61	1381.51	0.3	43.39	1027.53	65.14	15.42	
	50.02	1.707	85.38	1532.59	0.38	60.98	1257.05	71.42	14.72	
	50.02	2.13	106.54	1668.41	0.44	76.86	1471.16	72.14	13.8	
	50	2.807	140.34	1830.56	0.55	105.42	1791.79	75.11	12.76	
	50	3.389	169.44	1965.87	0.63	129.68	2075.67	76.53	12.25	
	49.99	3.794	189.66	2059.08	0.69	148.77	2232.31	78.44	11.77	
	49.97	4.608	230.26	2190.21	0.79	181.17	2560.05	78.68	11.11	
	49.94	5.173	258.33	2282.1	0.87	207.89	2747.94	80.47	10.63	
	49.94	5.791	289.2	2381.65	0.93	231.93	3064.82	80.19	10.59	
	49.91	7.628	380.71	2598.32	1.12	304.72	3587.67	80.03	9.42	
49.86	9.239	460.65	2763.39	1.27	367.48	4064.63	79.77	8.82		
49.83	10.885	542.39	2907.46	1.41	429.26	4510.82	79.14	8.31		
49.79	12.689	631.78	3046.24	1.57	500.79	4962.61	79.26	7.85		
49.75	15.181	755.25	3205.42	1.74	584.02	5539.28	77.32	7.33		
49.68	17.335	861.2	3327.22	1.91	665.44	6006.16	77.26	6.97		
49.64	20.98	1041.44	3507.09	2.12	778.53	6654.37	74.75	6.38		
49.38	30.376	1499.96	3844.73	2.57	1034.65	7984.3	68.97	5.32		
EOLO CN28*9 .5	44.85	1.274	57.26	1257.79	0.31	40.82	1004.59	71.28	17.54	110°C 30s
	44.86	1.743	78.36	1419.2	0.41	60.92	1262.2	77.74	16.1	
	44.84	2.191	98.46	1536.25	0.48	77.21	1496.57	78.41	15.19	
	44.84	2.692	120.97	1653.48	0.55	95.22	1712.5	78.71	14.15	
	44.83	3.237	145.43	1771.37	0.63	116.85	1975.82	80.34	13.58	
	44.81	4.041	181.48	1914.34	0.73	146.33	2280.44	80.63	12.56	
	44.79	4.731	212.37	2031.41	0.82	174.42	2549.51	82.13	12	
	44.77	5.371	240.99	2119.02	0.9	199.69	2753.59	82.86	11.42	
	44.77	5.948	266.88	2201.57	0.95	219	2969.13	82.05	11.12	
	44.83	7.664	343.57	2393.23	1.13	283.17	3546.25	82.41	10.32	
	44.68	9.674	433.2	2578.04	1.32	356.33	4109.92	82.25	9.48	
	44.64	11.682	522.65	2754.4	1.48	426.85	4574.8	81.67	8.75	
	44.61	13.528	604.83	2874.43	1.62	487.59	5061.2	80.61	8.36	
	44.55	15.812	706	3016.75	1.78	562.28	5512.44	79.64	7.8	
	44.52	18.095	807.39	3136.57	1.91	627.31	5978.44	77.69	7.4	
	44.48	20.624	919.41	3265.74	2.03	694.18	6379.4	75.5	6.93	
	44.38	27.902	1238.29	3600.67	2.48	935.04	7705.21	75.51	6.22	
	50.03	1.12	56.03	1241.34	0.31	40.29	985.22	71.9	17.58	
	49.98	1.565	78.21	1416.68	0.41	60.82	1262.41	77.76	16.14	
	50	1.985	99.25	1553.43	0.48	78.07	1505.69	78.65	15.17	
50.03	2.481	124.12	1693.27	0.56	99.29	1762.04	79.99	14.19		
50	3.079	153.95	1815.16	0.66	125.44	2042.79	81.48	13.26		
49.98	3.68	183.92	1938.39	0.74	150.19	2349.02	81.66	12.77		
49.99	4.39	219.45	2067.92	0.83	179.72	2586.79	81.89	11.78		
49.96	4.96	247.8	2156.61	0.91	205.49	2838	82.92	11.45		
49.96	5.24	261.79	2208.48	0.94	217.37	2914.83	83.03	11.13		

	49.94	7.013	350.22	2414.2	1.13	285.65	3534.01	81.56	10.09	
	49.88	8.557	426.82	2585.15	1.3	351.9	4033.87	82.44	9.45	
	49.86	10.279	512.51	2738.81	1.46	418.7	4553.18	81.69	8.88	
	49.84	12.01	598.57	2885.32	1.6	483.4	4980.31	80.75	8.32	
	49.78	14.461	719.86	3048.14	1.79	571.32	5543.45	79.36	7.7	
	49.73	16.7	830.49	3180.85	1.94	646.16	6095.86	77.8	7.34	
	49.71	18.761	932.6	3300.72	2.05	708.53	6448.89	75.97	6.91	
	49.64	22.277	1105.83	3427.75	2.25	807.58	7018.04	73.02	6.34	
	49.42	31.111	1537.5	3732.93	2.63	1028.02	8198.04	66.86	5.33	
EOLO C28*9.5	44.79	1.281	57.37	1246.98	0.28	36.56	1018.35	63.72	17.75	120°C 20s
	44.81	1.752	78.5	1411.23	0.37	54.67	1247.58	69.64	15.89	
	44.82	2.2	98.6	1528.61	0.44	70.42	1489.16	71.41	15.1	
	44.79	2.838	127.11	1676.57	0.53	93.04	1762.28	73.19	13.86	
	44.81	3.422	153.33	1800.09	0.6	113.09	2039.8	73.75	13.3	
	44.8	4.009	179.6	1908.82	0.68	135.91	2279.69	75.67	12.69	
	44.79	4.745	212.52	2027.91	0.76	161.38	2553.49	75.93	12.01	
	44.78	5.37	240.46	2107.9	0.86	189.82	2764.81	78.94	11.49	
	44.76	6.348	284.13	2231.38	0.98	228.97	3044.93	80.58	10.71	
	44.72	7.741	346.17	2382.05	1.13	281.85	3446.73	81.41	9.95	
	44.69	9.639	430.76	2563.5	1.3	348.95	4002.77	81	9.29	
	44.64	11.764	525.14	2735.93	1.48	423.99	4541.93	80.73	8.64	
	44.6	13.778	614.49	2857.28	1.64	490.67	5052.79	79.84	8.22	
	44.58	15.999	713.23	2988.19	1.76	550.7	5459.44	77.21	7.65	
	44.51	18.743	834.25	3130.7	1.93	632.69	6000.25	75.83	7.19	
	44.32	28.441	1260.5	3553.49	2.48	922.79	7638.91	73.2	6.06	
	50.08	1.344	67.3	1289.03	0.34	45.89	1012.51	68.18	15.04	
	50.03	1.69	84.55	1411.54	0.42	62.07	1236.25	73.41	14.62	
	50.06	2.144	107.32	1550.06	0.49	79.53	1483.36	74.1	13.82	
	50.02	2.617	130.9	1683.06	0.57	100.45	1708.5	76.73	13.05	
	50.02	3.222	161.16	1812.01	0.66	125.22	1999.34	77.69	12.4	
	50	3.808	190.39	1930.13	0.75	151.58	2256.63	79.61	11.85	
	49.95	4.608	230.16	2059.56	0.87	187.62	2612.33	81.51	11.35	
	49.96	5.12	255.79	2149.4	0.92	207.06	2839.29	80.94	11.1	
	49.95	5.738	286.61	2237.3	1	234.27	2898.5	81.73	10.11	
	49.94	7.236	361.36	2408.15	1.17	295.02	3573.33	81.64	9.88	
	49.89	8.85	441.52	2568.9	1.32	355.07	3993.02	80.41	9.04	
	49.88	10.568	527.13	2730.62	1.47	420.31	4529.65	79.73	8.59	
	49.81	12.552	625.21	2865.07	1.66	498.01	5052.86	79.65	8.08	
	49.77	14.532	723.25	3002.1	1.79	562.69	5534.99	77.8	7.65	
	49.74	16.627	827.02	3115.2	1.94	632.82	5918.12	76.51	7.15	
	49.67	19.899	988.38	3286.7	2.13	733.05	6524.87	74.16	6.6	
49.62	22.503	1116.59	3384.16	2.26	800.85	6947.33	71.72	6.22		
48.97	32.478	1590.44	3742.79	2.76	1081.68	8433.21	68.01	5.3		

Prop(inch)	Voltage(V)	Current(A)	Input power(W)	Speed (rpm)	Torque (N.m)	Output power(W)	Thrust (gf)	Efficiency (%)	Force effect (g/W)	Load temperature in 100% throttle
EOLO C28*9.5	22.45	2.708	60.79	1274.32	0.38	50.7	1033.49	83.4	17	71°C
	22.46	3.302	74.16	1380.93	0.43	62.17	1198.62	83.83	16.16	
	22.45	4.444	99.76	1548.08	0.52	84.29	1465.94	84.49	14.69	
	22.43	5.781	129.7	1702.28	0.62	110.51	1781.8	85.23	13.74	
	22.4	7.154	160.2	1831.16	0.71	136.13	2065.11	84.95	12.88	
	22.37	8.232	184.1	1937.68	0.77	156.23	2256.17	84.84	12.25	
	22.33	9.842	219.8	2049.15	0.87	186.67	2522.59	84.93	11.47	
	22.31	11.26	251.3	2135.16	0.95	212.39	2827.11	84.52	11.25	
	22.18	17.1	379.2	2439.82	1.24	316.79	3726.76	83.55	9.82	
	24.9	2.434	60.6	1286.31	0.35	47.14	1006.68	77.78	16.61	
	24.89	3.243	80.71	1426.71	0.43	64.23	1251.7	79.58	15.5	
	24.86	4.264	106	1578.16	0.52	85.93	1514.23	81.06	14.28	
	24.84	5.081	126.2	1687.2	0.59	104.23	1712.68	82.58	13.57	
	24.81	6.473	160.6	1834.31	0.69	132.53	2039.98	82.52	12.7	
	24.8	7.38	183	1921.67	0.75	150.91	2261.82	82.45	12.35	
	24.78	8.645	214.2	2016.89	0.84	177.4	2449.9	82.81	11.43	
	24.72	11.47	283.6	2222.74	1.02	237.4	2796.64	83.7	9.86	
24.67	13.36	329.6	2336.52	1.12	274.02	3274.61	83.14	9.93		
24.55	19.71	483.8	2635.15	1.42	391.82	4278.78	80.98	8.84		
EOLO CN28*9.5	22.51	2.575	57.96	1289.49	0.36	48.6	1009.37	83.85	17.41	70°C
	22.47	3.772	84.75	1481.97	0.47	72.93	1322.25	86.05	15.6	
	22.45	4.719	105.9	1608.3	0.54	90.94	1555.72	85.84	14.68	
	22.44	5.865	131.6	1739.05	0.62	112.9	1803.28	85.78	13.7	
	22.39	7.157	160.2	1868.82	0.7	136.98	2078.41	85.48	12.97	
	22.38	8.103	181.3	1949.57	0.76	155.14	2266.99	85.55	12.5	
	22.37	9.38	209.8	2039.13	0.84	179.35	2481.45	85.47	11.82	
	22.34	11	245.8	2149.63	0.93	209.33	2771.97	85.16	11.27	
	22.21	16.61	368.8	2466.72	1.2	309.95	3557.68	84.03	9.64	
	22.26	16.62	369.8	2464.19	1.16	299.31	3582.63	80.92	9.68	
	25	2.359	58.97	1296.59	0.34	46.16	1011.32	78.27	17.14	
	24.99	3.297	82.39	1465.7	0.43	65.99	1273.77	80.09	15.46	
	24.95	4.004	99.89	1568.03	0.49	80.45	1429.81	80.53	14.31	
	24.95	5.046	125.9	1704.26	0.58	103.5	1736.84	82.21	13.79	
	24.93	6.317	157.5	1849.79	0.68	131.71	2017.96	83.63	12.81	
	24.91	7.184	179	1936.35	0.75	152.06	2188.29	84.97	12.22	
	24.89	8.459	210.5	2043.62	0.82	175.47	2476.46	83.34	11.76	
24.87	10.22	254.1	2172.14	0.93	211.52	2744.44	83.22	10.79		
24.86	11.33	281.6	2245.75	0.99	232.8	3001.17	82.68	10.65		
24.71	19.47	481	2666.63	1.39	388.12	4240.47	80.69	8.81		

Prop(inch)	Voltage (V)	Current(A)	Input power(W)	Speed (rpm)	Torque (N.m)	Output power(W)	Thrust (gf)	Efficiency (%)	Force effect(g/W)	Load temperature in 100% throttle
EOLO C28*9.5	22.4	2.853	63.9	1270.2	0.34	45.22	1004.79	70.76	15.72	95°C 3min
	22.37	3.743	83.73	1415.18	0.42	62.23	1244.54	74.32	14.86	
	22.35	4.812	107.54	1560.75	0.49	80.08	1480.43	74.46	13.76	
	22.33	6.274	140.09	1695.63	0.6	106.53	1794.21	76.04	12.8	
	22.31	7.452	166.25	1834.99	0.68	130.65	2031.72	78.58	12.22	
	22.27	8.92	198.64	1954.93	0.77	157.62	2296.09	79.34	11.55	
	22.23	10.592	235.46	2099.87	0.86	189.09	2547.01	80.3	10.81	
	22.2	12.589	279.47	2170.12	0.96	218.14	2978.01	78.05	10.65	
	22.09	17.684	390.63	2427.43	1.17	297.39	3455.52	76.13	8.84	
	22.01	21.152	465.55	2550.07	1.33	355.14	4011.68	76.28	8.61	
	21.85	29.581	646.34	2842.84	1.61	479.26	4927.69	74.14	7.62	
	24.89	2.716	67.6	1287.79	0.36	48.54	1064.47	71.8	15.74	
	24.88	3.408	84.79	1415.78	0.43	63.74	1251.12	75.17	14.75	
	24.88	4.341	108	1546.87	0.5	80.98	1493.91	74.98	13.83	
	24.85	5.443	135.25	1673.81	0.58	101.65	1739.39	75.15	12.86	
	24.81	6.531	162.03	1806.16	0.67	126.71	1999.18	78.2	12.33	
	24.79	7.68	190.38	1905.3	0.74	147.63	2255.29	77.54	11.84	
	24.78	9.217	228.39	2069.86	0.83	179.89	2548.92	78.76	11.16	
	24.74	10.659	263.7	2169.94	0.93	211.31	2885.18	80.13	10.94	
	24.7	11.984	296	2263.72	0.99	234.66	3055.2	79.27	10.32	
	24.63	15.454	380.63	2439.52	1.16	296.31	3524.56	77.84	9.25	
	24.59	17.482	429.88	2548.74	1.25	333.6	3779.57	77.6	8.79	
24.48	22.525	551.41	2745.76	1.46	419.77	4521.74	76.12	8.2		
24.38	27.291	665.35	2904.89	1.64	498.85	4988.96	74.97	7.49		
24.25	33.798	819.6	3089.97	1.82	588.87	5613.88	71.84	6.84		
EOLO CN28*9.5	22.5	2.783	62.61	1292.19	0.33	44.65	1011.29	71.31	16.15	100°C 3min
	22.48	3.801	85.44	1455.59	0.42	64.01	1301.68	74.91	15.23	
	22.46	4.773	107.2	1565.54	0.5	81.96	1504.75	76.45	14.03	
	22.43	5.792	129.91	1685.91	0.57	100.62	1754.86	77.45	13.5	
	22.4	7.003	156.86	1808.87	0.66	125.01	2018.07	79.69	12.86	
	22.38	8.446	189.02	1934.17	0.73	147.84	2267.03	78.21	11.99	
	22.33	10.141	226.44	2054.94	0.84	180.74	2572.04	79.81	11.35	
	22.25	12.813	285.08	2229.27	0.98	228.76	3014.61	80.24	10.57	
	22.19	16.455	365.13	2401.97	1.15	289.24	3516.63	79.21	9.63	
	22.1	20.496	452.96	2562.82	1.31	351.54	4041.8	77.6	8.92	
	21.94	29.191	640.45	2873.43	1.59	478.4	4972.47	74.69	7.76	
	24.95	2.591	64.64	1319.92	0.35	48.37	1052.4	74.82	16.28	
	24.94	3.28	81.8	1436.1	0.41	61.65	1219.12	75.36	14.9	
	24.92	4.383	109.22	1600.67	0.5	83.8	1517.67	76.72	13.89	
	24.89	5.47	136.14	1734.86	0.59	107.17	1792.1	78.72	13.16	
	24.87	6.678	166.08	1865.18	0.68	132.8	2063.35	79.96	12.42	
	24.84	7.821	194.27	1964.06	0.76	156.3	2343.65	80.45	12.06	
	24.79	9.011	223.38	2074.36	0.83	180.28	2508.16	80.7	11.22	
	24.78	9.913	245.64	2133.52	0.87	194.36	2694.76	79.12	10.97	
	24.75	11.975	296.38	2263.14	0.99	234.6	3091.12	79.15	10.42	
24.66	15.033	370.71	2445.73	1.15	294.51	3557.53	79.44	9.59		
24.62	18.518	455.91	2602.08	1.3	354.2	4015.23	77.69	8.8		
24.51	22.775	558.21	2779.44	1.49	433.65	4556.31	77.68	8.16		
24.42	27.043	660.39	2923.42	1.65	505.09	5016.53	76.48	7.59		
24.3	33.413	811.93	3111.7	1.85	602.79	5711.31	74.24	7.03		