



SHENZHEN GMAII TECHNOLOGY CO., LTD

Android POS Solution Provider



Shenzhen Gmai Technology Co., Ltd

Shenzhen Gmai Technology Co., Ltd is a high-tech enterprise integrating R&D, production, sales and service of mobile POS terminals, smart POS terminals, smart cashier terminals, self-service terminals and payment system software solutions with well-equipped testing facilities and strong technical force, After more than ten years of development, it has become a world-leading supplier of complete electronic payment solutions.

With a wide range, good quality, reasonable prices and stylish designs, our products are extensively used in catering, retail, commercial, hotel, e-commerce, logistics, medical, mobile and other industries.

Our products are widely recognized and trusted by users and can meet continuously changing economic and social needs.

We welcome new and old customers from all walks of life to contact us for future business relationships and mutual success!




JOIN IN COOPERATION

ANDROID POS SOLUTION PROVIDER

Distribution of Cooperators

Gmai is a well-known pos system supplier that integrates R&D, design, production and sales. We are committed to provide users with Intelligence and convenient pos solution, Let's work for this vision together!





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S10	
Version	Dual Touch Screen	
CPU	ARM 8 Core Cortex-A7 CPU, 2.0GHz	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	12.5 inch , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	12.5 inch , Resolution 1920x1080 DPI	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non / Addible	
Network Connection	100M Ethernet ; Wi-Fi , 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 6KG	Net Weight : 5.5KG
Size(mm)	Package : 425 (L) x375 (W) x415 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S15	
Version	Dual Touch Screen	
CPU	ARM 8 Core Cortex-A7 CPU, 2.0GHz	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	12.5 inch , Resolution 1920x1080 DPI	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Membership Card Reader Inside	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7.5KG	Net Weight : 7KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S15D	
Version	One Touch Screen	
CPU	ARM 8 Core Cortex-A7 CPU, 2.0GHz	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch , Resolution 1366x786 or 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	Digital Display	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Membership Card Reader Inside	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7KG	Net Weight : 6.5KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmail Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S16	
Version	One Touch Screen	
CPU	ARM 8 Core Cortex-A7 CPU, 2.0GHz	
Operating System	Android 7.0	
Memory	2G RAM + 8G ROM	
Main Screen	10.1 inch , Resolution 1280x800 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	Digital Display	
Certifications	CE, RoHS, FCC	
Extend	Support, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Membership Card Reader Inside	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Speaker Inside UV , Banknote Lamp Inside	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 3.3KG	Net Weight : 2.8KG
Size(mm)	Package : 410 (L) x255 (W) x225 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




NON TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S21	
Version	Non Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	
Memory	2G RAM + 8G ROM	
Main Screen	12.1 inch , Resolution 1920x1080 DPI	
Screen Type	Non Touch Screen	
Assistant Screen	Digital Display	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 6 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Package Included	Pos register*1 Thermal printer*1 Keyboard*1	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7.2KG	Net Weight : 6.7KG
Size(mm)	Package : 485 (L) x390 (W) x510 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




NON TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S22	
Version	Non Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	
Memory	2G RAM + 8G ROM	
Main Screen	12.1 inch , Resolution 1920x1080 DPI	
Screen Type	Non Touch Screen	
Assistant Screen	Digital Display	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 6 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio	
NFC	Membership Card Reader Inside	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Package Included	Pos register*1 Thermal printer*1 Keyboard*1	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 3.5KG	Net Weight : 3KG
Size(mm)	Package : 410 (L) x340 (W) x410 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




NON TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S22D	
Version	Non Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	
Memory	2G RAM + 8G ROM	
Main Screen	12.1 inch , Resolution 1920x1080 DPI	
Screen Type	Touch Screen	
Assistant Screen	Digital Display	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 6 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Package Included	Pos register*1 /58mm Thermal printer*1	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 3.5KG	Net Weight : 3KG
Size(mm)	Package : 410 (L) x340 (W) x410 (H)	
Pos Software	Gmail Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPORT DEVICE EXTEND

Model	GM-S24	
Version	Dual Screen with thermal printer inside	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	12 inch Touch Screen , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	12 inch , Resolution 1920x1080 DPI non touch	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 6.42KG	Net Weight : 5.92KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmail Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPORT DEVICE EXTEND

Model	GM-S24S	
Version	Dual Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	12 inch Touch Screen , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	12 inch , Resolution 1920x1080 DPI non touch	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 6KG	Net Weight : 5.5KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmail Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S26	
Version	Dual Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch , Resolution 1920x1080 DPI touch screen	
Screen Type	Capacitive Touch Screen	
Assistant Screen	11.6 inch , Resolution 1920x1080 DPI non touch	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Membership Card Reader Inside	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7KG	Net Weight : 6.5KG
Size(mm)	Package : 475 (L) x375 (W) x485 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S30	
Version	Single Touch Screen with 80mm thermal printer inside	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch , Resolution 1920x1080 DPI touch screen	
Screen Type	Digital Screen	
Assistant Screen	Non	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 2 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Support	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 6.5KG	Net Weight : 6.2KG
Size(mm)	Package : 500 (L) x300 (W) x490 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPORT DEVICE EXTEND

Model	GM-S31	
Version	Single Touch Screen with 80mm thermal printer inside	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	17 inch Resolution 1920x1080 DPI touch screen	
Screen Type	Capacitive Touch Screen	
Assistant Screen	17 inch Resolution 1920x1080 DPI non touch	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7.5KG	Net Weight : 7KG
Size(mm)	Package : 500 (L) x300 (W) x490 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S33	
Version	Single Touch Screen with 58mm thermal printer inside	
CPU	ARM 4 Core	
Operating System	Android 7.0	
Memory	1G RAM + 8G ROM / 2G RAM + 8G ROM	
Main Screen	15.6 inch , Resolution 1920x1080 DPI touch screen	
Screen Type	Capacitive Touch Screen	
Assistant Screen	10 inch non touch screen	
Certifications	CE, RoHS, FCC	
Extend	Support , cash drawer, barcode scanner	
Interface	1xPower , 2 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 12.5KG	Net Weight : 11KG
Size(mm)	Package : 600 (L) x550 (W) x450 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM




CAPACITIVE TOUCH SCREEN



SUPORT DEVICE EXTEND

Model	GM-S35	
Version	Dual Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch Touch Screen , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	15.6 inch , Resolution 1920x1080 DPI non touch	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 7.5KG	Net Weight : 7KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM





CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S35D	
Version	Dual Touch Screen	
CPU	ARM 4 Core	
Operating System	Android 7.0	Windows 7/ Window 10
Memory	2G RAM + 8G ROM	4G RAM + 32 ROM / 4G RAM + 64G ROM
Main Screen	15.6 inch Touch Screen , Resolution 1920x1080 DPI	
Screen Type	Capacitive Touch Screen	
Assistant Screen	Non	
Certifications	CE, RoHS, FCC	
Extend	Support electronic scale, thermal printer, cash drawer, kitchen printer, barcode scanner	
Interface	1xPower , 4 x USB , 1 x VGA ,1 x RJ45 , 1 x 3.5mm Audio, 1 x TF Card	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 6KG	Net Weight : 5.6KG
Size(mm)	Package : 560 (L) x400 (W) x430 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	





ARM CPU



CUSTOMIZED SYSTEM



CAPACITIVE TOUCH SCREEN



SUPPORT DEVICE EXTEND

Model	GM-S36	
Version	Single Touch Screen with 58mm thermal printer inside	
CPU	Quad core,1.3Ghz	
Operating System	Android 6.1	
Memory	2G RAM + 8G ROM	
Main Screen	5.5-inch 1280*720 IPS-LCD	
Camera	5MP, Flash, AF	
Printer	58MM thermal printer inside	
Dimensions	211*83*54 mm	
Speaker	0.7W	
Interface	1xMicro USB Debug Port, 1xSIM Card Slot, 1x4 Section Headphone Hole	
NFC	Non	
Network Connection	100M Ethernet ; Wi-Fi 2.4G/5G ; BT4.2/LE	
Speaker	Non	
Power adapter	Input : 100V~240V AC/50~60Hz/1.2A , Output : 19.0~20.0V DC/1.5A	
Weight(kg)	Gross Weight : 0.5KG	Net Weight : 0.4KG
Size(mm)	Package : 240 (L) x125 (W) x80 (H)	
Pos Software	Gmai Pos Software, CN/EN Multilingual	



APPLICATION IMAGE



GM-S10



GM-S15



GM-S15D



GM-S16

APPLICATION IMAGE



GM-S21



GM-S22



GM-S24



GM-S28

Model	GM-A02
Product Name	58mm Thermal Printer
Interface	USB
Printing Method	Direct thermal
Print Speed	70mm/Second
Paper Width	58mm
Color	Silver+Black
Font Size	ANK , Font A : 1.5×3.0mm (12×24 dot) Font B : 1.1×2.1mm (9×17 dot)
Print Order	Support ESC/POS order
Reliability	50KM
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ CODABAR/ITF/CODE93/CODE128
Paper Thickness	0.06~0.08mm
Resolution	203 dpi
Adaptor Input	AC 110V/220V,50~60Hz
Adaptor Output	DC 8.5V/3A
Printer Input	DC 8.5V/3A
Cash Drawer Output	DC 12V/1A
Work Environment	Temperature : 0~15°C , Humidity : 10~80%
Storage Environment	Temperature : -10~60°C , Humidity : 10~90%
Command	Compatible with ESC/POS
Weight(kg)	Gross Weight : 1.1 KG Net Weight : 0.88KG
Size(mm)	Package : 248 (L) x158 (W) x197 (H)



Model	GM-A08
Product Name	58mm Thermal Printer
Interface	USB
Printing Method	Direct thermal
Print Speed	70mm/Second
Paper Width	58mm
Color	White+Black
Font Size	ANK , Font A : 1.5×3.0mm (12×24 dot) Font B : 1.1×2.1mm (9×17 dot)
Print Order	Support ESC/POS order
Reliability	50KM
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ CODABAR/ITF/CODE93/CODE128
Paper Thickness	0.06~0.08mm
Resolution	203 dpi
Adaptor Input	AC 110V/220V,50~60Hz
Adaptor Output	DC 8.5V/3A
Cash Drawer Output	DC 12V/1A
Work Environment	Temperature : 0~15°C , Humidity : 10~80%
Storage Environment	Temperature : -10~60°C , Humidity : 10~90%
Weight(kg)	Gross Weight : 0.94KG Net Weight : 0.72KG
Size(mm)	Package : 248 (L) x158 (W) x197 (H)




Model	GM-A07
Product Name	58mm Thermal Printer for Kitchen
Print method	Line thermal
Print speed	90mm/sec
Paper width	57.5±0.5mm
Paper thickness	0.06~0.08mm
Print columns	576 dots per line or 512 dots per line
Resolution	203*203 dpi(Maximum)
Character size	ANK, Font A: 1.5x3.0mm(12x24dots) Font B: 1.1x2.1mm(9x17dots) Simplified/traditional Chinese: 24x24 dots
Command	50KM
Interface	3 interfaces together (USB + Serial + LAN), or Parallel or Serial or USB port optional
Cash drawer	DC 24V=1A
Black mark	Support
Kitchen print	Support
Cutter	1,000,000 times
Data receive buffer	64 KBytes
Work Environment	Temperature(0~45 Deg C), humidity(10~80%)
Storage Environment	Temperature(-10~60 Deg C), humidity(10~90%)
Weight(kg)	Gross Weight : 1.8KG Net Weight : 1.6KG
Size(mm)	Package : 242 (L) x158 (W) x199 (H)



Model	GM-A10
Product Name	80mm Thermal Printer
Interface	USB
Printing Method	Direct thermal
Print Speed	250mm/Second
Paper Width	72mm
Color	Silver+Black
Font Size	ANK: 12 x24 Chinese: 24 x 24
Print Order	Support ESC/POS order
Reliability	50KM
Auto Cutter	2,000,000 cuts
Emulation	ESC/POS
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ CODABAR/ITF/CODE93/CODE128
Paper Thickness	0.06~0.07mm
Resolution	203 dpi
Adaptor Input	AC 110V/220V,50~60Hz
Adaptor Output	DC 8.5V/3A
Printer Input	DC 8.5V/3A
Cash Drawer Output	DC 12V/1A
Work Environment	Temperature : 0~15°C , Humidity : 10~80%
Storage Environment	Temperature : -10~60°C , Humidity : 10~90%
Command	Compatible with ESC/POS
Weight(kg)	Gross Weight : 2.0 KG Net Weight : 1.6KG
Size(mm)	Package : 220 (L) x220 (W) x200 (H)



Model	GM-A11
Product Name	80mm Lable Printer
Interface	USB
Printing Method	Direct thermal
Print Speed	125mm/Second
Paper Width	104mm
Color	Silver
Font Size	19-114mm
Print Order	Support ESC/POS order
Reliability	30KM
Auto Cutter	Non
Emulation	ESC/POS
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ CODABAR/ITF/CODE93/CODE128
Paper Thickness	0.06~0.07mm
Resolution	203 dpi
Adaptor Input	AC 110V/220V,50~60Hz
Adaptor Output	DC 8.5V/3A
Printer Input	DC 8.5V/3A
Cash Drawer Output	DC 12V/1A
Work Environment	Temperature : 0~15°C , Humidity : 10~80%
Storage Environment	Temperature : -10~60°C , Humidity : 10~90%
Command	Compatible with ESC/POS
Weight(kg)	Gross Weight : 2.5 KG Net Weight : 2.2KG
Size(mm)	Package : 220 (L) x220 (W) x200 (H)



Model	GM-A09
Product Name	Barcode Scanner Box
Scan type	CMOS
Light source	5600K LEDs(illumination)
CPU	32-bit
Optical Resolution	640*480
Resolution	≥10mil/1mm(PCS90%,Code 39)
Scan tolerance	60CM/S
Depth of field	10mm-170mm
Scan mode	Auto sense, Command trigger
Scan angle	Roll360°,Pitch±65°,Skew±60°(PCS90%,Code 39, 10mil/0.25mm)
Print contrast signal	≥20%
Ambient light	Dark, indoor natural light
Decoding speed	180 times/s ±2%
Operating temperature	-20°C to 50°C
Storage temperature	-40°C to 70°C
Humidity	5% to 95%(non-condensing)
Drop Height	1.5m
Transport vibration Test	10H@125RPM
Color Depth	24 Bit
Weight(kg)	Gross Weight : 0.27KG Net Weight : 0.22KG
Size(mm)	Package : 130 (L) x128 (W) x92 (H)



Model	GM-A04
Product Name	Barcode Scanner
Light source	650 (visible laser)
Scan model	single line Bi-directional
Scan speed	300scan/sec
Resolution	4mil
Width of scan	5-30cm
Depth of scan	2-50cm
Scan angles	Roll30°,Pitch75°,Yaw65°
Decode capacity	Code39,Code 39Full ASCII,Code128Full ,ASCII,Codabar,Interleaved 2 of 5,Code93,MSI,Code11,ISBN,ISSN,china post code,UPC/EAN,UPC/EAN(include complement code),Code128,UCC/EAN128,etc
Interface	RS232,PS2,USB
Prompt	30% minimum
Material	ABS+PC
Power supply	DC 5V±5%
Current	Working: 50mA standby: 30mA
Laser security	DC 8.5V/3A
Temperature	Working: 0°C-50°C Storage :0°C-50°C
Humidity	Operating and Storage humidity 20%-85% (non-condensing)
Environment Luminance	Max.5,000 Lux (flosrescence)
Certificate	CE,FCC,RoHS ,IP54
Weight(kg)	Gross Weight : 0.24KG Net Weight : 0.19KG
Size(mm)	Package : 235 (L) x140 (W) x88 (H)



Model	GM-A05/GM-A06
Product Name	Cash Drawer
Color	Black
Dimension	335(W)X368(D)X80(H)
Micro switch	Cash drawer status micro switch
Interface	RJ11/RJ12 ,RS-232,USB(optional)
Media slot	Double media slot
Lock	Three positions
Package	PE bag+Foam bag+Carton
Durability	1 millions operations
Voltage	6V,9V,12V,24V optional
Bill tray	Five position depth
Coin tray	Five position depth,Independently adjustable
Shell	0.8mm SPCC powder spray the surface of cold rolled plate
Floor	0.8mm SECC resistant fingerprint board
Material	Steel Construction Case,steel construction with painted front or stainless steel front
GM-A05 - Weight(kg)	Gross weight: 3.98KG; Net weight: 3.5KG
GM-A05 - Size(mm)	Package : 455(W)X395(L)X 145(H)MM
GM-A06 - Weight(kg)	Gross weight: 5.78KG; Net weight: 5.41KG
GM-A06 - Size(mm)	Package : 470(W)X460(L)X 150(H)MM

