



QS8001 Specification

Black mark detection	Support clearance label
print density	576 points / lines
Printed Line Width	24 Chinese/Line 48 English/Line Or 36 Chinese/Line 72 English/Line
Printing speed	70MM/S
Printing Content	English, numbers, various symbols, characters, pictures, 1D and 2D code printing ,different languages
Support System	Android,iOS,(Win9X/Win ME/Win2000/WinNT/WinXP/WinVista./Win7, Win8/Linux)
Instruction Set	ESC/POS Compatible Instruction Set
Build-in Font	ASCII Font library(12*24 8*16) GBK(24*24 16*16) (32*32 , 48*48)
Paper type	thermal paper /thermal label paper /label paper
Paper diameter	Maximum Φ39mm

Application Environment

Storage temperature	-20° to 70°C
Humidity	0 ~ 95% (Non Condensing)
Error warning	Paper deficiency/Paper barn door/Low electricity
Print width	Paper Width: 80MM Effective Printing Width : 72MM
Battery	Detachable 9V1.5A 1400mAh high performance lithium battery
Power adapter	Input AC 110-240V , output DC 9V/1.5A
Size(LxWxD)	120*100*50.5MM
Weight	650g

Communication

Bluetooth	Bluetooth 2.0/4.0
USB	USB2.0
Processor	M3 32 bit processor
Flash	2048Kb RAM
Printing method	Line type thermal printing

Accessories

www.qsprinter.com

SHENZHEN QUNSUO TECHNOLOGY CO., LTD



Box



Main frame



Thermal printer paper



Charger



USB cable



Instruction



Carry bag(optional)



Lable(optional)

Shenzhen Qunsuo Technology Co., LTD

Address: 4F C Building ,Fuxinlin Industrail Park ,Xixiang ,Bao' an,Shenzhen ,China

Web:www.qsprinter.com

Tel :0086-0755-61153535