

HUALI TECHNOLOGY CO., LTD.

Source manufacturer/cross-border factory/support oem/odm

Contact person: Ms Lucia

Cell phone: 0086-18686696586

WeChat/whatsapp: 0086-18686696586

www.jlhualitech.com

Email: huali01@ilhualitech.com

Product name: Electronic sphygmomanometer

Features

- Heart rate test, double 99 group memory
- WHO blood pressure classification, IHBarrhythmia detection
- Intelligent pressure, voltage and power detection,
- WHO blood pressure classification, human voice (optional)
- Intelligent color backlit display (optional)
- Product specifications
- Product size: 118mm×95mm×65mm
- ◆ Storage temperature: -20°C~50°C Storage humidity: 15%~90%
- Operating temperature: 10°C~40°C
 Operating humidity: 40%~85%
- Display: LCD digital display
- Measurement method: pulse scanning method/oscillometric method
- Measuring range: hypertension/hypotension:
 20mmHg~280mmHg
- ◆ Pulse: (40~200) beats/minute
- Resolution: 1mmHg (0.1kPa)
- Accuracy: ±3mmHg (±0.4kPa)
- Pulse: within ±3% of reading
- Voltage: 6V Power consumption: 0.01W



model	Specification	Box regulations
869	Regular	Color box volume: 10*8.4*15cm
869	English plus voice	Outer box volume: 51.5*36*32cm Weight: about 450 grams per unit, 30
	English plus voice backlight	units per carton, 12.5 kg per carton
Support multi	-language customization	

Product name: wrist sphygmomanometer

Features

- Heart rate test, double 99 group memory
- HB arrhythmia detection,
- WHO blood pressure classification
- Intelligent pressure, voltage and power detectionHuman voice (optional)

- Product size: 118mm×95mm×65mm(excluding wrist strap)
- ◆ Storage temperature: -20°C~50°C Storage humidity: 15%~90%
- Operating temperature: 10°C~40°C
 Operating humidity: 40%~85%
- Display: LCD digital display
- Measurement method: pulse scanning method/oscillometric method
- Measuring range: hypertension/hypotension: 20mmHg~280mmHg
- ◆ Pulse: (40~200) beats/minute
- Resolution: 1mmHg (0.1kPa)
- Accuracy: ±3mmHg (±0.4kPa)
- ◆ Pulse: within ±3% of reading
- Voltage: 3V Power consumption: 0.01W



model	Specification	Box regulations
	Regular	Color box volume: 11.8*9.5*6.5cm
	English plus voice	Outer box volume: 51.7*35*34cm Weight: about 450 grams per unit, 30
	English plus voice backlight	units per carton, 12.5 kg per carton
Support multi-language customization		

Product name: wrist sphygmomanometer

- Features
- ◆ Heart rate test, double 99 group memory
- IHB arrhythmia detection,
- WHO blood pressure classification
- Intelligent pressure, voltage and power detectionHuman voice (optional)

- ◆ Product size: 100×128mm×56mm
- ◆ Storage temperature: -20°C~50°C Storage humidity: 15%~90%
- Operating temperature: 10°C~40°C
 Operating humidity: 40%~85%
- Display: LCD digital display
- Measurement method: pulse scanning method/oscillometric method
- Measuring range: hypertension/hypotension: 20mmHg~280mmHg
- ◆ Pulse: (40~200) beats/minute
- Resolution: 1mmHg (0.1kPa)
- Accuracy: ±3mmHg (±0.4kPa)
- Pulse: within ±3% of reading
- ◆ Voltage: 6V Power consumption: 0.02W



Specification	Box regulations
Regular	Color box capacity: 118mm×95mm×65mm
English plus voice	Outer box volume: 55*42.5*34cm 20.5kg Weight: about 450 grams per piece, 50
English plus voice backlight	pieces per box, 20.5 kilograms per box

Product name: wrist sphygmomanometer

Features

- Double 99*2 groups of memory, LCD digital display
- Intelligent pressure, easy to carry
- Intelligent power saving, one-key measurement
- With voice (optional) +2 yuan
- Two colors available (black/white)

- Product size: 60*57*25mm (78*69*29mm)
- Host weight: about 110g (without battery)
- Package weight: about 216g (without battery)
- Display mode: LCD digital display
- Measurement method: oscillometric stepdown measurement
- Measurable wrist circumference: 13.5cm-19.5cm
- Measuring range: blood pressure (0-280) mmHg pulse (40-199)/min
- ◆ Allowable error value: blood pressure ± 3mmHg pulse ± 5%
- Number of memory groups: 99 groups of measurement results memory for two persons
- Working voltage: DC 3V (2 AAA batteries)



model	Specification	Box regulations
black	Regular	Host size: 60*57*25mm (78*69*29mm)
white	Regular models plus voice	Color box size: 12*9.5*9CM Carton size: 48*41*38.5CM Packing quantity: 60 sets/carton Net weight: 13kg .Gross weight: 14kg

thermometer

- Features:
- Humanized previous memory function
- Replaceable battery
- Buzzer prompt after measurement
- Hard head and soft head,
 Fahrenheit/Celsius optional
- ♦ Acrylic tube +0.3
- Soft head plus 0.3

- Product name: The electronic thermometer (non-medical) ships with a button battery by default
- Product size: 126x19x9MM
- Product bare metal weight: hard head 9.5g, soft head 9.6g
- Packing box size: 136x26x20MM,
- Package weight: 17g hard head, 17.7g soft head
- Default packaging: machine + PVC blister + English manual + color box
- ◆ Box gauge: 500PCS 48*31.5*29.5cm 10.3kg



model	Above 5000	Box regulations
Hard head	2.4	Product size: 126x19x9MM Packing box size:
Soft head	2.7	136x26x20MM, Box gauge: 500PCS
Acrylic tube +0.3, soft head plus 0.3, above 5000 can be customized Initial batch, logo monochrome +0.1		48*31.5*29.5cm 10.3kg

Product name: Non-contact human body thermometer

- Features
- The measurement is accurate, stable and reliable.
- Abnormal reminder, backlight distinction
- Memory function, °C/°F conversion
- Stable performance, no mercury
- Chinese and English versions are available
- Product specifications
- Ambient temperature: 16°C-35°C
- Atmospheric pressure: 70kPa-106kPa
- ♦ Humidity≤85%
- Power supply voltage: 3.0V DC (2 AA alkaline batteries)
- Size: 149 * 77 * 43mmWeight: 105g/131g
- Measuring range: body temperature mode: 32°C-42.9°C
- Measurement accuracy: 35.0-42.0°C: ±0.2°C; beyond the range of 35.0-42.0°C: ±0.3°C
- Measuring distance: 3-5 cm
- Measuring time: <2 seconds
- 3-color display: body temperature: 34.0-37.3°C green; 37.4-38°C yellow; 38.1-42.6°C red
- Automatic shutdown: 15 seconds
- Storage and transportation: -20°C-55°C, relative humidity: ≤93%



model	Box regulations
Chinese Version	Product size: 159*86*45mm 131g Product box gauge: 47*46*35CM
English version	Box gauge: 100PCS/box Weight: 13KG

Product name: Grid atomizer

Feature:

- Fine particles: large fog, fine atomized particles
- ◆ Fast speed: microporou spray sheet, fast atomization speed
- Mute: The low-noise design is quieter through piezoelectric components
- Less residue: chemical residue ≤0.5ml, economical to use
- Flashing light reminder: green light on means normal operation, red light on means battery is out of power or voltage is insufficient

- Product name: Grid atomizer
- ◆ 2. Residual amount of liquid medicine: ≤0.5mL
- ◆ 3. Atomization speed: ≥0.2ml/min
- 4. Atomized particles: 3~5μm
- 5. Medicine cup capacity: minimum about 0.5mL and maximum 8mL
- ◆ 6. Noise: ≤50dB (A)
- 7. Working frequency: 120KHz±10%
- 8. Power consumption: 2.0W
- 9. Power configuration: DC5V/1000mA USB power adapter cable or 2*1.5V (2 pieces of No. 5 AA alkaline, the product does not contain batteries)



Specification	Box regulations
blue	Product size: 45*45*100mm Color box size: 200*120*60mm
green	Carton size: 640*410*320mm Packing quantity: 50 sets Weight per box: 14kg
grey	
Nebulizer*1 Adapter*1 Adult mask*1 Child mask*1 Atomizing mouthpiece*1 Dust cover*1 Power adapter cable*1 Blister packaging (blue)*1 English user manual*1 Color box*1	

Manual sphygmomanometer

- Blood glucose meter
- ♦ 50 boxes/carton
- Gross weight: 7.46kg Net weight: 7kg
- ◆ Box gauge: 50.5cm*24.5cm*33cm
- Blood glucose test strips
- 200 boxes/carton
- Net weight: 8.6kg
- Gross weight: 9.36kg
- Box gauge 33cm*39.5cm*34cm
- 1 microliter capillary blood: 1uL blood sample
- Display the result within 7 seconds: 7 secords test time
- Free code: Auto coding
- Glucose oxidase method: GoD enzyme test strip
- Blood cell volume range: Hematocrit range 30%-55%
- Memory storage capacity: Memory-250 test results
- Automatic ejector: Test strip ejector
- Convenient query: 7.14.28 days average
- Personalized customization: Bluetooth(option)/ GPRS(option)



Multi-parameter monitor

- ◆ 12.1 inch TFT screen: high resolution: 800×600dpi
- Standard 6 parameters: ECG, SpO2, NIBP, TEMP, RESP, HR/PR
- Optional parameters: touch screen, 2-IBP, EtCO2, printer, etc.
- Patient range: adults only
- ◆ Packing information Packing size: 37*21*43cm
- Net weight/Gw: 6kg/7kg



Product name: manual sphygmomanometer

Product specifications:

Measuring range: 0-300mmHgAccuracy: +/-3mmHg(0.4kPa)

Minimum scale: 2mmHg

◆ Nylon strap, with D ring, 48*14 or 51*14cm

◆ Latex bag 22*12cm

Package:

Single color box, 50 pcs/cartonGross weight: 26.5KGS/ box

◆ Volume: 55*40*39cm/box



Feature:

 Aneroid sphygmomanometer with single head stethoscope

- Huali Technology Co., Ltd. is a company specializing in the production and processing of products and has a complete and scientific quality management system. The integrity, strength and product quality of Huali Technology Co., Ltd. have been recognized by the industry. Friends from all walks of life are welcome to visit, guide and negotiate business.
- We have extensive export experience. each month has fixed orders from Turkey, Pakistan, Taiwan, Indonesia, Malaysia, India, South Africa, South Korea, French, Greece, Italy, UK etc. High quality and excellent service make us earning high reputation.