

1042C 10.4" LCD

Open Android touch all-in-one

GreenTouch's 1042C 10.4" Open Android touch all-in-One PC is the integrated touch solution designed for automatic information systems, gaming and entertainment, as well as industrial Automation and control. the open frame touch all-in-one PC is made based on the idea 'designed for simple and convenience" and with the proven GreenTouch professionalism and reliability. The precise small frame design makes it easier for customers to install them product in the cabinet. Designed and built by GreenTouch, the model has a long life cycle and can offer long-term demands.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, the ultra-low power consumption and cost-effective ZC-3566 solution is recommended; the board integrates multimedia decoding, LCD driver, Ethernet, HDMI, WIFI, 3G, Bluetooth, supports most of the current popular video and picture format decoding, supports HDMI video output, TF card, which greatly simplifies the systemdesign of the whole machine; built-in speaker, 12V low-voltage power supply.

The all-in-one machine comes with a series of output connection ports, supporting various third-party peripheral devices. The standard ports include 2 standard USB ports, a 100 Mbps wired network card interface, and 1 3.5MM audio left and right channel output, 1 TF card, and 1 HDMI video output port, facilitating the addition of a second customer display.

A variety of industry-leading GreenTouch projected capacitive touch technologies is available. The model has global standard of agencies' certification and GreenTouch warranty and after-sales service, providing a cost-effective solution for industrial embedded systems integrators and value-added resellers (VARs).

- "Design for simple and convenience" the idea
- · Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen,various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001Quality Management System . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC,ROHS . The objective of GreenTouch is to become the most reliable supplier oftouch screen, high value-added and special touch products and touch solutions in the world.

Applications

- · Information Kiosk
- · Game and Entertainment
- · Industrial Automation
- · Self-checking service

Features

- Optional Motherboard Configuration inlcudes: ZC-3566
- Optional touch technologies include:

 Projected capacitive
- Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option
- · Worldwide agency approvals
- One year standard warranty





Specifications

Case/ frame color	Black			
Machine dimensions	261.64mm(W) x208.84mm(H),Thickness:47.5mm			
Display type	10.4" Diagonal,Ratio 4:3,Active matrix TFT LCD, LED backlight			
Resolution(pixel)	1024x 768 @ 60Hz			
Active Area Dimensions	213.2mm(H) x160.4mm(V)			
Display Colors	16.7M			
Brightness (Standard)	400 cd/m ²			
Response time (standard)	25ms			
View Angle(from center)	Horizontal (left / right): ±80° or a total of 160° Vertical (up/down):±80°, or a total of 160°			
Contrast ratio (standard)	1000: 1(Typ.)			
Touch Technology	projected capacitive Touch thip: welda Touch points; 1-10 Touch supply voltage: 5V Touch interface; USB Touch support system; Windows, Android, linux			
Motherboard	ZC-3566 Rockchip RK3566 High-performance, low-power quad-core 64-bit Cortex-ASS, the main frequency is up to 1.86hz			
Operating system	Android11			
Memory	DDR3 4GB			
Built in memory	EMMC FLASH 32G			
Network support	3G、Ethernet, WiFi / Bluetooth 4.0, wireless peripheral extension			
Wireless	Built in WiFi or WiFi / BT module (optional), 802.11b/g/n, default single WiFi module, external 3dB omnidirectional antenna			
Speakers	Built-in 2°3W speakers			
HDMI Output	1, Support 1080P@120Hz,4kX2k@60Hz Output			
USB2.0 interface	2 USB HOST			
TF Card	Support TF Card			
Headset / Microphone	1 external headphone audio output			
Audio and video output	1 built-in socket output, can directly drive up to 2*3W / 8Ω speakers			
Video function	USB camera support			
Power	Extemal DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC) Type: DC cartridge receptacle; Cartridge ID: 5.5 mm (± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartridge depth: 8.0 mm (± 0.3 mm);			
Power consumption (standard)	Depend on Motherboard and the minimum is 25W			
Temperature	Operating: -10°C to 60°C; Storage: -20°C to70°C			
Humidity	Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)			
Warranty	1 year			
Weight (approx.)	Net weight:1.6 kg(Typ.); Shipping: 3 kg (reference)			
Mounting options	100mm or 75mm VESA mounting,open bracket mounting			
Water and dust protection/Explosion-proof	IP65(front)/IK08(front)			
Surface treatment	NA NA			
Agency Approvals	FCC, CE, CB,China RoHS CQC			

Ordering Information

Model	CPU	RAM	Storage	Surface Treatment	Availability
GT-TC2C-104-RK3566-D4GS32G	RK3566	4G	32G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.