

1852C 18.5" LCD

Open Android touch all-in-one

GreenTouch's 1852C 18.5" Open Android touch all-in-One PC is the integrated touch solution designed for automatic information systems, gaming and entertainment, as well as industrial Automation and control. the open frame touch all-in-one PC is made based on the idea 'designed for simple and convenience" and with the proven GreenTouch professionalism and reliability. The precise small frame design makes it easier for customers to install them product in the cabinet. Designed and built by GreenTouch, the model has a long life cycle and can offer long-term demands.

This model has diverse and powerful functions, modular design, and optional configurations. The ZC-3566 solution with powerful performance is selected. The board integrates multimedia decoding, LCD driver, Ethernet, HDMI, WIFI, 3G, and Bluetooth, supporting the decoding of the majority of current popular video and image formats, HDMI video output, TF card, providing strongerstability and greatly simplifying the overall system design; Built in speaker, powered by a 12V low-voltagepower supply.

The all-in-one machine comes with a series of output connection ports, supporting various third-party peripheral devices. The standard ports include 2 standard USB ports, a 100 Mbps wired network card interface, and 1 3.5MM audio left and right channel output, 1 TF card, and 1 HDMI video output port, facilitating the addition of a second customer display.

A variety of industry-leading GreenTouch projected capacitive touch technologies is available. The model has global standard of agencies' certification and GreenTouch warranty and after-sales service, providing a cost-effective solution for industrial embedded systems integrators and value-added resellers (VARs).

- "Design for simple and convenience" the idea
- · Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen,various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001Quality Management System . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC, ROHS . The objective of GreenTouch is to become the most reliable supplier oftouch screen, high value-added and special touch products and touch solutions in the world.

Applications

- · Information Kiosk
- Game and Entertainment
- Industrial Automation
- · Self-checking service

Features

- Optional Motherboard Configuration includes: ZC-3566
- Optional touch technologies include:

Projected capacitive

- Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option
- · Worldwide agency approvals
- · One year standard warranty





Specifications

Black			
457mm(W) x281.5 mm(H),Thickness: 46.5 mm			
18.5' Diagonal, Ratio16:9, Active matrix TFT LCD, LED backlight			
1366 x 768 @ 60Hz			
408.7mm(H) x 229mm(V)			
16.7M			
250cd/m ²			
1.4ms			
Horizontal (left / right): ±85° or a total of 170°			
Vertical (up / down): ± 80° or a total of 160°			
1000: 1(Typ.)			
projected capacitive			
Touch chip: weida			
Touch points: 1-10			
Touch supply voltage: 5V			
Touch interface: USB			
Touch support system; Windows, Android, linux			
ZC-3566			
Rockchip RK3566 High-performance, low-power quad-core 64-bit Cortex-A55, the main frequency is			
up to 1.8Ghz Andmid11			
4GB			
EMMC 32G			
3G、Ethemet, WiFi / Bluetooth 4.0, wireless peripheral extension			
Built in WiFi or WiFi / BT module (optional), 802.11b/g/n, default single WiFi module, external 1 3dB omnidirectional antenna			
Built-in 2°3W speakers			
1, Support 1080P@120Hz,4kX2k@60Hz Output			
2 xUSB HOST			
Support TF Card			
1 external headphone audio output			
Support left and right channel output, built-in 8R / 5W power amplifier			
USB camera support			
External DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC			
Type: DC cartridge receptacle; Cartridge ID: 5.5 mm			
(± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartridge depth: 8.0 mm (± 0.3 mm);			
Depend on Motherboard and the minimum is 25W			
Operating: 0°C-50°C; Storage: -20°C 60°C			
Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)			
1 year			
Net weight: 4.4 kg(Typ.); Shipping: 6.2 kg (reference)			
100mm or 75mm VESA mounting.open bracket mounting			
IP65(front)/IK08(front)			
protection/Explosion-proof			
less.			

Ordering Information

Model	CPU	RAM	Storage	Surface Treatment	Availability
GT-TC2C-185-RK3566-D4GS32	RK3566	4G	32G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.