

## 1012C 10.1" LCD Open Frame Touchmonitor

The GreenTouch's 1012C LCD open frame touch monitor is a touch solution developed for automated information systems, gaming and entertainment, as well as light industrial automation controls, making GreenTouch's touchmonitor product line even more complete. The 1012C touch monitor is based on the concept "Design for simple and convenience", with proven GreenTouch expertise and reliability. Precise small frame design will be completely sealed touch screen, so that it has dust-proof, dirt-proof and water-proof function, and make it easier for customers to install 1012C in the cabinet. Designed and built by GreenTouch, the model has a long life cycle Period and can supply long-term demands. Even if the future replacement of a new generation of LCD panels, you do not need to do external changes.

The models adopted the industry-leading GreenTouch projected capacitive touch technology. This model has a global standard of agency certification with GreenTouch warranty and overall after-sale service. The 1012C LCD open frame touch monitor is a cost-effective touch solution for system integrators and value-added resellers (VARs).

### Applications

- Information Kiosk
- Game and Entertainment
- Industrial Automation
- Self-checking service



### Features

- Optional touch technologies include: PCAP
- Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option
- Worldwide agency approvals
- One year standard warranty

- "Design for simple and convenience" as the idea
- Outstanding quality, reliability and Cost-effective

### About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—Green-Touch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ROHS. The objective of GreenTouch is to become the most reliable supplier of touch screen, high value-added and special touch products and touch solutions in the world.

### Specifications

|   |  |
|---|--|
| Case/ frame color                         | Black  |
| Display type                              | Active matrix TFT LCD, LED backlight   |
| The diagonal dimension                    | 10.1" diagonal   |
| Aspect ratio                              | 16:10  |
| Active Area Dimensions                    | 218.96mm(H) x 137.6mm(V)   |
| The display size                          | 264.89mm(W) x 179.49mm(H), Thickness: 43.5 mm  |
| Resolution(pixel)                         | 1280 x 800 @ 60Hz  |
| Display Colors                            | 16.2M  |
| Brightness (Standard)                     | 1000 cd/m <sup>2</sup>   |
| Response time (standard)                  | 30 ms  |
| View Angle(from center)                   | L/R:85/85;U/D:85/85 (Typ.)(CR>=10)   |
| Contrast ratio (standard)                 | 900: 1(Typ.)   |
| Input video formats                       | Analog VGA and digital DVI,HDMI  |
| Sweep frequency                           | 31.5-60.2kHz, vertical: 56.3-75 Hz   |
| Touch Technology                          | projected capacitive<br>Touch chip: veida<br>Touch points: 1-10<br>Touch supply voltage: 5V<br>Touch interface: USB<br>Touch support system: Windows, Android, linux   |
| Power                                     | External DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC) - Type: DC cartridge receptacle; Cartridge ID: 5.5 mm(± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartridge depth: 8.0 mm (± 0.3 mm);<br>Power connector (on power adapter) - Type: DC cartridge Plug; Cartridge OD: 5.5 mm (± 0.1mm); Needle Inner Diameter: 2.1 mm (± 0.1 mm); Cartridge Length: 9.5 mm (± 0.5 mm) |
| Power consumption (standard)              | Display only: 13.5W(Typ.)  |
| Temperature                               | Operating:-20℃-70℃; Storage: -30℃- 80℃   |
| Humidity                                  | Operating: 20% to 80% (no condensation); Storage: 10% to 90% (non-condensing)  |
| MTBF                                      | 50,000 hours   |
| Weight (approx.)                          | Net weight:1.6 kg(Typ.); Shipping: 3 kg (reference)  |
| Warranty                                  | 1 year   |
| OSD                                       | Digital OSD  |
| User Controls                             | OSD Button: Menu, Up, Down, Select, Power; OSD: Contrast, Brightness, Horizontal / Vertical Bits Clock, phase, call default, language (English, German, Spanish, Japanese, French); OSD Fail / Active: Power, OSD menu   |
| OSD Remote Accessories                    | Optional controls (front): Menu, Up, Down, Select, Power   |
| Mounting options                          | 100mm or 75mm VESA mounting, open bracket mounting   |
| Water and dust protection/Explosion-proof | IP65(front)/IK08(front)  |
| FAN                                       | 1  |
| Agency Approvals                          | FCC, CE, CB, China RoHS CQC  |

### Ordering Information

| Model                 | Touch Technology | Display Ports | Interface | Surface Treatment | Availability |
|-----------------------|------------------|---------------|-----------|-------------------|--------------|
| GT-TM2CGL-101-F-CW10U | W-series PCAP    | VGA,DVI,HDMI  | USB       | Clear             | Worldwide    |

To find out more about our extensive range of GreenTouch touch solutions, go to [www.greentouch.com.cn](http://www.greentouch.com.cn), or [ifo@greentouch.com.cn](mailto:ifo@greentouch.com.cn)

Service call: +86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright. All rights reserved.

2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.