

1012C 10.1" LCD Open Android touch all-in-one

GreenTouch's 1012C 10.1 " Open Android touch all-in-One PC is the integrated touch solution designed for automatic information systems, gaming and entertainment, as well as industrial Automation and control. the open frame touch all-in-one PC is made based on the idea "designed for simple and convenience" and with the proven GreenTouch professionalism and reliability. The precise small frame design makes it easier for customers to install them product in the cabinet. Designed and built by GreenTouch, the model has a long life cycle and can offer long-term demands.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, the ultra-low power consumption and cost-effective ZC-3566 solution is recommended; the board integrates multimedia decoding, LCD driver, Ethernet, HDMI, WIFI, 3G, Bluetooth in one, supports most currently popular video and picture format decoding, supports HDMI video output , TF card , greatly simplifying the design of the wholesystem; built-in speaker, 12V low voltage power supply.

The all-in-one machine comes with a series of output connection ports, supporting various third-party peripheral devices. The standard ports include 2 standard USB ports, a 100 Mbps wired network card interface, and 1 3.5MM audio left and right channel output, 1 TF card, and 1 HDMI video output port, facilitating the addition of a second customer display.

A variety of industry-leading GreenTouch projected capacitive touch technologies is available. The model has global standard of agencies' certification and GreenTouch warranty and after-sales service.providing a cost-effective solution for industrial embedded systems integrators and value-added resellers (VARs).

## • "Design for simple and convenience" the idea

Outstanding quality, reliability and Cost-effective

## About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO90010uality Management System . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC, ROHS The objective of GreenTouch is to become the most reliable supplier oftouch screen high value-added and special touch products and touch solutions in the world.

## Applications

- Information Kiosk
- Game and Entertainment Industrial Automation
- Self-checking service

### **Features**

 Optional Motherboard Configuration inlcudes: ZC-3566

· Optional touch technologies include Projected capacitive

· Compact and easy to integrate with mounting from sides or top and bottom; also a VESA mount option

Worldwide agency approvals

One year standard warranty





# **Specifications**

Case/ frame color	Black				
Machine dimensions	264.89mm(W) x179.49mm(H),Thickness: 43.4 mm				
Display type	10.1" Diagonal,Ratio16:10,Active matrix TFT LCD, LED backlight				
Resolution(pixel)	1280 x 800 @ 60Hz				
Active Area Dimensions	218.96mm(H) x 137.6mm(V)				
Display Colors	16.7M				
Brightness (Standard)	400 cd/m <sup>2</sup>				
Response time (standard)	30ms				
	Horizontal (left / right): ±85° or a total of 170°				
View Angle(from center)	Vertical (up / down): ± 85° or a total of 170°				
Contrast ratio (standard)	900: 1(Typ.)				
Touch Technology	projected capacitive Touch chip: weida Touch points: 1-10 Touch supply voltage: SV Touch interface: USB Touch interface: USB				
Motherboard	ZC-3566 Rockchip RK3566 High-performance, low-power quad-core 64-bit Cortex-A55, the main frequency is uo to 1.86/biz				
Operating system	Android11				
Memory	4GB				
Built in memory	EMMC 32G				
Network support	3G、Ethemet, WiFi / Bluetooth 4.0, wireless peripheral extension				
Wireless	Built in WiFi or WiFi / BT module (optional), 802.11b/g/n, default single WiFi module, external 1 3dB omnidirectional antenna				
Speakers	Built-In 2*3W speakers				
HDMI Output	1, Support 1080P@120Hz,4kX2k@60Hz Output				
USB interface	2 xUSB HOST				
TF Card	Support TF Card				
Headset / Microphone	1 external headphone audio output				
Audio and video output	Support left and right channel output, built-in 8R / 5W power amplifier				
Video function	USB camera support				
Power	Extemal DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one Pi Type: DC cartidge receptacle; Cartidge ID: 5.5 mm (± 0.3 mm); Needle 0D: 2.0 mm (+0.0 -0.1 mm); Cartidge depth: 8.0 mm (± 0.3 mm);				
Power consumption (standard)	Depend on Motherboard and the minimum is 25W				
Temperature	Operating: -20°C to 70°C; Storage: -30°C to 70°C				
Humidity	Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)				
Warranty	1 year				
Weight (approx.)	Net weight: 1.6 kg(Typ.); Shipping: 3 kg (reference)				
Mounting options	100mm or 75mm VESA mounting,open bracket mounting				
Water and dust protection/Explosion-proof	IP65(front)/IK08(front)				
Surface treatment	NA				
	FCC, CE, CB,China RoHS CQC				

## Ordering Information

Model	CPU	RAM	Storage	Surface Treatment	Availability
GT-TC2C-101-RK3566-D4GS32G	RK3566	4G	32G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

#### Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved