

1 Polyurethane Adhesive

Item No.	Appearance	Main Component	Viscosity (cps/25°C)	Main Application and Characteristics	Packages
XC-900 Non-yellowing PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1600 ± 200	Non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-900L Non-yellowing PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1400 ± 200	Low viscosity type, non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-900H Non-yellowing PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1800 ± 200	High-viscosity type, non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-900F Toluene-free and non-yellowing PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1600 ± 200	Toluene-free and non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-900HF Toluene-free and non-yellowing PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1800 ± 200	High-viscosity toluene-free and non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-800W Non-yellowing PU Adhesive	Foggy translucent Viscous Liquid	PU copolymer	1400 ± 200	Non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-800WH Non-yellowing PU Adhesive	Foggy translucent Viscous Liquid	PU copolymer	1600 ± 200	High-viscosity type, non-yellowing PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg
XC-700W Yellowing-resistance PU Adhesive	Colorless Transparent Viscous Liquid	PU copolymer	1600 ± 200	Yellowing-resistance PU adhesive with good adhesion strength, initial peel strength and superior operability, suitable for bonding of PVC、PU、TPR、EVA、Rubber and leather etc.	15kg

Purpose and description::

Use material range: Rubber、PVC、TPR、EVA、nylon、PU and other materials such as PVC leather、PU leather、nylon fabric、leather、Sumelon Leather and other materials.

Note: 1. Apply the hardener 3-5% before the use of PU adhesive, and use after mixing.

2. White materials should be used for non-yellowing type PU adhesive, with non-yellow type curing agent.

3. The maintenance time of PU adhesive is short, and it must be pressurized when heated.

4. In the process of manual and assembly line work, it should avoid the direct blow of wet and cold air.

5. All solvent-based PU adhesive can be diluted by XC-03.

6. Water-based PU adhesive must be used with water-based curing agent.

7. Keep away from fire.

