

# NS-5600-450

## 粘台機 (帶自動平衡系統)

## Fusing Machine (with Automatic Balancing System)



運輸帶清潔系統  
conveyor belt cleaning system



- 適用於粘台褲頭、襟朴、女裝領、袖等低溫、低壓朴
- 採用耐高溫鐵氟龍傳送帶，傳熱速度快
- 開邊設計，適於大件物料通過
- 彈簧式加壓，壓力可達0.5kgf/cm<sup>2</sup>
- 工作闊度：450mm
- 最高設計溫度：200℃
- 可調校運轉速度
- 滾筒運輸帶式設計，無長度限制，生產效率高

- Suitable for fusing interlining of waist band, front placket, lady blouse collar and cuff at low temperature and low pressure
- Adopt high temperature resistant Teflon belt as conveyer belt for fast heat transfer
- Open side design enables free passing of large piece of material
- Spring type pressure adding system; pressure can reach 0.5kgf/cm<sup>2</sup>
- Working width: 450mm
- Max. design temperature: 200 °C
- Variable speed control
- Roller conveyer belt design, high production efficiency and no limit on length to be fused

型號 Model	電源 Power Supply	總功率(kW) Total Power	平均粘台壓力(kgf/cm <sup>2</sup> ) Average Fusing Pressure	傳輸速度(m/min) Delivering Speed	加熱時間(sec) Heating Time	最高設計溫度 Max. Design Temp. (°C)	工作闊度(mm) Working Width	淨重(kg) Net Weight	機身尺寸 (mm) Machine Size	裝箱尺寸(mm) Packing Size
NS-5600-450	1PH/220V/50Hz	4.1	0.5	0.7~4.5	4.5~35	200	450	152	2230x880x510	970x970x570



### 藝誠(余氏)發展有限公司 Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852) 2741 9981, 2742 0078

Fax: (852) 2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com