


# NS-9501D

## 自動轉頭雙袖山縫壓平機

### Automatic Rotation Double Armhole Press



- 適用於襯衫雙袖山縫同時粘合壓熨
- 採用PLC可編程控制器控制及人性化觸摸顯示屏操作
- 採用垂直加壓方式，壓熨更平整，壓力效率更大
- 輕壓、重壓兩種壓熨方式供選擇設定，可滿足不同面料需求
- 上模採用電加熱，由六通道智能溫度模塊配合觸摸屏分區控制，溫度控制更精確
- 自動旋轉式四下模設計，操作方便，工作效率高
- 單套發熱上模配合雙下模交替式操作，可節省電力
- 下模氣袋再配合硅膠條(耐高溫、高壓)，可徹底消除模與襯衫袖山縫形狀間的偏差，配合不同布料達到完美壓熨效果
- 備有獨立真空泵，有助衣物定位，冷卻、定型效果佳

#### 選購件:

O-J-01-4 吹風冷卻系統(壓縮空氣)  
各種袖山模

- Suitable for fusing and pressing double armholes simultaneously
- Adopt PLC and user friendly touch screen for operation
- Vertical pressure increasing mode offers smooth pressing effect and high pressure efficacy
- Two pressing modes, i.e. light press and heavy press, are available for selection to cater for different fabrics
- Minimal temperature fluctuation of electric heated upper mould thanks to 6-channel intelligent temperature module and touch screen, through which the temperature control and setting of each zone of upper mould is realized
- Four automatic rotation lower moulds enables easy operation and high efficiency
- Single set of upper heating mould alternately works with two sets of lower moulds, thereby saving power
- Lower mould airbag and silica rubber (high temperature and pressure resistant) can completely offset the shape difference between mould and shirt armhole, thereby to achieve perfect pressing effect
- With independent vacuum pump to facilitate garment fixing, cooling and shaping

#### Option:

O-J-01-4 Compressed air blowing cool down system  
Various armhole moulds



雙袖山縫可同時鋪料及粘合壓熨  
Double armholes can be laid, fused and pressed simultaneously



PLC可編程控制器控制及人性化操作界面觸摸顯示屏  
操作  
Adopt PLC and human friendly touch screen for  
operation



獨立真空泵，有助衣物定位，冷卻、定型效果  
Independent vacuum pump facilitates garment  
positioning, cooling and shaping

型號 Model	電源 Power Supply	總功率(kW) Total Power	發熱線功率 (kW) Heater Power	真空泵功率(kW) Vacuum Pump Power	壓縮空氣壓力(kgf/cm <sup>2</sup> ) Compressed Air Pressure	耗壓縮空氣量(L/min) Compressed Air Consumption	平均粘合壓力(kgf/cm <sup>2</sup> ) Average Fusing Pressure	淨重(kg) Net Weight	機身尺寸(mm) Machine Size
NS-9501D	3PH/380V/50Hz	6.4	4.8	1.5	5	180	2.5	1125	1950x2100x1950



藝誠(余氏)發展有限公司  
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下  
G/F., 52 Wing Hong St.,  
Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078 E-MAIL: info@ngaishing.com  
Fax: (852) 2785 3149 Http://www.ngaishing.com