


A801單針數碼拖輪
A802雙針數碼拖輪
A803日字埋夾數碼拖輪

Digital Puller For Single Needle Machine
Digital Puller For Double Needle Machine
Digital Puller For Japan Made Chain Stitch Feed-off Arm
Machine
Digital Puller For Placket Machine
Digital Bottom Hemming Puller



A801



A801安裝后外觀
Appearance of A801 after installation

- A801適用針車: JUKI DDL-9000B / 8700 / 8000A 單針平車
- 驅動方式: 上輪
- 拖輪規格: Ø25×17mm(跟機已安裝)
- 針距長度: 0.7~4mm
- 車縫速度: 1~4000 轉/分
- 電源: AC 100~240V
- 適用蝴蝶(選購):
 - A. 襯衫拉鈕子: F206、F207、F208、F254
 - B. 平袋口: F252, F253
 - C. 落擔幹: F213

選購件:

APT07-00921M-V1 拖輪 Ø40×17mm

- Applicable sewing head for A801: JUKI DDL-9000B / 8700 / 8000A single needle lockstitch machine
- Drive mode: upper wheel
- Pulling wheel size: Ø25×17mm(has been installed on machine)
- Stitch length: 0.7~4mm
- Sewing speed: 1~4000 RPM
- Power supply: AC 100~240V
- Applicable folders(Option):
 - A. Shirt under placket sewing: F206, F207, F208, F254
 - B. Pocket hemming: F252, F253
 - C. Yoke attaching: F213

Option:

APT07-00921M-V1 Pulling wheel Ø40×17mm

- A802適用針車: JUKI LH-3528A / BROTHER T-8420系列 雙針車
- 驅動方式: 上輪
- 拖輪規格: Ø50×50mm(跟機已安裝)
- 針距長度: 0.7~4mm
- 車縫速度: 1~3000 轉/分
- 電源: AC 100~240V
- 適用蝴蝶(選購):
 - 襯衫拉鈕筒: F201、F203、F204、F214

- Applicable sewing head for A802: JUKI LH-3528A / BROTHER T-8420 series double needle machine
- Drive mode: upper wheel
- Pulling wheel size: Ø50×50mm(has been installed on machine)
- Stitch length: 0.7~4mm
- Sewing speed: 1~3000 RPM
- Power supply: AC 100~240V
- Applicable folders(Option):
 - Shirt front box placket sewing: F201, F203, F204, F214

A802



A803



- A804適用針車: KANSAI DFB1404 恤衫拉筒車
- 驅動方式: 上輪
- 拖輪規格: Ø50x50mm (跟機已安裝)
- 針距長度: 0.7~4mm
- 車縫速度: 1~3000 轉/分
- 電源: AC 100~240V
- 適用蝴蝶(選購):
襯衫拉筒: F201、F204、F307

- Applicable sewing head for A804: KANSAI DFB1404 shirt placket machine
- Drive mode: upper wheel
- Pulling wheel size: Ø50x50mm(has been installed on machine)
- Stitch length: 0.7~4mm
- Sewing speed(continuous/intermittent): 1~3000 RPM
- Power supply: AC 100~240V
- Applicable folders(Option):
shirt placket sewing: F201, F204, F307

A805



O-D-10-01
三段速度控制系統
3-stage speed control
system

- A803適用針車: JUKI MS-1190 雙針埋夾車
- 驅動方式: 上下輪
- 拖輪上輪規格: Ø40x17mm (跟機已安裝)
- 拖輪下輪規格: Ø25x19mm (跟機已安裝)
- 針距長度: 0.7~4mm
- 車縫速度: 1~3000 轉/分
- 電源: AC 100~240V
- 適用蝴蝶(選購):
襯衫埋夾: F236、F243
- Applicable sewing head for A803: JUKI MS-1190 double needle feed-off arm machine
- Drive mode: upper and lower wheels
- Upper pulling wheel size: Ø40x17mm(has been installed on machine)
- Lower pulling wheel size: Ø25x19mm(has been installed on machine)
- Stitch length: 0.7~4mm
- Sewing speed: 1~3000 RPM
- Power supply: AC 100~240V
- Applicable folders(Option):
Under arm seam and side seam joining: F236, F243

A804



- A805適用針車: JUKI DDL-9000C / 9000B / 8700 / 8000A 單針平車
- 驅動方式: 上輪
- 拖輪規格: Ø20x17mm (帶坑拖輪)(跟機已安裝)
- 針距長度: 0.7~4mm
- 車縫速度: 1~4000 轉/分
- 電源: AC 100~240V
- 適用蝴蝶(選購):
拉衫腳: F503、F504
- 選購件:
APT07-00962M 拖輪 Ø20x17mm
O-D-10-01 三段速度控制系統
- Applicable sewing head for A805: JUKI DDL-9000C / 9000B / 8700 / 8000A single needle lockstitch machine
- Drive mode: upper wheel
- Pulling wheel size: Ø20x17mm(wheel with grooves)(has been installed on machine)
- Stitch length: 0.7~4mm
- Sewing speed: 1~4000 RPM
- Power supply: AC 100~240V
- Applicable folders(Option):
Shirt bottom hemming: F503, F504
- Option:
APT07-00962M pull wheel Ø20x17mm
O-D-10-01 3-stage speed control system

客戶在訂購以上各款拖輪時，請提供縫紉機詳細型號及說明縫紉機是否帶撥線器！
When placing order for above pullers, customers need provide detailed information about sewing machine model, including whether the sewing machine is equipped with a thread wiper!



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下
G/F., 52 Wing Hong St.,
Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078 E-MAIL: info@ngaishing.com
Fax: (852) 2785 3149 Http://www.ngaishing.com