



Taian zhengtai construction machinery Co., Ltd
Industrial Park Shiheng town Feicheng City Shandong province China

whatsapp/ wechat: +86 13953879973
EMAIL: woniuniu9527@163.com



Description	Specification
rated load(kg)	5000
Rated bucket capacity (m ³)	3
operating weight (kg)	16300
Max.breakout force (kN)	150
Max.dump height (MM)	3400
Max.dump reach (MM)	1083
Articulation angle (°)	±35
Climb ability (°)	29
Raising time (s)	≤6
Total cycle time(lifting, dumping, lowering) (s)	≤10
Min turning radius (MM)	6200
Wheel base (MM)	2920
Tread (MM)	2250
Min.ground clearance (MM)	534
Overall dimensions (l×w×h)mm (MM)	7929×3024×3423
travel speed (km/h)	
Forward gear I	0~13.5
II	0~35
reverse gear I	0~17
II	0~38
Engine Model	WD10G220E21
Type	Water injection four-stroke inline
Rated power (kW)	162
Rated speed (rpm)	2200
Tire model	23.5-25
Steering system pressure (MPa)	16
The braking system	
Service brake	Gas-liquid caliper disc brake
Parking brake	Breathe manipulating drum brake
Fuel Tank	260L
Engine Oil	201L
Cooling System	45L
Hydraulic System	270L
Transmission and Torque Converter	45L
Axles, Each	27*2L