



<b>Model Number</b>	<b>S200-19GTP-AC</b>
Manage	None Managed
Switch Chipset	Realtek
PoE	Support PoE
Housing	Metal
Ports	16X10/100/100Mbps RJ45
	2X10/100/1000Mbps RJ45 + 1X10/100/1000Mbps SFP (Not Combo)
PoE Standard	IEEE802.3af/at
PoE Chipset	Realtek, Support PoE negotiate power supply
PoE Pin	1,2 + / 3,4-
Single Port Max Power	30W
AI DIP Switch	PoE Watchdog: Auto reboot the unresponsive PoE devices for recovery
	250M: 1-8 ports support 250m power and data transmission
	Port Isolation: All LAN ports are isolated from each other to avoid interference
	Network storm control: Able to limited the network storm within 3%
Total PoE Power	180W

Switch Capacity	9.2G
Forwarding Rate	6.84Mpps
Mac Table	4K
Buffer	2K
Forwarding Delay	<5us
MDX/MIDX	Support
Working Temperature	(-10°C~+50°C)
Storage temperature	(-40°C~+75°C)
Relative humidity	5%~95% non-condensing
MTBF	100000 Hours
ESD	8KV~ 15KV
Surge Proof	General 6000V Difference: 2000V
Free Fall	0.5m
Product Size	319X207X45 mm
Weight	0.87Kgs
Power In	AC 100-240V 50/60Hz