

GL2008 GPON OLT

Datasheet

Product overview

GL2008 is highly integrated, medium-capacity GPON OLT for operators, ISP, enterprises and park applications. The product follows the ITU-T G.984/G.988 technical standard, The product has good openness, strong compatibility, high reliability, and complete software functions. It can be widely used in operators' FTTH access, VPN, government and enterprise park access, campus network access, etc.

GL2008 is only 1U in height, easy to install and maintain, and save space. Supports mixed networking of different types of ONUs, which can save a lot of costs for operators.

Picture 1: GL2008 OLT



Main Feature

- Rich Layer 2/3 switching features and Flexible management methods
- Support multiple link redundancy protocols such as FlexLink/STP/RSTP/MSTP/ERPS/LACP
- Support RIP、OSPF、BGP、ISIS and IPV6
- Safe DDOS and virus attack protection
- Support Power redundancy backup, Modular power supply
- Support power failure alarm
- Type C management interface

Product specifications

Attributes	GL2008
Exchange capacity	104Gbps
Packet forwarding rate	77.376Mpps
Memory and storage	Memory: 512MB, storage: 32MB
Management port	Console, Type C
Port	8*GPON Port 4*10/100/1000M Base-T 4*1000MBase-X SFP/4*10GE SFP+
PON	Comply with ITU-TG.984/G.988 standard 60KM transmission distance 1:128 Max splitting ratio Standard OMCI management function Open to any brand of ONT ONU batch software upgrade
VLAN	Support 4K VLAN Support Vlan based on port, MAC and protocol Support dual Tag VLAN, port-based static QinQ and flexible QinQ
MAC	16K Mac address Support static MAC address setting Support black hole MAC address filtering Support port MAC address limit
Ring network protocol	Support STP/RSTP/MSTP Support ERPS Ethernet ring network protection protocol Support Loopback-detection port loopback detection
port control	Support two-way bandwidth control Support port storm suppression Support 9K Jumbo ultra-long frame forwarding
Port aggregation	Support static link aggregation Support dynamic LACP Each aggregation group supports a maximum of 8 ports
Mirroring	Support port mirroring Support stream mirroring

ACL	<p>Support standard and extended ACL</p> <p>Support ACL policy based on time period</p> <p>Provide flow classification and flow definition based on IP header information</p> <p>Such as source/destination MAC address, VLAN, 802.1p, ToS, DSCP, source/destination IP address, L4 port number, protocol type, etc</p>
QoS	<p>Support flow rate limiting function based on custom business flow</p> <p>Supports mirroring and redirection functions based on custom business flows</p> <p>Support priority marking based on custom service flow, support 802.1P, DSCP priority Remark capability</p> <p>Support port-based priority scheduling function</p> <p>Support queue scheduling algorithms such as SP/WRR/SP+WRR</p>
Safety	<p>Support user hierarchical management and password protection</p> <p>Support IEEE 802.1X authentication</p> <p>Support Radius&TACACS+ authentication</p> <p>Support MAC address learning limit, support black hole MAC function</p> <p>Support port isolation</p> <p>Support broadcast message rate suppression</p> <p>Support IP Source Guard Support ARP flood suppression and ARP spoofing protection</p> <p>Support DOS attack and virus attack protection</p>
Layer 3	<p>Support ARP learning and aging</p> <p>Support static route</p> <p>Support dynamic route RIP/OSPF/BGP/ISIS</p> <p>Support VRRP</p>
System management	<p>CLI, Telnet, WEB, SNMP V1/V2/V3, SSH2.0</p> <p>Support FTP, TFTP file upload and download</p> <p>Support RMON</p> <p>Support SNMP</p> <p>Support system work log</p> <p>Support LLDP neighbor device discovery protocol</p> <p>Support 802.3ah Ethernet OAM</p> <p>Support RFC 3164 Syslog</p> <p>Support Ping and Traceroute</p>
Environment temperature	<p>Working Temperature: -10°C~55°C</p> <p>Storage temperature: -40°C~70°C</p>
Environment humidity	<p>Operating humidity: 10%~95% (non-condensing)</p> <p>Storage humidity: 10%~95% (non-condensing)</p>
Environment friendly	China RoHs, EEE
Weight	≤5kg
FAN	Fixed fans (three fans)
Power	<p>AC: 100~240V 47/63Hz</p> <p>DC: 36V~75V</p>
Power consumption	65W
Dimensions (Width * height * depth)	440mm*44mm*260mm

Purchasing Information

Product name	Product description
GL2008	8*PON port, 4*10GE/GE SFP +4GERJ45 uplink port, Dual power with optional