

Loader



ShanDing Group is a professional construction machinery manufacturer integrating production and sales



SHANDONG SHANDING MACHINERY CO.,LTD

电子邮箱(E-mail): jojo@sddavoo.com

官方网站 (official website) : www.shanding-china.com

地 址: 山东国际商贸港·西城经济产业园
Add: Yucheng Xicheng Industrial Park, Shandong Province.



ZHAINIU MALL

About Us >

The mission of company

create an extremely cost-effective machinery and equipment brand and liberate more labor for the world
 create an extremely cost-effective machinery and equipment brand and liberate more labor for the world.

corporate vision

to create and operate 7 international companies in different countries.

Company values

customer first, honesty and trustworthiness, teamwork, extremely slow like hatred, love and dedication.

management idea

market-oriented, customer-centric, innovation-centric, and leading-driven



智力打造坚固耐用的装载机领军品牌
INTELLIGENCE BUILDS THE LEADING BRAND OF STRONG AND DURABLE LOADERS

品质缔造世界
Quality makes the world

装载机 S65-63 LOADER

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.2
额定载重量 (kg) Rated load (kg)	2500
整机重量 (kg) Machine weight (kg)	6100
发动机额定功率 (kw) Rated engine power (kw)	85-88
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	≥3600
卸载距离 (mm) Dumping reach (mm)	≥920
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡能力 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	7300 × 2440 × 3190



The design of the chair and control lever in the cab is more in line with the principle of ergonomics. The super large space of the driving room can reduce the fatigue of the driver and make the driving easier. The cab can body welding can reduce the vibration of the whole machine, which is safer and more reliable, and the whole plastic interior is easy to clean.



The overall design of the frame is optimized and rounded to enhance the strength of the car body and reduce the vibration of the whole machine. The well adopts the pickling and phosphating process, which is equipped with erosion and has a long service life.



装载机
LOADER **SG38**



主要技术参数

铲斗容量 (m³)	1.2
Bucket capacity (m³)	1.2
额定载重量 (kg)	2300
Rated load (kg)	2300
整机重量 (kg)	≤5600
Machine weight (kg)	≤5600
发动机标定功率 (kw)	76-78-88
Rated engine power (kw)	76-78-88
铲斗提升时间 (s)	≤5-8
Bucket lifting time (s)	≤5-8
卸载高度 (mm)	≥3500
Dumping height (mm)	≥3500
卸载距离 (mm)	≥900
Dumping reach (mm)	≥900
最高时速 (km/h)	≤35
Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm)	4500
Minimum turning radius (mm)	4500
爬坡度 (°)	30
Climbing ability (°)	30
外型尺寸 (mm)	6000 × 2000 × 2900
Overall dimensions (mm)	6000 × 2000 × 2900

主要技术参数

铲斗容量 (m³)	1.1
Bucket capacity (m³)	1.1
额定载重量 (kg)	2300
Rated load (kg)	2300
整机重量 (kg)	≤5000
Machine weight (kg)	≤5000
发动机标定功率 (kw)	63-76
Rated engine power (kw)	63-76
铲斗提升时间 (s)	≤5-8
Bucket lifting time (s)	≤5-8
卸载高度 (mm)	≥3500
Dumping height (mm)	≥3500
卸载距离 (mm)	≥960
Dumping reach (mm)	≥960
最高时速 (km/h)	≤35
Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm)	4500
Minimum turning radius (mm)	4500
爬坡度 (°)	30
Climbing ability (°)	30
外型尺寸 (mm)	6000 × 2060 × 2900
Overall dimensions (mm)	6000 × 2060 × 2900

装载机
LOADER **ZL38**



主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.0
额定载重量 (kg) Rated load (kg)	2100
整机重量 (kg) Machine weight (kg)	≤4500
发动机标定功率 (kw) Rated engine power (kw)	65-76
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	≥3200
卸载距离 (mm) Dumping reach (mm)	≥720
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡度 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	5400 × 1850 × 2800

装载机 **SG36**
LOADER



装载机 **ZL32**
LOADER



主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	0.9
额定载重量 (kg) Rated load (kg)	2000
整机重量 (kg) Machine weight (kg)	≤3800
发动机标定功率 (kw) Rated engine power (kw)	42-65
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	≥3200
卸载距离 (mm) Dumping reach (mm)	≥760
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡度 (°) Climbing ability (°)	≥30
外型尺寸 (mm) Overall dimensions (mm)	5300 × 1850 × 2800

主要技术参数

铲斗容量 (m³)	0.8
Bucket capacity (m³)	0.8
额定载重量 (kg)	1800
Rated load (kg)	1800
整机重量 (kg)	≤3500
Machine weight (kg)	≤3500
发动机标定功率 (kw)	38-47
Rated engine power (kw)	38-47
铲斗提升时间 (s)	≤5-8
Bucket lifting time (s)	≤5-8
卸载高度 (mm)	≥3200
Dumping height (mm)	≥3200
卸载距离 (mm)	≥720
Dumping reach (mm)	≥720
最高时速 (km/h)	≤35
Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm)	4500
Minimum turning radius (mm)	4500
爬坡能力 (°)	≥30
Climbing ability (°)	≥30
外型尺寸 (mm)	5400 × 1850 × 2800
Overall dimensions (mm)	5400 × 1850 × 2800

装载机
LOADER **SG32**

装载机
LOADER **ZL26**

主要技术参数

铲斗容量 (m³)	0.7-1.0
Bucket capacity (m³)	0.7-1.0
额定载重量 (kg)	1500
Rated load (kg)	1500
整机重量 (kg)	≤3800
Machine weight (kg)	≤3800
发动机标定功率 (kw)	33-44
Rated engine power (kw)	33-44
铲斗提升时间 (s)	≤5-8
Bucket lifting time (s)	≤5-8
卸载高度 (mm)	≥3000
Dumping height (mm)	≥3000
卸载距离 (mm)	≥920
Dumping reach (mm)	≥920
最高时速 (km/h)	≤35
Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm)	≤4500
Minimum turning radius (mm)	≤4500
爬坡能力 (°)	≥30
Climbing ability (°)	≥30
外型尺寸 (mm)	4800 × 1780 × 2700
Overall dimensions (mm)	4800 × 1780 × 2700



主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	0.4
额定载重量 (kg) Rated load (kg)	1200
整机重量 (kg) Machine weight (kg)	≤2800
发动机标定功率 (kw) Rated engine power (kw)	21-25
铲斗提升时间 (s) Bucket lifting time (s)	5-8
卸载高度 (mm) Dumping height (mm)	≥3000
卸载距离 (mm) Dumping reach (mm)	940
最高时速 (km/h) Maximum speed per hour (km/h)	≤30
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡能力 (°) Climbing ability (°)	≥30
外型尺寸 (mm) Overall dimensions (mm)	4600 x 1510 x 2600

装载机
LOADER ZL20



装载机
LOADER ZL08

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	0.25
额定载重量 (kg) Rated load (kg)	600
整机重量 (kg) Machine weight (kg)	2000
发动机标定功率 (kw) Rated engine power (kw)	38
铲斗提升时间 (s) Bucket lifting time (s)	5-8
卸载高度 (mm) Dumping height (mm)	2400
卸载距离 (mm) Dumping reach (mm)	800
最高时速 (km/h) Maximum speed per hour (km/h)	30
最小转弯半径 (mm) Minimum turning radius (mm)	3500
爬坡能力 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	4300 x 1300 x 2600



叉木机 ZL46

WOOD FORKLIFT

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.0-1.5
额定载重量 (kg) Rated load (kg)	2000
整机重量 (kg) Machine weight (kg)	5500
发动机标称功率 (kw) Rated engine power (kw)	65-85
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	≥4200/4500
卸载距离 (mm) Dumping reach (mm)	920/1500
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡能力 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	6700 × 2000 × 2900



可定做ZL20-ZL46型叉木机

We can manufacture ZL20-ZL46 typewood forklift

装载机 ZL48

LOADER

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.5
额定载重量 (kg) Rated load (kg)	2800
整机重量 (kg) Machine weight (kg)	6000
发动机标称功率 (kw) Rated engine power (kw)	65-85
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	4800/5000
卸载距离 (mm) Dumping reach (mm)	≥920/1200
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡能力 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	8500 × 2440 × 3190

新款高举王
New style lifting king

叉木机 **ZL46**
WOOD FORKLIFT

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.0-1.5
额定载重量 (kg) Rated load (kg)	2000
整机重量 (kg) Machine weight (kg)	5500
发动机标定功率 (kw) Rated engine power (kw)	65-85
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	≥4200/4500
卸载距离 (mm) Dumping reach (mm)	920/1500
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡度 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	6700 × 2000 × 2900



可定做ZL20-ZL46型叉木机

We can manufacture ZL20-ZL46 typewood forklift

装载机 **ZL48**
LOADER

主要技术参数

铲斗容量 (m³) Bucket capacity (m³)	1.5
额定载重量 (kg) Rated load (kg)	2800
整机重量 (kg) Machine weight (kg)	6000
发动机标定功率 (kw) Rated engine power (kw)	65-85
铲斗提升时间 (s) Bucket lifting time (s)	≤5-8
卸载高度 (mm) Dumping height (mm)	4800/5000
卸载距离 (mm) Dumping reach (mm)	≥920/1200
最高时速 (km/h) Maximum speed per hour (km/h)	≤35
最小转弯半径 (mm) Minimum turning radius (mm)	4500
爬坡度 (°) Climbing ability (°)	30
外型尺寸 (mm) Overall dimensions (mm)	8500 × 2440 × 3190



新款高举王
New style lifting king

扫雪车 ZL36

SNOWPLOW



The loading sails produced by our company can be equipped with digging anti sail, container fork, grabbing fork, connecting beard device, snow shovel side tipping bucket, grabbing fork, wheat straw fork, Yige fork and other optional parts to meet the requirements of various working conditions.



除尘机 Dust Collector



抓纸叉 Scratch paper fork



麦草叉 Wheatgrass fork



抱夹 Hold clamp



快换装置 Quick change device



扫地机 2 Sweeping machine 2



推雪铲 2 Push snow shovel 2



直板抱夹 Straight clamp

矿车 ZL38

BOGIE TRUCK

可定做ZL20-38型矿车

We can manufacture ZL20-30 type Bogie truck



主要技术参数

铲斗容量 (m³)	0.8
Bucket capacity (m³)	
额定载重量 (kg)	1600
Rated load (kg)	
整机重量 (kg)	≤3600
Machine weight (kg)	
发动机额定功率 (kw)	60-75
Rated engine power (kw)	
铲斗提升时间 (s)	≤6-8
Bucket lifting time (s)	
卸载高度 (mm)	≥1800/2200
Dumping height (mm)	
卸载距离 (mm)	≥920
Dumping reach (mm)	
最高时速 (km/h)	≤35
Maximum speed per hour (km/h)	
最小转弯半径 (mm)	≤4500
Minimum turning radius (mm)	
爬坡能力 (°)	≥30
Climbing ability (°)	
外型尺寸 (mm)	4700 × 1600 × 2750
Overall dimensions (mm)	




搅拌斗 Stirring bucket



接臂装置 The arm device



推雪铲 1 Push snow shovel 1



侧翻斗

Side dump



旋转叉头 Rotating fork



斗叉 Bucket fork



集装箱叉 Container fork



挖坑机 Earth auger