

The most knowledgeable heat dissipation expert of LED grow light





致力于生物光照型材设计 精密散热、表面处理 光谱定制一站式全案

Committed to biological lighting profile design, precision heat dissipation, surface treatment, spectrum customizationone-stop case

OEM/ODM

深圳市普威迅科技有限公司 深圳植光科芯生物科技有限公司

② 手机: +86 136 3153 8487

+86 135 4411 5506 ② 电话:+86 755 2851 2032

◎ 邮箱: pvisung@pvisung.com

www.pvisunggrowlight.com

地址:深圳市龙岗区宝龙街道南约社区 高科大道57号普威迅工业园 Shenzhen Pvison Technology Co.,Ltd. Shenzhen Pvisungrow Biotechnology Co.,Ltd.

MOBILE: +86 136 3153 8487 +86 135 4411 5506

TEL: +86 755 2851 2032

E-MAIL : pvisung@pvisung.com

SITE: www.pvisung.com www.pvisunggrowlight.com

ADDRESS: PVISON Industrial Park, No. 57, Gaoke
Avenue, Nanyue Community, Baolong Street,
Longgang District, Shenzhen City, Guangdong

PVISOP 普威迅 PVISUNGR W 植光科芯

Company Introduction 公司介绍

普威迅成立于2004年,是一家集研发、生产、销售于一体的国家高新技术企业。致力于型材设 计, 表面处理,精密散热,生物光照一站式服务全案。先后获得国内外50多项专利,是国家AAA企 业,广东省守合同重信用企业。公司严格依照IS09001质量管理体系,建立了一整套标准化的生产体 系。在散热和铝制品结构方面成为了多个一线品牌优秀供应商,基于这两方面的优势,配备专业光学技术 人才,整合科技智慧农业设施项目企业,创新研发生物光照产品。多款产品凭借技术优势,成功引领市 场,获得客户的广泛认可。普威迅秉承"以工匠精神,铸造精品、以合作共赢成就未来"的经营理念,力 争成为全球生物光照领域的倡导者、领导者、践行者。人在"铝"途,觅光而行,为人类的美好生活贡 献应有力量。

Founded in 2004, Pvison is a national high-tech enterprise integrating R&D, production and sales. Committed to profile design, surface treatment, precision heat dissipation, biological illumination one-stop service for the whole case. It has obtained more than 50 patents at home and abroad, and is a national AAA enterprise and a contract-abiding and credit-abiding enterprise in Guangdong Province China. The company has established a set of standardized production system in strict accordance with IS09001 quality management system. In terms of heat dissipation and aluminum product structure, it has become an excellent supplier of many first-line brands. Based on these two advantages, it is equipped with professional optical technical talents, integrates scientific and technological smart agricultural facilities project enterprises, and innovates and develops biological lighting products. A number of products have successfully led the market with their technological advantages and have been widely recognized by customers. Adhering to the business philosophy of "creating high-quality products with the spirit of craftsmen, and achieving the future with win-win cooperation", Pvison strives to become an advocate, leader and practitioner in the field of global bio-illumination. Pvison is on the road of "aluminum", look for light to move ahead, contributing our due strength to the better life of mankind.















科技战略

成为农业协会副会长单位;参与农协行 业设施标准制定;太空科技南方研究院战略合作伙伴;在生物光照领域打造 PVSUNG高端品牌

Become the vice-chaiman unit of the Agricultural Association: participate in the formulation of he industry facility standards of the Agricultural Association; strategic partner of the Southern Institute of Space Science and Technology; created high-end brand of PVISUNG in the field of biological illumination.



挂牌上市 **Public Listing**

成为国家高新技术企业,在前海股 权交易中心挂牌。成功整合了上下游供 应链,成为行业配套完善的优质供应

tech enterprise and listed in Qianhai Equity Exchange Center. And successfully integrated the upstream and downstream supply chain to become a high-quality supplier with complete supporting cilities in the industry.

2016年



行业延伸

Industry extension

拥有独立自主研发能力,走向产研 销一体。从铝制品散热器行业延展到精 密铝制品外观件行业。

Have independent research and development capabilities, move towards the integration of production, research and sales. Expand from the aluminum radiator industry to the business of precision aluminum appearance oroducts industry.



On the road of "aluminum'

普威迅成立,进入铝制品,散

Pvison was established and entered the aluminum products and radiator industries.





2022年

PVISUNGROW 植光科芯

觅光而行

Look for light to move ahead



Work hard to press ahead

xpand, emerge in the radiator









致力于生物光照型材设计、精密散热 表面处理、光谱定制一站式全案

Committed to biological lighting profile design, precision heat dissipation, surface treatment, spectrum customization one-stop case

High-grade heatsink 高精尖散热器案例展示



高铁车厢工控散热结构件 Heatsink of high-speed railway carriage

中国每一节高铁车厢 里,都有普威迅生产的散热 器。

工艺:铝挤压,CNC精密加工,热导管散热,表面阳极氧化,喷粉等。



中海达海洋测绘设备散热器

普威迅对产品精益求精,为海洋测绘生产的高品质散热器,可以通过360个小时的盐雾测试。

工艺:铝挤压, CNC, 精密加工, 热导管散热, 表面阳极氧化, 喷粉等。



微星主板散热器 Heatsink of Msi computer motherboard

普威迅生产的电脑 CPU散热器,极致精雕,高 效急速散热。

工艺:铝挤压,CNC精密及阳极氧化,丝印等。

Precision aluminum products

精密铝制品案例展示



华为智慧屏边框 Huawei Smart screen frame

普威迅创新研发红外触控 铝边框,深受市场青睐,成为 多家上市公司供应商。

工艺: 铝挤, CNC精密加工, 喷砂, 拉丝, 氧化, 喷粉, 拉丝, 高光, 镭雕等。



滤波器 Aluminum filter

17年"铝"途深耕,产研销精密铝制品。

工艺:阳极氧化,外观铝件。

LED grow light aluminum housing 植物灯套件展示

创新研发冷热自循环植物灯散热系统,高效散热,减少光衰,

保证光效。 工艺: 喷砂, 拉丝, 氧化, 压铸等。


03

全球创新伸缩抽拉植物灯

Global Innovation Retractable Plant Lamp


全球创新伸缩抽拉两用款结构,结构轻巧,优化成本,即插即用。


与市场上其他产品对比,重量减少约30%,包装体积减少约50%。




Hot and cold self-circulation system 冷热自循环系统工作原理展示

创新的冷热自循环散热系统独家蜂窝铝型材冷却材料







左上角放大图:是型材两端塑料件,设有透气孔,供室温空气进入型材。

如图所示:蓝色代表较低温空气流入方向 , 红色代表较热空气上升方向。 热气上升会导致型材内空气成负压 , 周围空气低于其温度会被大气压通过蜂窝 孔挤入型材 , 实现自循环冷热交替系统。

物理原理:

空气温度越高密度越小,空气温度越低密度越大。并且密度小的物质自然 上升运动,密度大的物质下沉运动。压强自平衡流动。

植物灯产品展示

LED grow light display

普威迅,人在"铝"途,觅光而行。在转型升级的重要关 口,遇到了指引企业继续前行的光。

这束光一半来于自己多年的行业优势 , 一半来自于植物光照 市场蓬勃发展的机遇,一半来自于生物光照的科技创新。

普威迅凭借自身散热和型材研发优势,配备相关技术人才, 创新生产生物光照产品。


突破行业关键性难题,多款产品引领市场研发方向,获得多 项发明专利,深受市场好评。

- 灯具(可伸缩式) LED light (retractable) ZL 2021 3 0486479.5
- 吊灯 (UFO) UFO grow light ZL2021 3 0499442.6
- 一种防尘防水灯管 Dustproof and waterproof tube ZL 2021 2 2705517.9
- 一种冷热空气自循环散热器 Heat and cold air self-circulating radiator ZL 2021 2 1737135.8
- 一种农作物促生长用匀光低热型光照补偿系统 The invention discloses a uniform light and low heat ight compensation system for promoting crop growth ZL 2019 1 0777940.4
- ■植物灯灯管 Tube LED grow light L20213 0481595.8

植物灯产品套件介绍 型号: PVS-B730

全球创新伸缩抽拉两用款结构,结 构轻巧,优化成本,即插即用。与市场 上其他产品对比,重量减少约30%,包 装体积减少约50%。

The globally innovative telescopic pull-out dual purpose structure is lightweight, optimized for cost, and plug and play. Compared with other products on the market, the weight is reduced by about 30% and the packaging volume is reduced by about 50%.







专利研发冷热自循环散热系统,极 致控温,保证光效,延缓光衰。与市场 上其他产品对比,温度多降低约30%。

Patented research and development of self-circulation cooling system of cold and heat, ultimate temperature control, ensure light efficiency and delay light decay. Compared with other products on the market, the temperature is reduced by about 30%.


ITEM NO.	PVS-B730			
DESCRIPTION	PVISUNG 730W			
PPF	1940 μmol/s			
EFFICACY	2.732 μmol/J			
FREQUENCY	50/60 Hz			
EMITTING COLOUR	WHITE 5000K + WHITE 3000K + RED 660nm+ SUNLIKE			
LED CHIP	Samsung & Epistar & Seoul SUNLIKE			
LED QUANTITY	1860pcs			
DRIVER	Sosen			
	Stretch size: 42.1" L x 41.9" W x 3.56" H (1070x1064x90.4mm)			
PRODUCT SIZE	Shrink size:12.4" L x 41.9" W x 3.56" H (316x1064x90.4mm)			
PACKAGING DIMENSIONS	43.7"L x 17.3"W x4.3"H (1110X440X110mm)			
N.W./G.W.:	8.4/9.75KGS			
CUSTOMIZATION	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM			



植物灯产品介绍 型号: PVS-B1000

全球创新伸缩抽拉两用款结构,结 构轻巧,优化成本,即插即用。与市场 上其他产品对比,重量减少约30%,包 装体积减少约50%。

The globally innovative telescopic development of self-circulation pull-out dual purpose structure is lightweight, optimized for cost, and plug and play. Compared with other products on the market, the weight is reduced by about 30% and the packaging volume is reduced by about 50%.





专利研发冷热自循环散热系统,极 致控温,保证光效,延缓光衰。与市场 上其他产品对比,温度多降低约30%。

Patented research and cooling system of cold and heat, ultimate temperature control, ensure light efficiency and delay light decay.

Compared with other products on the market, the temperature is reduced by about 30%.


						1111		шет		LN	/130	1B/		552
	2003	109		078 3308 1	1971	2139 9 10 1131 1236 10 10 10 10 10 10 10 10 10 10 10 10 10	14 873 674 46	7 234	313	612 652 652 731 1960 659 659 617	936 936 1 110 1160 1100 944 665 770	2037 903 2037 903 2036 902	CAST 27 CAST 27 CAST 27 CAST 28 CAST 2	5 297
70	186	F	IE	IG	HT (OF 1	12"	194	Н	EIGI	HT C)F 1	7.7	37

	ITEM NO.	PVS-B1000				
	DESCRIPTION	PVISUNG 1000W				
	PPF	2663 μmol/s				
	EFFICACY	2.896µmol/J				
	FREQUENCY	50/60 Hz				
	EMITTING COLOUR	WHITE 5000K + WHITE 3000K + RED 660nm+ SUNLIKE				
	LED CHIP	Samsung & Epistar & Seoul SUNLIKE				
	LED QUANTITY	2604pcs				
	DRIVER	Sosen				
	DDODUOT OUT	Stretch size: 63.8"L x 42"W x 3.56"H (1620x1067x90.4mm)				
	PRODUCT SIZE	Shrink size:17.3"L x 42"W x 3.56"H (439x1067x90.4mm)				
Ž.	PACKAGING DIMENSIONS	43.7"L x 22.8"W x4.3"H (1110X580X110mm)				
À	N.W./G.W.:	11.05/13.05KGS				
	CUSTOMIZATION	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM				

植物灯产品介绍 型号: PVS-D150

工业级表面处理,呼吸式UFO电 源,家用植物灯。


Industrial grade surface treatment, breathing UFO power supply, household plant lamps.







ITEM NO.	PVS-D150			
DESCRIPTION	PVISUNG 150W			
PPF	395 μmol/s			
EFFICACY	2.70 μmol/J			
FREQUENCY	50/60 Hz			
EMITTING COLOUR	WHITE 5000K + WHITE 3000K + RED 660nm+IR 730nm			
LED CHIP	Samsung & Epistar & Seoul SUNLIKE			
LED QUANTITY	476pcs			
DRIVER	Sosen			
PRODUCT SIZE	20.1"L x 9.45"W x 3.54"H (510x240x90mm)			
PACKAGING DIMENSIONS	22.83"L x 10.73"W x 5.98"H (580x272.5x152mm)			
N.W./G.W.	3.05/4.01KGS			
CUSTOMIZATION	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM			









LM301B/H

HEIGHT OF 12"

HEIGHT OF 17.7"



植物灯产品介绍 型号: PVS-D320

工业级表面处理,呼吸式UFO电 源,我们不一样!

Industrial grade surface treatment, breathing UFO power supply, we are different!











ITEM NO.	PVS-D320				
DESCRIPTION	PVISUNG 320W				
PPF	787 µmol/s				
EFFICACY	2.61 μmol/J				
FREQUENCY	50/60 Hz				
EMITTING COLOUR	WHITE 5000K + WHITE 3000K + RED 660nm+IR 730nm				
LED CHIP	Samsung & Epistar & Seoul SUNLIKE				
LED QUANTITY	1020pcs				
DRIVER	Sosen				
PRODUCT SIZE	20.1"L x 18.9"W x 3.54"H (510x480x90mm)				
PACKAGING DIMENSIONS	22.83"L x 21.46"W x 5.98"H (580x545x152mm)				
N.W./G.W.	5.35/6.55KGS				
CUSTOMIZATION	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM				



LM301B/H





HEIGHT OF 17.7"


HEIGHT OF 12"



植物灯产品介绍 型号: PVS-T36


单管V型双灯条广角,科技简约的 外观,植物工厂、禽类、畜牧工厂应用。

Single tube V double light strip wide angle, with a minimalist appearance, suitable for use in plant factories, poultry, and animal husbandry factories.



V Angle wide Angle

ITEM NO.	PVS-T36A	PVS-T36B	PVS-T36C	PVS-T36D	PVS-T36E	
DESCRIPTION	PVISUNG 36W	PVISUNG 36W	PVISUNG 36W	PVISUNG 36W	PVISUNG 36W	
PPF	77.03	96.78	78.98	81.64	79.8	
EFFICACY	2.07	2.5	1.923	2.069	2.049	
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	
EMITTING COLOUR	Warm White+Red+Blue+UV+IR	Red+Blue+IR	Red+Blue+IR	Red+Blue+IR	Red+Blue+IR	
SPECTRUM	Root seedling	Cannbis seedling	Leaf vegetable seedling	Fruits and vegetables	Herb	
LED CHIP	Nationstar & Customization	Nationstar & Customization	Nationstar & Customization	Nationstar & Customization	Nationstar & Customization	
150 011115777	208pcs	208pcs	208pcs	208pcs	208pcs	
LED QUANTITY	or Customization	or Customization	or Customization	or Customization	or Customization	
PRODUCT SIZE 41.4"L x 1.34"W x 1.2"H L1050mm*W34mm*H30mm		41.4"L x 1.34"W x 1.2"H L1050mm*W34mm*H30mm	41.4"L x 1.34"W x 1.2"H L1050mm*W34mm*H30mm	41.4"L x 1.34"W x 1.2"H L1050mm*W34mm*H30mm	41.4"L x 1.34"W x 1.2"H L1050mm*W34mm*H30mm	
PACKAGING 43.3"L x 3.94"W x 2.76"H DIMENSIONS (1PCS (1100x100x70mm)		43.3"L x 3.94"W x 2.76"H (1100x100x70mm)	43.3"L x 3.94"W x 2.76"H (1100x100x70mm)	43.3"L x 3.94"W x 2.76"H (1100x100x70mm)	43.3"L x 3.94"W x 2.76"H (1100x100x70mm)	
N.W./G.W.;	0.46/0.8KGS	0.46/0.8KGS	0.46/0.8KGS	0.46/0.8KGS	0.46/0.8KGS	
CUSTOMIZATION	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV IR / ODM / OEM	Spectrum / LED Chip / Logo / Fixture Color / Packaging / UV I / ODM / OEM	





— 工程项目Project —









一 荣誉证书Honor Certificate

















































— 战略合作伙伴Strategic Partners —





















