





Oxygen Sensor Disassembly tool

	<p>JXSS041A Squire Drive size: 3/8 "(10mm) Inside diameter: 7/8 "(22mm) Slot width: 0.38 "(9.7mm) Slot length: 30.7 mm</p>		<p>JXSS041B Drive size: 3/8 "(10mm) Inside diameter: 7/8 "(22mm) Slot width: 0.38 "(9.7mm) Slot length: 50mm</p>		<p>JXSS041C Squire Drive size: 3/8 "(10mm) Inside diameter: 7/8 "(22mm) Length: 80 mm Opening: 8 mm</p>		<p>JXSS041D-36 36mm Oil Filter Socket Hexagonal Drive: 3/8" Hex: 6-Point, 36-millimeter</p>
	<p>JXSS041E-L Squire Drive size: 1/2"(12.5mm) Inside diameter : 7/8"(22mm) Length: 3"(90mm) Slot: 67mm Opening: 27mm</p>		<p>JXSS041E-S Squire Drive size: 1/2"(12.5mm) Inside diameter : 7/8"(22mm) Length: 3"(90mm) Slot: 67mm Opening: 8mm</p>		<p>JXSS041F Drive size: 3/8"(10mm) Inside diameter : 7/8"(22mm) Length: 80mm Slot: 31mm Opening: 8mm</p>		<p>JXSS041G Thread chaser Outer Hexagonal 20mm, length: 40mm thread M18*1.5</p>
	<p>JXSS041-3</p>		<p>JXSS041-4</p>		<p>JXSS041-5</p>		<p>JXSS041-7</p>
	<p>JXSS041-10</p>						