

# Ecome ET-D446

## DMR Digital Walkie-talkie

### Features

1. Time-out Timer(TOT)
2. Channel scan
3. Remote kill and activation
4. Emergency alert
5. 24 groups of voice encryption
6. Single call/group call/all call



## SPECIFICATION

**Ecome**<sup>®</sup>

### General

Frequency Range	UHF: 400 ~ 470 MHz
Memory Channel	16
Battery Capacity	3800mAh
Frequency Stability	±2.5ppm
Operating Temperature	-20℃~ +50℃
Operating Voltage	DC 7.4V
Dimension	132 × 60 × 39mm
Weight	About 274g(include the battery & antenna)

### Transmission Part

Output Power	5W
Modulation	16K0F3E / 11K0F3E
Frequency Stability	±2.5ppm
Maximum Frequency Deviation	±2.5KHz
Adjacent Channel Power Ratio	≤ -65dB / ≤-60dB
Signal to noise Ratio	≤ -40dB / ≤-35dB
CTCSS	0.7±0.1KHz / 0.4±0.1KHz
Modulation Sensitivity	8-12mV
Transmission Current	±1.4A

### Reception Part

Receiving Sensitivity	-121dBm
Adjacent Channel Selectivity	≥60dB
Audio Output Power	1W@16Ω
Intermodulation	≥60dB
Spurious Suppression	≥60dB
Audio Distortion	≤5%

### Standard Accessories



Scan for more of our products