



ENABLING CURRENT AND FUTURE CRITICAL COMMUNICATIONS

# MTM5200 TETRA MOBILE RADIO

The **MTM5200** is the base model in the new series of TETRA radios. It shares the enhanced audio and receiver sensitivity of the current MTM5400, as well as being TEDS-ready for high speed data service which will enhance operation.

## MTM5200 BENEFITS

### SUPERIOR AUDIO PERFORMANCE

- Next generation audio architecture delivering the loudest and clearest audio performance of any Motorola TETRA mobile available on the market\*

### HIGH SPEED DATA CONNECTIVITY

- TEDS Ready hardware - with a simple software license upgrade, enables 20x faster data connectivity for accessing back-office systems and databases
- Integrated USB 2.0 PEI, enabling rapid radio programming and standardised interfacing to data terminals and accessories. For additional flexibility, USB host and slave modes are also supported

### LOW USER MIGRATION COSTS

- Familiar cellular style user interface and VGA colour display for enhanced usability and reduced staff training costs
- Same user interface as market proven MTP850 portable and MTM800 Enhanced mobile radios
- Re-use of MTM800 Enhanced accessories using GCAI connector

### ENHANCED END TO END ENCRYPTION OPTIONS

- Integrated hardware for SIM based end to end encryption
- Universal Crypto Module option

### ADVANCED TERMINAL MANAGEMENT

- USB 2.0 interface for fast radio programming via Motorola's integrated Terminal Management solution

### FLEXIBLE INSTALLATION OPTIONS

- Fully DIN-A compatible and available in Dash, Desk, Remote Head and Motorcycle mount formats
- Supports multiple control heads - an ideal solution for installations in trains, ambulances and fire vehicles where more than one control point might be required

### RUGGED DESIGN WITH EXCEPTIONAL RELIABILITY

- Includes IP67 control head option for exposed and challenging environments
- Front and Rear rugged GCAI connector for reliable connection of audio and data peripheral equipment
- Mobile radio and accessories are performance matched for enhanced reliability.

\* Assuming the appropriate audio accessory is used

**PRODUCT SPEC SHEET**  
MTM5200

**MODEL - COMPLIANCE WITH DIN 75490 (ISO 7736)**

Dash	Compact radio for fast vehicle installation
Desk	Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker
Motorcycle	Environmentally enhanced radio meeting IP67 specification. Suitable for demanding environments such as motorcycle, fire appliance and marine installations
Expansion head "Databox"	Radio without a control head, for data applications, or customised application development

**GENERAL**

	Dimensions HxWxD (mm)	Weight Typical (g)
Dash and Desk models (transceiver + control head)	60x188x198	1300
Transceiver only	45x170x169	1070
Standard control head	60x188x31	230
Remote control head	60x188x39	300
Motorcycle control head	60x188x39	320

**USER INTERFACE & DISPLAY**

Display	Diagonal dimension	2.8"
	Type	VGA - 640x480 pixels Transflective TFT, 65,000 colours
	Backlight	Variable backlight, User configurable
	Font sizes	Standard & Zoom mode (90 pixels, 4.5mm high) characters
Buttons & Keypad	Numeric	Integral backlit numeric keypad of 12 keys, with keypad lock option
	International keypad versions	Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters
	Programmable function keys	3 programmable function keys (plus 10 programmable numeric keys)
	Navigation	4-way navigation key, menu and soft keys
	Emergency	Emergency button with backlight
Rotary	Shortcuts	User configurable shortcuts to menus and common features using "One-Touch-Button" feature
	Dual Function	Talkgroup and volume change with lock option
Indication	LED	Tri-colour LED
	Tones	Configurable notification tones
User Interface Languages	Standard Options	Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish
	User defined	User programmable, using ISO 8859-1 character
Menu		Tailored to user needs
		Menu Shortcuts
		Menu Configuration
Contacts Management		Cellular Type
Contact List		Up to 1000 contacts
		Up to 6 numbers per contact, Max 2000 numbers
Multiple Dialling Methods		User selects how to dial
Fast/Flexible Call Response		Private Call Response to a Group Call via One Touch Button
Multiple Ring Tones		Configurable with CPS
Message Manager		Cellular Type
Text message list		20
Intelligent Keypad Text Input		All Control Heads
Status list		100
Country/Network Code List		100
Scan lists		40 lists of 20 groups
Discrete Mode		All Control Heads
Screen Saver		gif image & text (any user's selection)
Universal Time Display		All Control Heads
Keypad Lock		All Control Heads
Talkgroup Folders		Dual layer folder structure (folder/subfolder)
		256 folders
Favourite Folders		Up to 3 (to store any favourite talkgroup)

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature (°C)		-30 to +60
Storage Temperature (°C)		-40 to +85
Not in use - Storage	ETSI 300 019-1-1 CLASS 1.3	Non-Weather Protected Storage Locations
Not in use - Transportation	ETSI 300 019-1-2 CLASS 2.3	Public Transportation
Stationary use - Weather Protected Locations	ETSI 300 019-1-3 CLASS 3.2	Partly Temperature Controlled Locations
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5.2	Climatic Tests
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5M3	Mechanical Tests
MIL STD	810 C/D/E/F Specifications	All 11 categories met (or exceeded)
Dust and Water Ingress Protection	IP54 (dust cat. 2)	Dash/Desk/Remote models
	IP67	Motorcycle model (only control head is IP67; transceiver is IP54)

**EXPANSION HEAD OPTIONS**



EXPANSION HEAD (SINGLE STD CONNECTION)



EXPANSION HEAD ENHANCED STD AND AUXILIARY 25 PIN AND RS232

**CONTROL HEAD OPTIONS**



STANDARD CONTROL HEAD



REMOTE CONTROL HEAD



IP67 CONTROL HEAD

**PRODUCT SPEC SHEET**  
MTM5200

**ELECTRICAL SPECIFICATIONS**

Voltage Range		10.8 to 15.6 V DC
Current Consumption (A, typ.)	Idle / Rx / Tx @ 3W	0.5 / 1.0 / .9 (TX 2.2A Peak)
	Tx - TEDS @ 3W	2.3
	Using USB host	Adds 0.5A

**RF SPECIFICATIONS**

Frequency Bands (MHz)		350 – 390, 380 – 430, 410 – 470	806 – 870
Transmit / Receive Separation (MHz)		10	45
RF Channel Bandwidth (kHz)		25	
Transmitter RF Power	TETRA Release 2 (TEDS)	3W, Class 3	
RF Power Control	6 Power Step Levels (steps of 5 dBm)	Starting at 15 dBm; finishing at 40 dBm	
Receiver Class		A & B	
Receiver Static Sensitivity (dBm)		-114 minimum, -116 typical (ETSI 300-392-2)	
Receiver Dynamic Sensitivity (dBm)		-105 minimum, -107 typical (ETSI 300-392-2)	

**GPS SPECIFICATIONS**

Simultaneous Satellites		12
Mode of Operation		Autonomous or assisted (A-GPS)
GPS Antenna		Supports active antenna (5V, 25mA supply)
Autonomous Acquisition Sensitivity		-143 dBm / -173 dBW
Tracking Sensitivity		-159 dBm / -189 dBW
Accuracy		<5m (50% probable) <10m (95% probable)
TTFF (HOT Start - Autonomous)		<1s
TTFF (WARM Start - Autonomous)		<36s
TTFF (COLD Start - Autonomous)		<36s
Location Protocols		ETSI Location Information Protocol (LIP) Motorola LRRP

**VOICE SERVICES**

Talkgroups		2048 (TMO) & 1024 (DMO)
Phone book entries		1000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2000 entries
Scan lists		40 lists of 20 talkgroups
Trunked Mode (TMO) Services	Group call	Late Entry, TMO/DMO Mapping
	Private call	Half / Full Duplex
	Telephony (PABX, PSTN, MS-ISDN)	Full Duplex
	DGNA	Up to 2047 groups
	Scanning	Attachment signalling, supports SWMI initiated attachment/detachment
Direct Mode (DMO) Services		Group call Private call
Emergency (tailored by users)	Tactical	Emergency Group Call to ATTACHED talkgroup
	Non-Tactical	Emergency Group Call to DEDICATED talkgroup
	Individual	Emergency Call to PREDEFINED party (half/full duplex)
	Smart emergency	TMO/DMO/DMO to TMO automatic switching options
	Hot Mic	Configurable timers for automatic open mic (talk without PTT)
	Location	Location (GPS) sent with emergency
	Target Address	Sent to individual or group address (selected or dedicated)
Alarm (status message)		Emergency Status (or other pre-defined status)

**INTERFACES**

RS232		For PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT)
USB	USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)	
	USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming	
	USB On-The-Go (host & slave) capability for intelligent PEI applications	
	USB 1.1 support (Host Mode) to manage USB Slave Devices (e.g. SIM CARD READER)	
Rugged Accessory Connector (GCAI)		GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming
General Purpose Input/Output	Digital I/O	7 (4 on remote and motorcycle control head, 3 on transceiver)
	Analog input	4 (1 on remote and motorcycle control head, with 4 levels)

**INSTALLATION OPTIONS**

**DASH MOUNT - CAR, TRUCK**



**DESK MOUNT - CONTROL CENTRE**



**REMOTE HEAD MOUNT - CAR, AMBULANCE, FIRE TRUCK**



**IP67 MOUNT - BOAT, MOTORCYCLE**



**PRODUCT SPEC SHEET**  
MTM5200

DATA SERVICES		
Status	Alias messages	400 Entries
	Options	Can be sent via One-Touch or via menu
Short Data Service (SDS)	Inbox	200 Entries (short messages), 40 Entries (long messages of up to 1000 characters)
	Cellular style iTAP predictive text entry	
	Target Address	Sent to individual or group address (selected or dedicated)
	Voice Call Interaction	SDS messages can be sent and received during a voice call
Packet Data (PD)	Multi-slot PD	Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross
	TETRA Enhanced Data Service (TEDS) (via software upgrade)	Supporting 25kHz and 50kHz channel bandwidths and enabling practical data rates of up to 80kbit/s
TEDS (capable)		QAM Channels: 25 kHz and 50 kHz (but not D8PSK channels)
		QAM modulation/coding modes: 4-QAM R1/2, 16-QAM R1/2, 64-QAM R1/2, and 64-QAM R2/3
WAP	Integrated WAP browser (including WAP-PUSH)	Integrated Openwave browser
		WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack
Peripheral Equipment Interface (PEI)	Interface Protocol	AT Commands - Full Set ETSI Mandatory Compliant
		AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS)
		TNP1; enables simultaneous PD and SDS sessions
Terminal Management	Programmable via Motorola Integrated Terminal Management (ITM) solution	
	Over-The-Air Programming (OTAP) Mode* Capable	Background Mode PBackground Mode Programming (BMP) capable* - while radio is operational (providing TETRA services) it is being programmed/configured. * Planned features with software upgrade

SECURITY FEATURES		
Air Interface Encryption	Algorithms	TEA1, TEA2, TEA3
	Security Classes	Class 1 (Clear), Class 2 (SCK), Class 3G
	Authentication	Infrastructure initiated and made mutual by terminal
Provisioning		Secure provisioning tool via Key Variable Loader (KVL)
User Access Control		PIN/PUK code access
	Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation	Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure
Data		Packet Data user authentication
End to End Encryption (EtEE)	Voice E2EE	
	Packet Data E2EE	Enhanced End to End Encryption with OTAR supported through Universal Crypto Module (UCM) and SIM (via integrated card slot)
	Short Data (SDS) E2EE	

REGULATORY COMPLIANCE	
Radio (R&TTE Article 3.2)	EN 303 035-1
	EN 303 035-2
	ETSI EN 300-394-1
	ETSI EN 300-392-2
EMC (R&TTE Article 3.1.b)	EN 301 489-1 V1.3.1
	EN 301 489-18 V1.3.1
Electrical Safety (R&TTE Article 3.1.a)	EN 60950-1 (2001)
	EN50360:2001 EME
Environmental	Directive 2002/96/EC WEE
	Directive e2002/95/EC RoHS
Automotive	E-mark, Automotive EMC Directive 95/54/EC

To learn more, visit us on the web at: [motorolasolutions.com/MTM5200](http://motorolasolutions.com/MTM5200)

**Motorola Solutions Singapore Pte Ltd**

12 Ang Mo Kio Street 64, Ang Mo Kio Industrial Park 3, UE Biz Hub, Block A, Level 7 Singapore 569088 [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2015 Motorola Solutions, Inc. All rights reserved.

MTM5200 SPEC SHEET\_Rev.2\_250315

