



## ENABLING CURRENT AND FUTURE CRITICAL COMMUNICATIONS

# MTM5400 TETRA MOBILE RADIO

The **MTM5400** includes high power modes and the Gateway Repeater functionality features required by a number of end users.

## MTM5400 BENEFITS

### SUPERIOR AUDIO PERFORMANCE

- Next generation audio architecture delivering the loudest and clearest audio performance of any Motorola TETRA mobile available on the market\*

### HIGH SPEED DATA CONNECTIVITY

- TEDS Ready hardware - with a simple software license upgrade, enables 20x faster data connectivity for accessing back-office systems and databases
- Integrated USB 2.0 PEI, enabling rapid radio programming and standardised interfacing to data terminals and accessories. For additional flexibility, USB host and slave modes are also supported

### LOW USER MIGRATION COSTS

- Familiar cellular style user interface and VGA colour display for enhanced usability and reduced staff training costs
- Same user interface as market proven MTP850 portable and MTM800 Enhanced mobile radios
- Re-use of MTM800 Enhanced accessories using GCAI connector

### ENHANCED END TO END ENCRYPTION OPTIONS

- Integrated hardware for SIM based end to end encryption
- Universal Crypto Module option

### ADVANCED TERMINAL MANAGEMENT

- USB 2.0 interface for fast radio programming via Motorola's integrated Terminal Management solution

### FLEXIBLE INSTALLATION OPTIONS

- Fully DIN-A compatible and available in Dash, Desk, Remote Head and Motorcycle mount formats
- Supports multiple control heads - an ideal solution for installations in trains, ambulances and fire vehicles where more than one control point might be required

### RUGGED DESIGN WITH EXCEPTIONAL RELIABILITY

- Includes IP67 control head option for exposed and challenging environments
- Front and Rear rugged GCAI connector for reliable connection of audio and data peripheral equipment
- Mobile radio and accessories are performance matched for enhanced reliability.

\* Assuming the appropriate audio accessory is used

# MTM5400

## EXPANSION HEAD OPTIONS



**EXPANSION HEAD**  
(SINGLE STD CONNECTION)



**EXPANSION HEAD ENHANCED**  
STD AND AUXILIARY 25 PIN AND RS232

## CONTROL HEAD OPTIONS



**STANDARD CONTROL HEAD**



**REMOTE CONTROL HEAD**



**IP67 CONTROL HEAD**

## INSTALLATION OPTIONS



**DASH MOUNT -**  
CAR, TRUCK



**REMOTE HEAD MOUNT -**  
CAR, AMBULANCE, FIRE TRUCK

UP TO 10m



**IP67 MOUNT -**  
BOAT, MOTORCYCLE

UP TO 10m



**DESK MOUNT -**  
CONTROL CENTRE



USER SUPPLIED TERMINAL

**DATA ONLY INSTALLATION**

**PRODUCT SPEC SHEET**  
MTM5400

**MODEL - COMPLIANCE WITH DIN 75490 (ISO 7736)**

|                          |                                                                                                                                                               |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dash                     | Compact radio for fast vehicle installation                                                                                                                   |
| Desk                     | Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker                                             |
| Motorcycle               | Environmentally enhanced radio meeting IP67 specification.<br>Suitable for demanding environments such as motorcycle, fire appliance and marine installations |
| Expansion head "Databox" | Radio without a control head, for data applications, or customised application development                                                                    |

**GENERAL**

|                                                   | Dimensions HxWxD (mm) | Weight Typical (g) |
|---------------------------------------------------|-----------------------|--------------------|
| Dash and Desk models (transceiver + control head) | 60x188x198            | 1300               |
| Transceiver only                                  | 45x170x169            | 1070               |
| Standard control head                             | 60x188x31             | 230                |
| Remote control head                               | 60x188x39             | 300                |
| Motorcycle control head                           | 60x188x39             | 320                |

**USER INTERFACE & DISPLAY**

|                               |                               |                                                                                                                                                                                                                                   |
|-------------------------------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display                       | Diagonal dimension            | 2.8"                                                                                                                                                                                                                              |
|                               | Type                          | VGA - 640x480 pixels Transflective TFT, 65,000 colours                                                                                                                                                                            |
|                               | Backlight                     | Variable backlight, User configurable                                                                                                                                                                                             |
|                               | Font sizes                    | Standard & Zoom mode (90 pixels, 4.5mm high) characters                                                                                                                                                                           |
| Buttons & Keypad              | Numeric                       | Integral backlit numeric keypad of 12 keys, with keypad lock option                                                                                                                                                               |
|                               | International keypad versions | Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters                                                                                                                                                                    |
|                               | Programmable function keys    | 3 programmable function keys (plus 10 programmable numeric keys)                                                                                                                                                                  |
|                               | Navigation                    | 4-way navigation key, menu and soft keys                                                                                                                                                                                          |
|                               | Emergency                     | Emergency button with backlight                                                                                                                                                                                                   |
|                               | Shortcuts                     | User configurable shortcuts to menus and common features using "One-Touch-Button" feature                                                                                                                                         |
| Rotary                        | Dual Function                 | Talkgroup and volume change with lock option                                                                                                                                                                                      |
| Indication                    | LED                           | Tri-colour LED                                                                                                                                                                                                                    |
|                               | Tones                         | Configurable notification tones                                                                                                                                                                                                   |
| User Interface Languages      | Standard Options              | Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish |
|                               | User defined                  | User programmable, using ISO 8859-1 character                                                                                                                                                                                     |
| Menu                          |                               | Tailored to user needs                                                                                                                                                                                                            |
|                               |                               | Menu Shortcuts                                                                                                                                                                                                                    |
|                               |                               | Menu Configuration                                                                                                                                                                                                                |
| Contacts Management           |                               | Cellular Type                                                                                                                                                                                                                     |
| Contact List                  |                               | Up to 1000 contacts                                                                                                                                                                                                               |
|                               |                               | Up to 6 numbers per contact, Max 2000 numbers                                                                                                                                                                                     |
| Multiple Dialling Methods     |                               | User selects how to dial                                                                                                                                                                                                          |
| Fast/Flexible Call Response   |                               | Private Call Response to a Group Call via One Touch Button                                                                                                                                                                        |
| Multiple Ring Tones           |                               | Configurable with CPS                                                                                                                                                                                                             |
| Message Manager               |                               | Cellular Type                                                                                                                                                                                                                     |
| Text message list             |                               | 20                                                                                                                                                                                                                                |
| Intelligent Keypad Text Input |                               | All Control Heads                                                                                                                                                                                                                 |
| Status list                   |                               | 100                                                                                                                                                                                                                               |
| Country/Network Code List     |                               | 100                                                                                                                                                                                                                               |
| Scan lists                    |                               | 40 lists of 20 groups                                                                                                                                                                                                             |
| Discrete Mode                 |                               | All Control Heads                                                                                                                                                                                                                 |
| Screen Saver                  |                               | gif image & text (any user's selection)                                                                                                                                                                                           |
| Universal Time Display        |                               | All Control Heads                                                                                                                                                                                                                 |
| Keypad Lock                   |                               | All Control Heads                                                                                                                                                                                                                 |
| Talkgroup Folders             |                               | Dual layer folder structure (folder/subfolder)                                                                                                                                                                                    |
|                               |                               | 256 folders                                                                                                                                                                                                                       |
| Favourite Folders             |                               | Up to 3 (to store any favourite talkgroup)                                                                                                                                                                                        |

**ENVIRONMENTAL SPECIFICATIONS**

|                                              |                            |                                                                   |
|----------------------------------------------|----------------------------|-------------------------------------------------------------------|
| Operating Temperature (°C)                   |                            | -30 to +60                                                        |
| Storage Temperature (°C)                     |                            | -40 to +85                                                        |
| Not in use - Storage                         | ETSI 300 019-1-1 CLASS 1.3 | Non-Weather Protected Storage Locations                           |
| Not in use - Transportation                  | ETSI 300 019-1-2 CLASS 2.3 | Public Transportation                                             |
| Stationary use - Weather Protected Locations | ETSI 300 019-1-3 CLASS 3.2 | Partly Temperature Controlled Locations                           |
| Mobile use - Ground Vehicle Installation     | ETSI 300 019-1-5 CLASS 5.2 | Climatic Tests                                                    |
| Mobile use - Ground Vehicle Installation     | ETSI 300 019-1-5 CLASS 5M3 | Mechanical Tests                                                  |
| MIL STD                                      | 810 C/D/E/F Specifications | All 11 categories met (or exceeded)                               |
| Dust and Water Ingress Protection            | IP54 (dust cat. 2)         | Dash/Desk/Remote models                                           |
|                                              | IP67                       | Motorcycle model (only control head is IP67; transceiver is IP54) |

**PRODUCT SPEC SHEET**  
MTM5400

**ELECTRICAL SPECIFICATIONS**

|                               |                                     |                                |
|-------------------------------|-------------------------------------|--------------------------------|
| Voltage Range                 |                                     | 10.8 to 15.6 V DC              |
| Current Consumption (A, typ.) | Idle / Rx / Tx @ 10W                | 0.5 / 1.0 / 1.2 (TX 3.4A Peak) |
|                               | Idle / Rx / Tx @ 3W                 | 0.5 / 1.0 / .9 (TX 2.2A Peak)  |
|                               | Tx - Multi Slot PD (4 slots) @ 5.6W | 2.7                            |
|                               | Tx - TEDS @ 3W                      | 2.3                            |
|                               | Using USB host                      | Adds 0.5A                      |

**RF SPECIFICATIONS**

|                                     |                                             |                                                   |
|-------------------------------------|---------------------------------------------|---------------------------------------------------|
| Frequency Bands (MHz)               | 350 – 390, 380 – 430, 410 – 470             | 806 – 870                                         |
| Transmit / Receive Separation (MHz) | 10                                          | 45                                                |
| RF Channel Bandwidth (kHz)          | 25                                          |                                                   |
|                                     | TETRA Release 1                             | 10W, Class 2 Note: MSPD limited to 5.6W, Class 2L |
|                                     | TETRA Release 2 (TEDS)                      | 3W, Class 3                                       |
| RF Power Control                    | 6 Power Step Levels (steps of 5 dBm)        | Starting at 15 dBm; finishing at 40 dBm           |
| Transmitter RF Power                |                                             | A & B                                             |
| Receiver Class                      |                                             | A & B                                             |
| Receiver Static Sensitivity (dBm)   | -114 minimum, -116 typical (ETSI 300-392-2) |                                                   |
| Receiver Dynamic Sensitivity (dBm)  | -105 minimum, -107 typical (ETSI 300-392-2) |                                                   |

**GPS SPECIFICATIONS**

|                                    |                                                           |
|------------------------------------|-----------------------------------------------------------|
| Simultaneous Satellites            | 12                                                        |
| Mode of Operation                  | Autonomous or assisted (A-GPS)                            |
| GPS Antenna                        | Supports active antenna (5V, 25mA supply)                 |
| Autonomous Acquisition Sensitivity | -143 dBm / -173 dBW                                       |
| Tracking Sensitivity               | -159 dBm / -189 dBW                                       |
| Accuracy                           | <5m (50% probable) <10m (95% probable)                    |
| TTFF (HOT Start - Autonomous)      | <1s                                                       |
| TTFF (WARM Start - Autonomous)     | <36s                                                      |
| TTFF (COLD Start - Autonomous)     | <36s                                                      |
| Location Protocols                 | ETSI Location Information Protocol (LIP)<br>Motorola LRRP |

**VOICE SERVICES**

|                               |                                                                                |                                                                      |
|-------------------------------|--------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Talkgroups                    | 2048 (TMO) & 1024 (DMO)                                                        |                                                                      |
| Phone book entries            | 1000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2000 entries |                                                                      |
| Scan lists                    | 40 lists of 20 talkgroups                                                      |                                                                      |
| Trunked Mode (TMO) Services   | Group call                                                                     | Late Entry, TMO/DMO Mapping                                          |
|                               | Private call                                                                   | Half / Full Duplex                                                   |
|                               | Telephony (PABX, PSTN, MS-ISDN)                                                | Full Duplex                                                          |
|                               | DGNA                                                                           | Up to 2047 groups                                                    |
|                               | Scanning                                                                       | Attachment signalling, supports SWMI initiated attachment/detachment |
| Direct Mode (DMO) Services    | Group call                                                                     |                                                                      |
|                               | Private call                                                                   |                                                                      |
| Emergency (tailored by users) | Tactical                                                                       | Emergency Group Call to ATTACHED talkgroup                           |
|                               | Non-Tactical                                                                   | Emergency Group Call to DEDICATED talkgroup                          |
|                               | Individual                                                                     | Emergency Call to PREDEFINED party (half/full duplex)                |
|                               | Smart emergency                                                                | TMO/DMO/DMO to TMO automatic switching options                       |
|                               | Hot Mic                                                                        | Configurable timers for automatic open mic (talk without PTT)        |
|                               | Location                                                                       | Location (GPS) sent with emergency                                   |
|                               | Target Address                                                                 | Sent to individual or group address (selected or dedicated)          |
| Alarm (status message)        | Emergency Status (or other pre-defined status)                                 |                                                                      |

**INTERFACES**

|                                   |              |                                                                                                                                                                      |
|-----------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RS232                             |              | For PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT)                                    |
| USB                               |              | USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)                    |
|                                   |              | USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming |
|                                   |              | USB On-The-Go (host & slave) capability for intelligent PEI applications                                                                                             |
|                                   |              | USB 1.1 support (Host Mode) to manage USB Slave Devices (e.g. SIM CARD READER)                                                                                       |
| Rugged Accessory Connector (GCAI) |              | GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming                                                      |
| General Purpose Input/Output      | Digital I/O  | 7 (4 on remote and motorcycle control head, 3 on transceiver)                                                                                                        |
|                                   | Analog input | 4 (1 on remote and motorcycle control head, with 4 levels)                                                                                                           |

**GATEWAY SERVICES**

|                 |  |                                                                                             |
|-----------------|--|---------------------------------------------------------------------------------------------|
| DMO/TMO Gateway |  | Group voice calls from DMO to TMO                                                           |
|                 |  | Group voice calls from TMO to DMO                                                           |
|                 |  | Emergency group call from DMO to TMO                                                        |
|                 |  | Emergency group call from TMO to DMO                                                        |
|                 |  | Transmission of Gateway Presence Signal                                                     |
|                 |  | Automatic detection and management of co-located Gateways                                   |
|                 |  | Call Pre-emption (in either direction)                                                      |
|                 |  | SDS messaging from DMO to TMO (including GPS) or from TMO to DMO*                           |
|                 |  | Configurable routing of SDS messages to console or PEI                                      |
|                 |  | Intelligent handling of point to point calls and SDS messages whilst operating as a Gateway |

**REPEATER SERVICES**

|              |  |                                                                  |
|--------------|--|------------------------------------------------------------------|
| DMO Repeater |  | Repeats DMO voice                                                |
|              |  | Repeats SDS and Status messaging on selected talkgroup*          |
|              |  | ETSI type 1A DMO Repeater for channel efficient operation        |
|              |  | Transmission of Repeater Presence Signal                         |
|              |  | Priority Call                                                    |
|              |  | Emergency Call (Pre-emptive Priority Call)                       |
|              |  | E2EE Encrypted DMO traffic                                       |
|              |  | Monitoring of and participation in calls whilst in Repeater mode |
|              |  | Configurable Repeater Power Levels                               |

**DATA SERVICES**

|                                      |                                                                         |                                                                                                                                                                                                    |
|--------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status                               | Alias messages                                                          | 400 Entries                                                                                                                                                                                        |
|                                      | Options                                                                 | Can be sent via One-Touch or via menu                                                                                                                                                              |
| Short Data Service (SDS)             | Inbox                                                                   | 200 Entries (short messages), 40 Entries (long messages of up to 1000 characters)                                                                                                                  |
|                                      | Cellular style iTAP predictive text entry                               |                                                                                                                                                                                                    |
|                                      | Target Address                                                          | Sent to individual or group address (selected or dedicated)                                                                                                                                        |
|                                      | Voice Call Interaction                                                  | SDS messages can be sent and received during a voice call                                                                                                                                          |
| Packet Data (PD)                     | Multi-slot PD                                                           | Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross                                                                                                                            |
|                                      | TETRA Enhanced Data Service (TEDS) (via software upgrade)               | Supporting 25kHz and 50kHz channel bandwidths and enabling practical data rates of up to 80kbit/s                                                                                                  |
| TEDS (capable)                       |                                                                         | QAM Channels: 25 kHz and 50 kHz (but not D8PSK channels)                                                                                                                                           |
|                                      |                                                                         | QAM modulation/coding modes: 4-QAM R1/2, 16-QAM R1/2, 64-QAM R1/2, and 64-QAM R2/3                                                                                                                 |
| WAP                                  | Integrated WAP browser (including WAP-PUSH)                             | Integrated Openwave browser                                                                                                                                                                        |
|                                      |                                                                         | WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack                                                                                                                                               |
| Peripheral Equipment Interface (PEI) | Interface Protocol                                                      | AT Commands - Full Set ETSI Mandatory Compliant                                                                                                                                                    |
|                                      |                                                                         | AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS)                                                                                               |
| Terminal Management                  |                                                                         | TNP1; enables simultaneous PD and SDS sessions                                                                                                                                                     |
|                                      | Programmable via Motorola Integrated Terminal Management (iTM) solution |                                                                                                                                                                                                    |
|                                      | Over-The-Air Programming (OTAP) Mode* Capable                           | Background Mode PBackground Mode Programming (BMP) capable* - while radio is operational (providing TETRA services) it is being programmed/configured.<br>* Planned features with software upgrade |

**PRODUCT SPEC SHEET**

MTM5400

**SECURITY FEATURES**

|                              |                                                                                               |                                                                                                                                                                    |
|------------------------------|-----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Air Interface Encryption     | Algorithms                                                                                    | TEA1, TEA2, TEA3                                                                                                                                                   |
|                              | Security Classes                                                                              | Class 1 (Clear), Class 2 (SCK), Class 3G                                                                                                                           |
|                              | Authentication                                                                                | Infrastructure initiated and made mutual by terminal                                                                                                               |
| Provisioning                 |                                                                                               | Secure provisioning tool via Key Variable Loader (KVL)                                                                                                             |
| User Access Control          |                                                                                               | PIN/PUK code access                                                                                                                                                |
|                              | Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation | Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure |
| Data                         |                                                                                               | Packet Data user authentication                                                                                                                                    |
| End to End Encryption (EtEE) | Voice E2EE                                                                                    | Enhanced End to End Encryption with OTAR supported through Universal Crypto Module (UCM) and SIM (via integrated card slot)                                        |
|                              | Packet Data E2EE                                                                              |                                                                                                                                                                    |
|                              | Short Data (SDS) E2EE                                                                         |                                                                                                                                                                    |

**REGULATORY COMPLIANCE**

|                                         |                                           |
|-----------------------------------------|-------------------------------------------|
| Radio (R&TTE Article 3.2)               | EN 303 035-1                              |
|                                         | EN 303 035-2                              |
|                                         | ETSI EN 300-394-1                         |
|                                         | ETSI EN 300-392-2                         |
| EMC (R&TTE Article 3.1.b)               | EN 301 489-1 V1.3.1                       |
|                                         | EN 301 489-18 V1.3.1                      |
| Electrical Safety (R&TTE Article 3.1.a) | EN 60950-1 (2001)                         |
|                                         | EN50360:2001 EME                          |
| Environmental                           | Directive 2002/96/EC WEE                  |
|                                         | Directive e2002/95/EC RoHS                |
| Automotive                              | E-mark, Automotive EMC Directive 95/54/EC |

To learn more, visit us on the web at: [motorolasolutions.com/MTM5400](http://motorolasolutions.com/MTM5400)

**Motorola Solutions Singapore Pte Ltd**

12 Ang Mo Kio Street 64, Ang Mo Kio Industrial Park 3, UE Biz Hub, Block A, Level 7 Singapore 569088 [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2015 Motorola Solutions, Inc. All rights reserved.

MTM5400 SPEC SHEET\_250315\_Rev.2