

Model NO.	Nominal Capacity (mAh)	Voltage (V)	Dimensions			Approx. Weight (g)	Internal Impedance ( $\Omega$ )		Max Discharge Current		
			T $\pm 0.2$ mm	W $\pm 0.5$ mm	L $\pm 1.0$ mm				Continuous Discharge Current (C)	Burst Discharge Current (C)	Cut-off Voltage (V)
783496SP-2200	2200	3.7	7.6	34.0	97.0	51.0	$\leq 3.5$	2.6	25	50	2.75
564383HP-2400	2400	3.7	5.6	43.5	84.0	47.0	$\leq 3.5$	2.6	20	40	2.75
5042125SP-2500	2500	3.7	5.1	42.0	125.0	59.0	$\leq 3.5$	2.3	25	50	2.75
883496SP-2600	2600	3.7	8.7	34.0	97.0	58.0	$\leq 4.0$	2.3	25	50	2.75
855069P-2800	2800	3.7	8.2	50.0	69.5	59.0	$\leq 5.0$	3.0	8	20	2.75
784383HP-2900	2900	3.7	7.8	43.5	84.0	65.0	$\leq 3$	2.5	20	40	2.75
5243125SP-3000	3000	3.7	5.4	43.0	125.0	67.0	$\leq 3.0$	1.9	25	50	2.75
5243125HP-3200	3200	3.7	5.2	43.0	125.0	64.0	$\leq 3.0$	2.2	20	40	2.75
804383HP-3400	3400	3.7	8.0	43.5	84.0	67.0	$\leq 3$	2.2	20	40	2.75
953496P-3400	3400	3.7	9.3	34.0	97.0	66.0	$\leq 4.0$	2.2	10	20	2.75
5743125HP-3500	3500	3.7	5.7	43.0	125.5	69.0	$\leq 3$	1.7	20	40	2.75
<b>6043125HP-3700</b>	<b>3700</b>	<b>3.7</b>	<b>5.8</b>	<b>43.0</b>	<b>125.5</b>	<b>78.7</b>	<b><math>\leq 2.5</math></b>	<b>2.0</b>	<b>20</b>	<b>40</b>	<b>2.75</b>
814383HP-3750	3750	3.7	8.1	43.5	84.5	68.0	$\leq 3.5$	2.1	20	40	2.75
5643125HP-3900	3900	3.7	5.5	43.0	126.5	72.0	$\leq 3$	2.2	15	30	2.75
8634125P-3900	3900	3.7	8.4	34.0	125.0	77.0	$\leq 3.5$	2.3	10	20	2.75
6246148HP-4000	4000	3.7	6.2	46.0	148.0	91.0	$\leq 3$	2.1	20	40	2.75
8242125SP-4000	4000	3.7	8.0	42.0	125.0	93.5	$\leq 3$	1.4	25	50	2.75
7243125HP-4300	4300	3.7	7.2	43.0	125.0	86.0	$\leq 3$	2.1	20	40	2.75
7243125P-4800	4800	3.7	7.1	43.0	125.5	87.0	$\leq 3.0$	1.7	10	20	2.75
8043125HP-5000	5000	3.7	8.0	43.0	125.5	100.0	$\leq 3.5$	1.3	20	40	2.75
<b>8543125HP-5000</b>	<b>5000</b>	<b>3.7</b>	<b>8.5</b>	<b>43.0</b>	<b>125.5</b>	<b>119.2</b>	<b><math>\leq 2.0</math></b>	<b>1.26</b>	<b>20</b>	<b>40</b>	<b>2.75</b>
8843118HP-5000	5000	3.7	8.8	43.0	118.0	99.0	$\leq 3$	1.9	20	40	2.75
1043125SP-5200	5200	3.7	10.0	43.0	125.0	115.0	$\leq 3$	1.8	25	50	2.75
<b>8343128HP-5300</b>	<b>5300</b>	<b>3.7</b>	<b>8.5</b>	<b>43.4</b>	<b>128.0</b>	<b>112.7</b>	<b><math>\leq 2.0</math></b>	<b>1.1</b>	<b>20</b>	<b>40</b>	<b>2.75</b>
<b>9043125HP-5400</b>	<b>5400</b>	<b>3.7</b>	<b>8.7</b>	<b>43.0</b>	<b>125.5</b>	<b>107.6</b>	<b><math>\leq 2.0</math></b>	<b>1.26</b>	<b>20</b>	<b>40</b>	<b>2.75</b>
8045145HP-5500	5500	3.7	7.9	45.0	145.0	145.0	$\leq 4$	1.8	20	40	2.75
8246148HP-6000	6000	3.7	8.0	46.0	148.5	119.0	$\leq 3$	1.6	20	40	2.75
9743125HP-6000	6000	3.7	9.8	43.0	125.5	115.0	$\leq 3$	1.3	20	40	2.75
1046115P-6300	6300	3.7	10.3	46.0	115.0	120.0	$\leq 4$	1.6	8	20	2.75
9545120MP-6500	6500	3.7	9.5	45.0	120.5	114.0	$\leq 3.5$	1.5	5	10	2.75
<b>C8643125HP-5000</b>	<b>5000</b>	<b>3.7</b>	<b>8.4</b>	<b>43.0</b>	<b>125.5</b>	<b>95.4</b>	<b><math>\leq 2.0</math></b>	<b>1.13</b>	<b>15</b>	<b>30</b>	<b>2.75</b>
<b>C1043125HP-6000</b>	<b>6000</b>	<b>3.7</b>	<b>9.7</b>	<b>43.0</b>	<b>125.5</b>	<b>114</b>	<b><math>\leq 2.0</math></b>	<b>1.12</b>	<b>15</b>	<b>30</b>	<b>2.75</b>
H564383HP-2700	2700	3.8	5.6	43.3	84.0	48.0	$\leq 6.0$	3.4	15	30	2.75
H5643125P-4000	4000	3.8	5.4	43.0	125.5	67.0	$\leq 3.5$	2.3	10	20	2.75
H5643125HP-4500	4500	3.8	5.6	43.0	126.0	73.0	$\leq 3.5$	2.0	10	20	2.75
H8545145HP-5600	5600	3.8	7.6	44.5	145.0	106.0	$\leq 3.5$	1.6	15	30	2.75
H1046115P-7000	7000	3.8	10.3	46.0	115.0	120.0	$\leq 4$	1.6	8	20	2.75
H8059156P-8700	8700	3.8	7.8	59.0	156.5	152.0	$\leq 4$	1.2	8	20	2.75
H9574106MP-10000	10000	3.8	9.4	74.0	106.0	162.0	$\leq 3.5$	1.2	5	10	2.75
S5643125HP-3500	3500	3.7	5.4	42.5	125.5	67.0	$\leq 3$	2.2	20	40	2.75
S6545145SP-4000	4000	3.7	6.3	44.5	144.5	89.0	$\leq 3$	2.1	25	50	2.75
S8843125HP-5000	5000	3.7	8.7	42.5	125.5	101.0	$\leq 3$	1.3	20	40	2.75
S8545145SP-5300	5300	3.7	8.4	45.0	145.0	116.0	$\leq 3.5$	1.1	25	50	2.75
S1145180SP-7600	7600	3.7	10.1	45.0	180.0	165.0	$\leq 3$	0.9	25	50	2.75

Model NO.	Nominal Capacity (mAh)	Voltage (V)	Dimensions			Approx. Weight (g)	Internal Impedance ( $\Omega$ )		Max Discharge Current		
			T $\pm 0.2$ mm	W $\pm 0.5$ mm	L $\pm 1.0$ mm				Continuous Discharge Current (C)	Burst Discharge Current (C)	Cut-off Voltage (V)
823496HT-2200	2200	3.7	8.4	34.0	97.0	54.6	$\leq 2.5$	1.45	60	100	2.75
7644132ET-3350	3350	3.7	7.4	44.0	136.0	85.9	$\leq 3$	0.97	60	180	2.75
8067102TP-4800	4800	3.7	7.4	66.0	104.0	111.4	$\leq 2$	0.97	30	120	2.75
8867135HT-6800	6800	3.7	8.3	67.0	135.0	166	$\leq 2$	0.62	60	100	2.75
C386786HT-1800	1800	3.7	3.8	67.0	87.0	46	$\leq 4$	2.2	60	120	2.75
C426888TP-2000	2000	3.7	4.0	67.5	88.0	57	$\leq 4$	2.0	30	120	2.75
C4442125TP-2000	2000	3.7	4.4	43.0	125.5	51	$\leq 3$	2.3	30	100	2.75
C536080HT-2000	2000	3.7	5.3	60.0	82.0	50.9	$\leq 3$	2.25	60	120	2.75
C526085HT-2100	2100	3.7	5.2	60.0	85.5	53	$\leq 3$	1.9	60	120	2.75
C506580TP-2200	2200	3.7	4.9	65.0	80.5	53	$\leq 3$	1.9	30	100	2.75
C3867102HT-2300	2300	3.7	3.8	67.0	102.0	56	$\leq 3$	1.8	60	120	2.75
C576080HT-2300	2300	3.7	5.7	59.5	80.5	58	$\leq 3$	1.6	60	120	2.75
C606080HT-2400	2400	3.7	6.0	60.0	82.0	61.9	$\leq 2$	0.84	60	120	2.75
C526786HT-2500	2500	3.7	5.0	67.0	89.0	61.1	$\leq 2.5$	1.48	60	120	2.75
C606080ET-2500	2500	3.7	6.0	59.5	80.5	62	$\leq 3$	1.3	80	150	2.75
C546786HT-2650	2650	3.7	5.4	67.0	88.0	62.4	$\leq 2.5$	1.54	60	120	2.75
C546786TP-2650	2650	3.7	5.3	67.0	86.5	65	$\leq 3$	1.6	30	100	2.75
C666080HT-2700	2700	3.7	6.6	70.0	82.0	67.0	$\leq 2$	1.23	60	120	2.75
C675095TP-2700	2700	3.7	6.7	50.0	96.0	62.4	$\leq 2.5$	1.39	30	100	2.75
C6552106HT-2950	2950	3.7	6.4	52.0	106.0	71	$\leq 3$	1.4	60	120	2.75
C706580HT-2950	2950	3.7	6.9	65.0	80.5	74	$\leq 3$	1.5	60	120	2.75
C5267102HT-3000	3000	3.7	5.2	67.0	103.0	73	$\leq 2$	1.5	60	120	2.75
C626786TP-3000	3000	3.7	6.0	67.0	86.0	72	$\leq 3$	1.7	30	100	2.75
C6842125TP-3000	3000	3.7	6.8	43.0	125.0	70.78	$\leq 2.5$	1.47	30	100	2.75
C766085HT-3100	3100	3.7	7.4	60.0	85.5	75	$\leq 3$	1.3	60	120	2.75
C7242125HT-3200	3200	3.7	7.2	43.0	125.5	79	$\leq 3$	1.3	60	120	2.75
C7343115TP-3200	3200	3.7	7.3	43.0	115.5	76	$\leq 3$	1.5	30	100	2.75
C607095HT-3250	3250	3.7	6.0	70.0	97.0	80.6	$\leq 2$	1.11	60	120	2.75
C747080TP-3500	3500	3.7	7.2	70.0	81.0	82	$\leq 3$	1.3	40	100	2.75
C7652106HT-3700	3700	3.7	7.4	52.0	106.0	85.2	$\leq 2$	1.31	60	120	2.75
C8242125HT-3700	3700	3.7	8.2	42.0	125.5	92	$\leq 3$	1.2	60	120	2.75
C4870140TP-4000	4000	3.7	4.7	70.0	140.0	96	$\leq 3$	1.3	30	100	2.75
C6074106HT-4000	4000	3.7	5.8	74.0	106.0	98	$\leq 2.0$	1.3	60	120	2.75
C6567102HT-4000	4000	3.7	6.5	67.0	103.5	98	$\leq 2.0$	1.1	60	120	2.75
C6567102TP-4000	4000	3.7	6.5	67.0	103.5	93.5	$\leq 3$	1.2	30	100	2.75
C7548135TP-4000	4000	3.7	7.0	48.0	35.0	95.3	$\leq 2$	1.07	30	100	2.75
C8554100TP-4000	4000	3.7	8.3	54.0	101.0	93	$\leq 2.5$	1.1	60	120	2.75
C857084TP-4000	4000	3.7	7.8	70.0	85.0	91.0	$\leq 2$	0.95	30	100	2.75
C8644132HT-4000	4000	3.7	8.4	44.0	133.5	99	$\leq 2.0$	1.3	60	120	2.75
C9042125HT-4000	4000	3.7	9.0	43.0	127.0	97.1	$\leq 2$	1.17	60	120	2.75
C9042125TP-4000	4000	3.7	8.7	42.0	125.5	96	$\leq 3$	1.3	30	100	2.75
C5576120TP-4500	4500	3.7	5.5	76.0	120.0	105	$\leq 3$	1.6	30	100	2.75
C9552106HT-4500	4500	3.7	9.3	52.0	106.0	105	$\leq 3$	1.0	60	100	2.75
C7567102TP-4600	4600	3.7	7.2	67.0	103.5	104	$\leq 3$	1.2	30	100	2.75
C8067102HT-4800	4800	3.7	7.6	67.0	104.0	112.8	$\leq 2$	0.85	60	120	2.75
C9548135TP-4900	4900	3.7	9.0	48.0	135.0	121	$\leq 2.0$	1.0	30	100	2.75
C1043125HT-5000	5000	3.7	10.3	44.0	125.5	116	$\leq 2.0$	1.1	60	110	2.75
C6068138TP-5000	5000	3.7	5.9	68.0	139.5	115	$\leq 2.0$	1.1	30	100	2.75
C6564145HT-5000	5000	3.7	6.4	64.0	145.0	122	$\leq 3$	1.1	30	120	2.75
C6870125HT-5000	5000	3.7	6.3	70.0	127.0	119	$\leq 2$	0.84	60	120	2.75
C7374106HT-5000	5000	3.7	7.2	74.0	106.0	119	$\leq 2.0$	1.1	60	120	2.75
C9348135HT-5000	5000	3.7	8.9	48.0	136.0	118.4	$\leq 2$	0.85	60	120	2.75
C9543125TP-5000	5000	3.7	9.4	43.0	126.0	107	$\leq 2$	1.11	30	60	2.75
C957084TP-5000	5000	3.7	9.8	70.0	85.0	117.1	$\leq 2$	0.72	30	100	2.75
C1045135HT-5200	5200	3.7	9.7	45.0	135.0	124	$\leq 2.5$	0.8	60	100	2.75
C9548135TP-5200	5200	3.7	9.0	48.0	136.0	120	$\leq 2$	0.9	30	90	2.75
C117084TP-5300	5300	3.7	10.0	70.0	85.0	118.3	$\leq 2$	0.65	30	100	2.75
C6675130TP-5800	5800	3.7	6.6	74.5	130.5	134	$\leq 2$	1.0	30	100	2.75

C1046148TP-6000	6000	3.7	9.4	46.0	148.5	136	≤2	1.0	30	90	2.75
<b>C1046148TP-6000</b>	<b>6000</b>	<b>3.7</b>	<b>9.3</b>	<b>46.0</b>	<b>150.0</b>	<b>138</b>	<b>≤2</b>	<b>1.10</b>	<b>30</b>	<b>100</b>	<b>2.75</b>
C6574135TP-6000	6000	3.7	6.4	74.0	135.0	136	≤2	1.2	30	100	2.75
C7070140HT-6000	6000	3.7	7.0	70.0	140.0	141	≤2.0	0.8	60	120	2.75
C7567135TP-6000	6000	3.7	7.3	67.0	135.0	141	≤2	0.9	30	100	2.75
<b>C8070125TP-6000</b>	<b>6000</b>	<b>3.7</b>	<b>7.4</b>	<b>70.0</b>	<b>127.0</b>	<b>135.4</b>	<b>≤2</b>	<b>0.85</b>	<b>30</b>	<b>100</b>	<b>2.75</b>
C8867135TP-7000	7000	3.7	8.4	67.0	135.0	160	≤2	0.7	30	100	2.75
C9070170HT-8000	8000	3.7	9.0	70.0	140.0	188	≤2.5	0.7	60	120	2.75
<b>DC386786HT-1800</b>	<b>1800</b>	<b>3.7</b>	<b>3.8</b>	<b>68.0</b>	<b>87.0</b>	<b>45.1</b>	<b>≤3</b>	<b>2</b>	<b>60</b>	<b>120</b>	<b>2.75</b>
<b>DC446786TP-2000</b>	<b>2000</b>	<b>3.7</b>	<b>4.4</b>	<b>68.0</b>	<b>87.0</b>	<b>53.58</b>	<b>≤2.5</b>	<b>1.79</b>	<b>30</b>	<b>60</b>	<b>2.75</b>
DC6537125HT-2000	2000	3.7	5.7	38.0	125.5	58.0	≤4	1.9	30	150	2.75
<b>DC606080ET-2500</b>	<b>2500</b>	<b>3.7</b>	<b>6.0</b>	<b>60.0</b>	<b>80.0</b>	<b>60.4</b>	<b>≤2</b>	<b>1.36</b>	<b>60</b>	<b>120</b>	<b>2.75</b>
DC7242125TP-3200	3200	3.7	7.0	42.0	125.5	78.0	≤3	1.3	30	100	2.75
<b>DC736786HT-3700</b>	<b>3700</b>	<b>3.7</b>	<b>7.2</b>	<b>68.0</b>	<b>88</b>	<b>86</b>	<b>≤2</b>	<b>1.2</b>	<b>60</b>	<b>120</b>	<b>2.75</b>
S386786TP-1800	1800	3.7	3.8	67.0	86.0	46	≤4	2.3	30	120	2.75
S687260HT-2150	2150	3.7	6.6	72.0	60.0	56	≤4	1.6	90	180	2.75
S753795TP-2200	2200	3.7	7.4	37.0	96.5	55	≤5	2.0	30	120	2.75
S3867102TP-2300	2300	3.7	3.8	67.0	102.0	56	≤5	2.0	30	120	2.75
S506786HT-2400	2400	3.7	4.9	67.0	86.0	60	≤3	1.9	60	120	2.75
S526786HT-2500	2500	3.7	5.2	67.0	86.0	64	≤3	1.7	60	150	2.75
S705780HT-2650	2650	3.7	6.9	57.0	80.5	58	≤4	1.5	60	150	2.75
S606580TP-3000	3000	3.7	6.0	65.0	81.0	66	≤3	2.2	30	120	2.75
S766085HT-3100	3100	3.7	7.4	60.0	85.5	76	≤3	1.7	60	120	2.75
<b>S726094ET-3150</b>	<b>3150</b>	<b>3.7</b>	<b>6.8</b>	<b>60</b>	<b>95</b>	<b>80.1</b>	<b>≤2</b>	<b>0.97</b>	<b>90</b>	<b>180</b>	<b>2.75</b>
S826080TP-3200	3200	3.7	7.9	59.0	80.0	77	≤4	1.8	30	120	2.75
S6060110TP-3350	3350	3.7	6.0	59.0	110.0	81	≤4	1.4	30	120	2.75
S6367102HT-3700	3700	3.7	6.3	67.0	102.0	91	≤3	1.2	60	120	2.75
S7652106TP-3700	3700	3.7	7.6	52.0	106.5	88	≤3	1.6	30	120	2.75
S8042125TP-3700	3700	3.7	7.8	42.0	125.0	88	≤3	1.3	30	120	2.75
S7548135TP-4000	4000	3.7	7.3	48.0	136.0	97	≤3	1.2	30	120	2.75
S9042125TP-4000	4000	3.7	8.8	42.0	125.5	96	≤3	1.6	30	120	2.75
<b>S937080HT-4000</b>	<b>4000</b>	<b>3.7</b>	<b>9</b>	<b>70</b>	<b>82</b>	<b>102</b>	<b>≤2</b>	<b>0.94</b>	<b>60</b>	<b>120</b>	<b>2.75</b>
S6064145ET-4500	4500	3.7	6.0	64.0	150.5	123	≤2.5	1.1	90	180	2.75
S9552106TP-4500	4500	3.7	9.1	52.0	106.0	106	≤3	1.7	30	120	2.75
S6864145ET-5000	5000	3.7	6.6	64.0	150.5	132	≤2.5	1.0	90	180	2.75
S9543125TP-5000	5000	3.7	9.7	43.0	125.0	120	≤3	1.1	30	90	2.75
S1045135TP-5200	5200	3.7	9.5	45.0	135.0	120	≤2.5	1.0	30	90	2.75
S6574135TP-6000	6000	3.7	6.5	74.0	135.0	140	≤2.5	0.9	30	120	2.75
S7567135TP-6000	6000	3.7	7.2	67.0	135.0	141	≤2.5	1.0	30	120	2.75
S9064145HT-6000	6000	3.7	8.5	64.0	150.5	156	≤2.5	0.9	90	180	2.75
S9659156TP-8000	8000	3.7	9.3	59.0	156.5	186	≤3	0.7	30	120	2.75
S9964145HT-8000	8000	3.7	10.0	64.0	150.5	200	≤2.5	0.7	90	180	2.75

Model NO.	Nominal Capacity (mAh)	Voltage (V)	Dimensions			Approx. Weight (g)	Internal Impedance ( $\Omega$ )		Max Discharge Current		
			T $\pm 0.2$ mm	W $\pm 0.5$ mm	L $\pm 1.0$ mm				Continuous Discharge Current (C)	Burst Discharge Current (C)	Cut-off Voltage (V)
DF754383ET-1500	1500	3.2	6.5	43.0	86.0	47	$\leq 2.5$	1.62	30	100	2.5
DF905565TP-2000	2000	3.2	9.4	55.0	66.0	62.0	$\leq 3$	1.6	30	80	2.5
DF964383ET-2000	2000	3.2	9.4	43.3	85.0	64.0	$\leq 3$	1.5	60	120	2.5
DF114383ET-2500	2500	3.2	10.8	43.3	85.0	75.0	$\leq 3$	1.2	60	120	2.5
DF706094HP-2500	2500	3.2	6.5	60.0	94.0	73	$\leq 3$	1.35	20	100	2.5
DF7045145TP-3000	3000	3.2	7.0	45.0	145.0	93.5	$\leq 2$	1.12	30	100	2.5
DF1245100TP-3400	3400	3.2	11.4	44.0	102.0	97	$\leq 2$	0.97	30	100	2.5
DF9643125TP-3500	3500	3.2	9.5	43.0	125.0	99	$\leq 2$	0.76	30	100	2.5
DF1249105TP-4000	4000	3.2	12.0	49.0	107.0	114	$\leq 2$	0.92	30	100	2.5
F5554106TP-2000	2000	3.2	5.3	54.0	105.5	61	$\leq 3$	1.9	30	100	2.5
F566786HT-2000	2000	3.2	5.4	67.0	87	61	$\leq 2.5$	1.61	40	120	2.5
F955069TP-2000	2000	3.2	9.3	50.0	59.5	60	$\leq 2.5$	1.8	30	100	2.5
F6154106HT-2100	2100	3.2	6.0	54.0	106.0	66	$\leq 2$	1.27	60	120	2.5
F7042125TP-2400	2400	3.2	7.0	43.0	125.5	73	$\leq 3$	1.6	30	100	2.5
F855585TP-2400	2400	3.2	8.3	55.0	85.5	70	$\leq 3$	1.5	30	100	2.5
F114383ET-2500	2500	3.2	10.8	43.3	85.0	72	$\leq 2.5$	1.4	30	100	2.5
F7242125TP-2500	2500	3.2	7.2	42.0	125.5	73	$\leq 3$	1.8	30	100	2.5
F825095TP-2500	2500	3.2	8.0	50.0	96.0	74	$\leq 2.5$	1.7	30	100	2.5
F6545145TP-2900	2900	3.2	6.4	45.0	145.0	84	$\leq 3$	1.5	30	100	2.5
F8054106SP-3000	3000	3.2	7.9	53.5	105.5	88	$\leq 3$	1.4	30	100	2.5
F8343125TP-3000	3000	3.2	8.2	43.0	125.5	87	$\leq 2.5$	1.3	30	100	2.5
F134295SP-3300	3300	3.2	12.3	42.5	96.5	93	$\leq 3$	1.2	30	100	2.5
F8443150TP-3400	3400	3.2	8.3	43.5	150.5	99	$\leq 3$	1.2	30	100	2.5
F6164145HT-3500	3500	3.2	6.0	64.0	145.0	102	$\leq 2$	0.97	60	120	2.5
F106094TP-3600	3600	3.2	9.9	59.0	94.5	102	$\leq 3$	1.1	30	100	2.5
F106094HP-3900	3900	3.2	9.8	59.0	94.5	103	$\leq 3$	1.6	20	80	2.5
F1143125TP-4000	4000	3.2	10.9	43.0	125.5	113	$\leq 3$	1.2	30	100	2.5
F6270140TP-4000	4000	3.2	6.1	70.0	140.0	115	$\leq 3$	0.9	30	100	2.5
F8867102TP-4000	4000	3.2	8.8	67.0	104.0	115	$\leq 2$	0.94	30	100	2.5
F9045145TP-4000	4000	3.2	8.8	45.0	145.0	113	$\leq 3$	1.4	30	100	2.5
F7075130HP-4500	4500	3.2	6.7	74.0	130.5	121	$\leq 3$	1.2	30	100	2.5
F1157130TP-5000	5000	3.2	10.3	57.0	131.0	141	$\leq 2$	1.0	30	100	2.5
F1167102TP-5000	5000	3.2	10.7	67.0	103.5	141	$\leq 2$	0.8	30	100	2.5
F7875130TP-5000	5000	3.2	7.7	73.5	130.5	143	$\leq 2$	1.1	30	100	2.5
F1070125TP-6000	6000	3.2	9.7	70.0	125.5	165	$\leq 2$	0.9	30	100	2.5
F1367102TP-6000	6000	3.2	12.4	67.0	104.0	169	$\leq 2$	0.49	30	100	2.5
F1257130HP-6100	6100	3.2	11.6	57.0	130.5	164	$\leq 2$	0.9	20	100	2.5
F1270125TP-7000	7000	3.2	11.7	70.0	125.5	196	$\leq 2$	0.7	30	100	2.5
F8084165HT-7000	7000	3.2	8.1	84.0	170.0	223	$\leq 2$	0.7	30	150	2.5
F8977150TP-7000	7000	3.2	8.7	77.0	150.5	195	$\leq 2$	0.7	30	100	2.5
F1187125TP-8000	8000	3.2	10.7	87.0	125.5	225	$\leq 2$	0.9	30	100	2.5
F70115145TP-8000	8000	3.2	7.0	115.0	146.0	239	$\leq 2$	0.7	30	100	2.5
F9084165TP-8000	8000	3.2	8.5	84.0	165.5	232	$\leq 2$	0.6	30	100	2.5
F10110140TP-10000	10000	3.2	9.5	110.0	140.5	286	$\leq 2$	0.6	30	100	2.5
F1284165SP-10000	10000	3.2	10.9	84.0	165.0	300	$\leq 2$	0.6	25	80	2.5
F1380138TP-10000	10000	3.2	13.1	80.0	138.0	270	$\leq 2$	0.6	10	60	2.5
F10130140TP-12000	12000	3.2	9.2	130.0	140.0	332	$\leq 2$	0.6	30	60	2.5
F12110140TP-12000	12000	3.2	11.5	110.0	140.5	336	$\leq 2$	0.6	30	100	2.5
F12140175TP-18000	18000	3.2	11.4	140.0	175.5	510	$\leq 2$	0.5	30	100	2.5

Model NO.	Nominal Capacity (mAh)	Voltage (V)	Dimensions			Approx. Weight (g)	Internal Impedance ( $\Omega$ )		Max Discharge Current		
			T $\pm 0.2$ mm	W $\pm 0.5$ mm	L $\pm 1.0$ mm				Continuous Discharge Current (C)	Burst Discharge Current (C)	Cut-off Voltage (V)
1059156HP-10000	10000	3.7	9.8	59.0	156.0	194	$\leq 2.0$	1.0	10	20	3.0
7870170HP-10000	10000	3.7	7.8	70.0	170.0	198	$\leq 2.0$	0.9	10	20	3.0
9070170HP-12000	12000	3.7	8.8	70.0	170.0	234	$\leq 2.0$	0.9	10	20	3.0
8584165HP-12000	12000	3.7	8.4	84.0	165.5	247	$\leq 2.0$	0.7	10	20	3.0
1084165HP-16000	16000	3.7	10.2	84.0	165.5	315	$\leq 2.0$	0.7	10	20	3.0
1174170HP-16000	16000	3.7	10.9	74.0	170.5	311	$\leq 2.0$	0.7	10	20	3.0
1190190HP-22000	22000	3.7	10.9	90.0	190.0	427	$\leq 2.0$	0.6	10	20	3.0
<b>C1190190SP-20000</b>	<b>20000</b>	<b>3.7</b>	<b>10.5</b>	<b>92.8</b>	<b>191.9</b>	<b>404</b>	<b><math>\leq 2.0</math></b>	<b>0.49</b>	<b>10</b>	<b>20</b>	<b>3.0</b>

Model NO.	Nominal Capacity (mAh)	Voltage (V)	Dimensions			Approx. Weight (g)	Internal Impedance (mΩ)		Max Discharge Current			Discharge temperature (°C)
			T ± 0.2 mm	W ± 0.5 mm	L ± 1.0 mm				Continuous Discharge Current (C)	Burst Discharge Current (C)	Cut-off Voltage (V)	
H3764143SP-4300	4300	3.8	4.0	64.0	143.0	80	≤3.5	2.3	2.0	6	2.33	-40
<b>H6076120SP-5200</b>	<b>5200</b>	<b>3.8</b>	<b>5.5</b>	<b>76</b>	<b>121</b>	<b>108</b>	<b>≤3.5</b>	<b>1.04</b>	<b>2.0</b>	<b>6</b>	<b>2.5</b>	<b>-40</b>
H4364143-5300	5300	3.8	4.3	64.0	143.5	80	≤5.0	3.2	1.0	5	2.33	-20
S584460-1700	1700	3.8	5.5	43.5	59.0	29	≤15	6.8	0.2	2	3.0	-20
S585960-2300	2300	3.7	5.7	58.5	60.0	41	≤7.0	5.6	0.2	2	3.0	-20