




HSF



ROHS



P. C. B LAYOUT

**SPECIFICATIONS:**

Current Rating: 0.75Amp  
 Insulation Resistance: 1000M ohms min  
 Contact Resistance: 20M ohms max  
 Dielectric Withstanding: AC500V  
 Operating Temperature: -65° C to +125° C  
 Contact Material: Brass  
 Insulator Material: PA6T, UL 94V-0 Black


**Ordering Code:**

PHBS02 - X - X - S - A-C-B - X - X - X  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No:
- ② No. of Contacts: 01 To 50
- ③ Contact Plating:  
 G0:Gold flash S0:Selective  
 G1:3U" Gold S1:Selective 3u"  
 G2:5u" Gold S2:Selective 5u"  
 G3:10u" Gold S3:Selective 10u"  
 G4:15u" Gold S4:Selective 15u"  
 G5:30u" Gold S5:Selective 30u"  
 SN:Tin
- ④ Connector Type:  
 S:Single
- ⑤ Pin Length:  
 A:0180=1.8mm  
 C:0420=4.2mm  
 B:0180=1.8mm  
 Please mark the desired length in the A/C/B
- ⑥ Insulator Material:  
 B:PA6T  
 C:LCP  
 E:PA9T
- ⑦ Packing:  
 A:Tray  
 B:Bag  
 T:Tube  
 U:Tube+CAP  
 R:Tape&Reel  
 W:Tape&Reel+CAP
- ⑧ Plastic High:  
 H1:1.0mm  
 H2:1.5mm

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW ZLA DATE 24/04/2022  
 CHECK BobYang DATE 24/04/2022



**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
 Http://www.atkconn.com

TITLE: 1.00mm Pin Header Single Row Double Plastic Straight Type

DRAWING NO: PHBS02-XXS-0180-0420-0180-XXX  
 PRODUCT NO: PHBS02-XXS-0180-0420-0180-XXX

REV	DESCRIPTION	DATE
1		
2		