

Scale:2:1
PCB Layout Diagram
Top View

Note:

1. Material:

- a. Contact:C5191
- b. Surface Plating:Au

2. Electric:

- a. Contact Resistance:30 Mlliohms Max.
- b. Insulation Resistance:1000 Mega Ohms Min.
- c. Dielectnic Voltage:500 V AC One Sec Level
- d. Operating Temperature:-55° To +105°

Order code:

BS — M — G0 — R — CR151A
① ② ③ ④ ⑤

① BT:Battery Contacts ③ Contact Plating

② Apperance for the product

M:SMT TYPE

S:180 TYPE

R:90 TYPE

SN:Tin

G0:Gold flash

G1: 3U" Gold

G2: 5U" Gold

G3:10U" Gold

G4:15U" Gold

G5:30U" Gold

④ Packing method

A: Tray packing


R: Tape & reel packing

⑤ Product number

CR151A

Unless Otherwise specified tolerance
X. ±0.35 X.XX:±0.20
X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm
DRAW ZLA DATE 21/07/2022
CHECK BobYang DATE 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
Http://www.atkconn.com

TITLE: Battery Contacts For CR151

DRAWING NO: BS-M-G0-R-CR151A

PRODUCT NO: BS-M-G0-R-CR151A

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		