

HSF



ROHS

SPECIFICATION




Current Rating: 0.75Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65°C to +125°C
 Contact Material: Brass
 Insulator Material: PA6T,UL 94V-0 Black

Ordering Code:

PHBM04 - 11 - G3 - D - 116 - B - B - 25


① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No:
- ② No. of Contacts
11P
- ③ Contact Plating:
G0:Gold flash S0:Selective
G1:3U" Gold S1:Selective 3u"
G2:5u" Gold S2:Selective 5u"
G3:10u" Gold S3:Selective 10u"
G4:15u" Gold S4:Selective 15u"
G5:30u" Gold S5:Selective 30u"
SN:Tin
- ④ Connector Type
D: Dual
- ⑤ Pin Length:
116=11.6 mm
- ⑥ Insulator Material
B:PA6T
C:LCP
E:PA9T
- ⑦ Packing:
A:Tray B:Bag T:Tube
U:Tube+CAP R:Tape&Reel
W:Tape&Reel+CAP
- ⑧ Plastic High
25=2.5mm



Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW ZLA DATE 24/04/2022
 CHECK BobYang DATE 24/04/2022



Atkconn® ATKCONN ELECTRONICS CO.,LTD
 Http://www.atkconn.com

TITLE: 1mm pitch asymmetric double plastic pin 11P, SMT

DRAWING NO: PHBM04-11G3D116BB25

PRODUCT NO: PHBM04-11G3D116BB25

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		