

HSF



ROHS

SPECIFICATIONS:

Current Rating: 1Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65° C to +125° C
 Contact Material: Brass
 Insulator Material: PA6T, UL94V-0 Black

Ordering Code:

PHCR01 - X - X - S - A-D-B - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦

① Series No:

② No. of Contacts:
01 To 50

③ Contact Plating:
 G0:Gold flash S0:Selective
 G1:3U" Gold S1:Selective 3u"
 G2:5u" Gold S2:Selective 5u"
 G3:10u" Gold S3:Selective 10u"
 G4:15u" Gold S4:Selective 15u"
 G5:30u" Gold S5:Selective 30u"
 SN: Tin

④ Connector Type:
S:Single Row

⑤ Pin Length:





A: 0300=3.00mm
 D: 0100=1.00mm
 B: 0180=1.80mm
 Please mark the desired length in the A/D/B

⑥ Insulator Material:

B:PA6T
 C:LCP
 E:PA9T

⑦ Packing:


A:Tray
 B:Bag
 T:Tube
 U:Tube+CAP
 R:Tape&Reel
 W:Tape&Reel+CAP



P. C. B LAYOUT

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm
 DRAW ZLA DATE 24/04/2022
 CHECK BobYang DATE 24/04/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: 1.27mm Pin Header Single Row Angle Type

DRAWING NO: PHCR01-XXS-0300-0100-0180-XXX

PRODUCT NO: PHCR01-XXS-0300-0100-0180-XXX

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		