



RECOMMENDED PCB PATTERN DIM.
TOLERANCE : ±0.05

NOTES:
Housing:LCP High-Temp Plastic UL94V-0 Black
Terminal:Phosphor Bronze
Plating:10u" Gold IN Contact Area Matte Tin on Tail

Ordering Code:

BB0.5 - F - X - X - X - 05
① ② ③ ④ ⑤ ⑥

- ① Series NO:
0.5mm Board to Board connector
- ② F:Female
- ③ NO. of Contacts:
See Table
For Example
180:180 Poles
- ④ Contact Plating:
S0:Selective
S1:Selective 3u"
S2:Selective 5u"
S3:Selective 10u"
S4:Selective 15u"
S5:Selective 30u"
SN:Tin
- ⑤ Packing
T:Tube A:Tray
B:Bag U:Tube+CAP
R:Tape & Reel
W:Tape & Reel+CAP
- ⑥ Serial Number: 05

NG. of contacts	Dimensions			
	A.	B.	C.	D.
60	21.38	20.13	20.18	0.10
120	41.38	40.13	40.18	0.10
180	61.38	60.13	60.18	0.15
240	81.38	80.13	80.18	0.15
300	101.38	100.13	100.18	0.15

Unless Otherwise specified tolerance
X. ±0.35 X.XX:±0.20
X.X:±0.25 X.XXX:±0.15

SCALE: As Shown UNIT: mm
DRAW ZLA DATE 24/10/2022
CHECK BobYang DATE 24/10/2022
VER. A0
3rd ANGLE PROJECTION

Atkonn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkonn.com](http://www.atkonn.com)

TITLE:
0.5mm DOUBLE ROW BTB FEMALE SOCKET H3.25

DRAWING NO: BB0.5-FXXX05

PRODUCT NO: BB0.5-FXXX05

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		