



NOTE:
 1. CONTACT: MAT'L
 0.30 (.012) TH "K PHOSPHOR BRONZE
 FINISH:
 GOLD FLASH PLATING
 .000003-.000005 GOLD, OVER
 .000100-.000150 NICKEL PLATE
 2. HOUSING: MAT'L
 HEAT RESISTANCE NYLON (UL94V-0)

Order code:
 BT — M — G0 — R — CR498A
 ① — ② — ③ — ④ — ⑤

- ① BT: Coin Cell Holders
- ② Appearance for the product
 M: SMT TYPE
 S: 180 TYPE
 R: 90 TYPE
- ③ Contact Plating
 SN: Tin
 G0: Gold flash
 G1: 3U" Gold
 G2: 5U" Gold
 G3: 10U" Gold
 G4: 15U" Gold
 G5: 30U" Gold
- ④ Packing method
 A: Tray packing
 R: Tape & reel packing
- ⑤ Product number
 CR498A

CONTACT MUST PROTRUDE
 BEYOND BASE TO MAX. OF.
 0.10 (.005)

Unless Otherwise specified tolerance
 X. ± 0.35 X. XX: ± 0.20
 X. X: ± 0.25 X. XXX: ± 0.15

SCALE: As Shown UNIT: mm
 DRAW ZLA DATE 21/07/2022
 CHECK BobYang DATE 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: 1/3 N HORIZONTAL SMT HOLDER

DRAWING NO: BT-M-G0-R-CR498A

PRODUCT NO: BT-M-G0-R-CR498A

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		