

HSF



ROHS



### SPECIFICATION

Current Rating: 7 Amp  
 Insulation Resistance: 1000M ohms min  
 Contact Resistance: 20M ohms max  
 Dielectric Withstanding: AC500V  
 Operating Temperature: -65°C to +125°C  
 Contact Material: Brass  
 Insulator Material: LCP,UL 94V-0 Black

Ordering Code:

PHGS01 - X - X - S - A-B - X - X  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No:
- ② No. of Contacts: 01 To 40
- ③ Contact Plating:  
 G0: Gold flash S0: Selective  
 G1: 3u" Gold S1: Selective 3u"  
 G2: 5u" Gold S2: Selective 5u"  
 G3: 10u" Gold S3: Selective 10u"  
 G4: 15u" Gold S4: Selective 15u"  
 G5: 30u" Gold S5: Selective 30u"  
 SN: Tin
- ④ Connector Type:  
 S: Single
- ⑤ Pin Length:  
 A: 1080=10.80mm  
 B: 0350=3.50mm  
 Please mark the desired length in the A/B
- ⑥ Insulator Material:  
 B: PA6T  
 C: LCP  
 E: PA9T
- ⑦ Packing:  
 A: Tray  
 B: Bag  
 T: Tube  
 U: Tube+CAP  
 R: Tape&Reel  
 W: Tape&Reel+CAP



PCB LAYOUT

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15


SCALE: As Shown	UNIT: mm
DRAW ZLA	DATE 24/04/2022
CHECK BobYang	DATE 24/04/2022

**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE:  
5.08 mm Pin Header Single Row Straight Type

DRAWING NO: PHGS01-XXS-1080-0350-XX

PRODUCT NO: PHGS01-XXS-1080-0350-XX



REV	DESCRIPTION	DATE