

PCB Layout Diagram
Top View

NOTE:

1. BASE: MAT' L: PBT BLACK
2. CONTACTS: Mn Steel, BRASS
3. ELECTRIC:
 - a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d. OPERATING TEMPERATURE: -25° C TO +85° C


Order code:

BT — S — SN — R — CR1620A
 ① — ② — ③ — ④ — ⑤

- | | |
|------------------------------|------------------------|
| ① BT: Coin Cell Holders | ③ Contact Plating |
| ② Appearance for the product | SN: Tin |
| M: SMT TYPE | G0: Gold flash |
| S: 180 TYPE | G1: 3U" Gold |
| R: 90 TYPE | G2: 5U" Gold |
| | G3: 10U" Gold |
| | G4: 15U" Gold |
| | G5: 30U" Gold |
| | ④ Packing method |
| | A: Tray packing |
| | R: Tape & reel packing |
| | ⑤ Product number |
| | CR1620A |

Unless Otherwise specified tolerance
 X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown	UNIT: mm
DRAW ZLA	DATE 21/07/2022
CHECK BobYang	DATE 21/07/2022



Atkconn® ATKCONN ELECTRONICS CO., LTD
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: Coin Cell Holders For CR1620

DRAWING NO: BT-S-SN-R-CR1620A

PRODUCT NO: BT-S-SN-R-CR1620A

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		