





HSF



ROHS



### SPECIFICATION

Current Rating: 7 Amp  
 Insulation Resistance: 1000M ohms min  
 Contact Resistance: 20M ohms max  
 Dielectric Withstanding: AC500V  
 Operating Temperature: -65°C to +125°C  
 Contact Material: Brass  
 Insulator Material: LCP,UL 94V-0 Black


Ordering Code:

PHGR01A - X - X - S - A-D-B - X - X  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No:
- ② No. of Contacts  
01 To 40
- ③ Contact Plating:  
G0:Gold flash S0:Selective  
G1:3U" Gold S1:Selective 3u"  
G2:5u" Gold S2:Selective 5u"  
G3:10u "Gold S3:Selective 10u"  
G4:15u" Gold S4:Selective 15u"  
G5:30u" Gold S5:Selective 30u"
- ④ Connector Type  
S:Single
- ⑤ Pin Length:  
A:0800=8.00mm  
D:0690=6.90mm  
B:0360=3.60mm  
Please mark the desired length in the A/D/B
- ⑥ Insulator Material  
B:PA6T  
C:LCP  
E:PA9T
- ⑦ Packing:  
A:Tray  
B:Bag  
T:Tube  
U:Tube+CAP  
R:Tape&Reel  
W:Tape&Reel+CAP

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW ZLA DATE 24/04/2022  
 CHECK BobYang DATE 24/04/2022



**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: 5.08 mm Pin Header Single Row Angle type, standard type

DRAWING NO: PHGR01A-XXS-0800-0690-0360-XX

PRODUCT NO: PHGR01A-XXS-0800-0690-0360-XX

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		