



Specifications

- CONTACT PLATING:30 MICROINCHES OF GOLD AVERAGE OVER PER MIL-G-45204C OVER 50 MICROINCHES MIN.SULFAMATE NICKEL PER QQ-N-290
- Contact Material:PHOSPHOR BRONZE ALLOY 510 SPRING TEMOER
- BODY MATERIAL:FORTRON 1140L6
- CONNECTORS UNLIMITED PART NUMBER 910173

Ordering Code:

BB1.0 - M - X - X - X - X - 02  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series NO:  
1.0mm Board to Board Connector
- ② M:Male F:Female
- ③ Mating Height:  
7.65=7.65mm  
12.65=12.65mm
- ④ NO. of Contacts:  
10:10poles
- ⑤ Contact Plating  
G0: Gold flash  
G1: 3u" Gold  
G2: 5u" Gold  
G3: 10u" Gold  
G4: 15u" Gold  
G5: 30u" Gold  
SN: Tin
- ⑥ Packing  
T:Tube A:Tray  
B:Bag U:Tube+CAP  
R:tape&Reel  
W:tape&Reel+CAP
- ⑦ Serial Number:  
02

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown	UNIT: mm
DRAW ZLA	DATE 24/10/2022
CHECK BobYang	DATE 24/10/2022
VER. A0	

**Atkconn**® ATKCONN ELECTRONICS CO., LTD  
[Http://www.atkconn.com](http://www.atkconn.com)

TITLE: 1.0mm Board to Board Male 2X5P Connector,  
 Mating Height=2.0mm

DRAWING NO: BB1.0M-XXXX02

PRODUCT NO: BB1.0M-XXXX02

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		