

南京全宁电器有限公司
Nanjing QuanNing Electric Co.,Ltd

江苏省南京市江宁区东山科创园润麒路 68 号

TEL: (025) 52628081

FAX: (025) 52628051

E-MAIL: njquanning@outlook.com

| | | | |
|----------|--|----------|------------------|
| CUSTOMER | | MODEL NO | QNC1 (CJX2)-6511 |
|----------|--|----------|------------------|

产品外形图



ORDER DESIGNATION (订货标记)

QN C 1 (CJX2) — 65 11

辅助触头数量: 1常开+1常闭
Auxiliary contact: 1NO+1NC

额定工作电流Rated working current (AC-3, 380V)

行业通用型号Industry general model

设计序号DesIgn Serial Number

接触器 Contactor

企业代号Corporation code

南京全宁电器有限公司

Nanjing QuanNing Electric Co.,Ltd

江苏省南京市江宁区东山科创园润麒路 68 号

TEL: (025) 52628081

FAX: (025) 52628051

E-MAIL: njquanning@outlook.com

1、产品应用范围：主要用于交流 50Hz（或 60Hz），额定绝缘电压至 690V，在 AC-3 使用类别下额定工作电压为 380V 时额定工作电流为 65A 的电路中，供远距离接通和分断电路，并可加装适当的热过载继电器组成电磁起动器，以保护可能发生负荷的电路。It is mainly used in the circuit with AC 50Hz (or 60Hz), rated insulation voltage up to 690V and rated working current of 65A when the rated working voltage is 380V under the use category of AC-3. It is used for remote connection and disconnection of the circuit, and an appropriate thermal overload relay can be added to form an electromagnetic starter to protect the circuit that may have overload

2、产品设计符合标准Standards: IEC60947-4, GB14048.4。

3、产品通过的认证Certification: CE、CQC 认证。

| | | | | |
|--|--|---|------------------|--|
| CUSTOMER | | MODEL NO | QNC1 (CJX2)-6511 | |
| ELECTRICAL SPECIFIC ATION | | | | |
| PRIMARY | | | | |
| 环境温度 Ambient Temperature | -25℃~+60℃ | | | |
| 海拔高度 Height above sea level | ≤3000m | | | |
| 触点形式 Contact Form | 3P+NO+NC | | | |
| 额定工作电压 Rated working voltage | 380V /660V | | | |
| 额定工作电流 Rated operating current Ie A | 65A (380V AC-3) | | | |
| 约定发热电流 Conventional thermat current Ith A | 65A | | | |
| 操作频率 h ⁻¹ Use frequencu h ⁻¹ | 600 (AC-3) | | | |
| 介质耐压 Initial Dielectric Strength | 线圈-触点Coil - contact | 工频 2500V/5s 无击穿或闪络现象，且泄露电流小于 50mA 2500V/1Min No breakdown or flashover , And leakage current ≤ 50mA | | |
| | 开路触点间Open the way between the contacts | | | |
| | 触头-地Contact - land | | | |
| | 线圈-地Coil - to ground | | | |
| 电气寿命 (AC-3) Electrical Life (AC-3) | 60×10 ⁴ 次 | | | |
| 温升 Elevatory temperature | 线圈 (额定控制电压下) Coil (Rated control voltage) | ≤40K | | |
| | 接线端子 (额定工作电流下) Conventional thermat current | ≤58K | | |
| 辅助触头 Auxiliary Contact | 约定发热电流 Conventional thermat current Ith A | 10A | | |
| | 可接通最小负载 Connect minimum load | DC5V 3mA | | |
| | 额定工作电流 Rated operating current Ie A | AC-15 (360VA) | 0.95A | |
| | | AC-13 (33W) | 0.15A | |
| 电气寿命 Electrical Life | 60×10 ⁴ 次 | | | |

线圈参数 (在 20℃下) COLLDATE (AT 20℃)

| | | | | |
|-------------------------------------|--------------------------|-----------------------------|------------------------------|---------------------------------|
| 额定电压 Us (V) RATED VOLTAGE Us (V) | 吸合电压 (V) PULL VOLTAGE | 释放电压 (V) RELEASE VOLTAGE | 吸合功率 (VA) PULL POWER (VA) | 保持功率 (VA) CONTAIN POWER (VA) |
| 24、48、110、220、380 | 70%~110% | 20%~60% | 230 | 32 |

特殊电压可根据客户要求定做Specifications can be made according to customer's order

南京全宁电器有限公司
Nanjing QuanNing Electric Co.,Ltd

江苏省南京市江宁区东山科创园润麒路 68 号

TEL: (025) 52628081

FAX: (025) 52628051

E-MAIL: njquanning@outlook.com

| | | | | | |
|---|--|----------|-------------------|--|--|
| CUSTOMER | | MODEL NO | QNC1 (CJX2) -6511 | | |
| OVERALL AND MOUNTING DIMENSIONS (外型尺寸与安装尺寸) | | | | | |
| | | | | | |
| 接线图 | | | | | |
| | | | | | |