

南京全宁电器有限公司
Nanjing QuanNing Electric Co.,Ltd

江苏省南京市江宁区东山科创园润麒路 68 号

TEL: (025) 52628081

FAX: (025) 52628051

E-MAIL: njquanning@outlook.com

CUSTOMER	MODEL NO	QNC1 (CJX2) -2510/2501/2511
----------	----------	-----------------------------

产品外形图



ORDER DESIGNATION (订货标记)

QN C 1 (CJX2) — 25 □

辅助触头数量: 10 为 1 常开, 01 为 1 常闭, 11 为 1 常开 + 1 常闭
Auxiliary contact: 10 indicates 1 NO, 01 indicates 1 NC, 11 indicates 1 NO+ 1 NC

额定工作电流 Rated working current (AC-3, 380V)

行业通用型号 Industry general model

设计序号 Design Serial Number

接触器 Contactor

企业代号 Corporation code

南京全宁电器有限公司

Nanjing QuanNing Electric Co.,Ltd

江苏省南京市江宁区东山科创园润麒路 68 号

TEL: (025) 52628081

FAX: (025) 52628051

E-MAIL: njquanning@outlook.com

1、产品应用范围：主要用于交流 50Hz（或 60Hz），额定绝缘电压至 690V，在 AC-3 使用类别下额定工作电压为 380V 时，额定工作电流为 25A 的电路中，供远距离接通和分断电路，并可加装适当的热过载继电器组成电磁起动器，以保护可能发生过负荷的电路。It is mainly used in the circuit with AC 50Hz (or 60Hz), rated insulation voltage up to 690V and rated working current of 25A when the rated working voltage is 380V under the use category of AC-3. It is used for remote connection and disconnection of the circuit, and an appropriate thermal overload relay can be added to form an electromagnetic starter to protect the circuit that may have overload

2、产品设计符合标准Standards: IEC60947-4, GB14048.4。

3、产品通过的认证Certification: CE、CQC 认证。

CUSTOMER		MODEL NO	QNC1 (CJX2)-2510/2501/2511	
ELECTRICAL SPECIFICATION				
PRIMARY				
环境温度 Ambient Temperature	-25℃~+60℃			
海拔高度 Height above sea level	≤3000m			
触点形式 Contact Form	3P+N0、3P+NC、3P+N0+NC			
额定工作电压 Ue (V) Rated working voltage	380、660			
额定工作电流 Ie (A) Rated operating current	25A (AC-3 380V)			
约定发热电流 Ith (A) Conventional thermat current	40			
操作频率 h ⁻¹ Use frequencu h ⁻¹	1200 (AC-3)			
介质耐压 Initial Dielectric Strength	线圈-触点 Coil - contact	工频 2500V/1min, 无击穿或闪络现象, 且泄露电流小于 50mA 2500V/1Min No breakdown or flashover , And leakage current ≤ 50mA		
	开路触点间 Open the way between the contacts			
	触头-地 Contact - land			
	线圈-地 Coil - to ground			
电气寿命 (AC-3) Electrical Life	100			
温升 Elevatory temperature	线圈 (额定控制电压下) Coil (Rated control voltage)	≤39K		
	接线端子 (额定工作电流下) Terminal blocks (Rated operating current)	≤44K		
辅助触头 Auxiliary Contact	约定发热电流 Conventional thermat current Ith A	10A		
	可接通最小负载 Connect minimum load	10V 10mA		
	额定工作电流 Ie (A) Rated operating current	AC-15 (360VA)	0.95A	
		AC-13 (33W)	0.15A	
电气寿命 Electrical Life	100×10 ⁴ 次			

4、产品技术参数:

线圈参数 (在 20℃下) COLLDATE (AT 20℃)

额定电压 Us (V) RATED VOLTAGE Us (V)	吸合电压 (V) PULL VOLTAGE	释放电压 (V) RELEASE VOLTAGE	吸合功率 (VA) PULL POWER (VA)	保持功率 (VA) CONTAIN POWER (VA)
24、48、110、220、380	70%~110%	20%~60%	110	11

特殊电压可根据客户要求定做 Specifications can be made according to customer's order.

