



## Guangzhou Huaxi C&T Co.,Ltd.

Add: Room 1203, No.66 Huadi South Ave, Liwan District, Guangzhou, Guangdong Province, China

E-mail: [info@choicybeauty.com](mailto:info@choicybeauty.com) Tel:+86-20-38263199 Website: [www.choicybeauty.com](http://www.choicybeauty.com)

### Choicy Beauty Equipment Series

### -- Multi Service Diode Laser Hair Removal Platform



**Model: CB-1001A**

#### Product Details



## System Characteristics

1. Multi-selective head-piece: different wavelength for different skin types and treatment areas.
2. Intelligent menu: auto-recognize different laser power hand-pieces, different hand-pieces plug and play.
3. Multi-aspect self-protection system, can work continuously for 24 hours \* 365 days.
4. New high power and high efficiency laser: faster hair removal and feel more comfortable.
5. Efficient heat dissipation and good thermal stability: guarantee the hand-piece works continually, and improve its life.
6. The internal structure is modular design, which is easily for testing, repairing and maintaining.

## Treatment Range

1. Suit for all kinds of skin
2. Remove the unwanted hair on all parts of your body, such as hairline, lip hair, whiskers, armpit hair, body hair, bikini hair or any other unwanted hair.

## Before and After Treatment





# Guangzhou Huaxi C&T Co.,Ltd.

Add: Room 1203, No.66 Huadi South Ave, Liwan District, Guangzhou, Guangdong Province, China

E-mail: [info@choicybeauty.com](mailto:info@choicybeauty.com) Tel:+86-20-38263199 Website: [www.choicybeauty.com](http://www.choicybeauty.com)

## Technical Specifications

Model	CB-1001A
Laser type	Diode laser
Wavelength	810nm
Spot size	10*20mm
Control mode	15 inch color touch screen
Cooling method	wind + water + semiconductor cooling system
Input power	3300W (AC220V/15A, AV110V30A)
<b>Fast mode:</b>	
Energy density	5-10J/cm <sup>2</sup>
Repetition rate	10Hz
Treatment mode	Hair texture (dense, crude, fine)
Cooling	Sapphire contact cooling
<b>Standard mode:</b>	
Energy density	5-120J/cm <sup>2</sup>
Repetition rate	1-10Hz
Pulse width	30~350ms
Cooling	Sapphire contact cooling

## NOTE:

The detailed instruction will be sent with the equipment.