



- $R \leq 0.2$
- $R_1 \leq 0.3$
- $R_2 \leq 2$

The surface of the rod should be finished by buffing (SPBF) to 0.8 to 1.6 μ mRz (0.2 to 0.4 μ mRa).

Model	φ d	φ D	t	h	φ D1	φ D2	H	Part number
AS-15	15	22	4.4	6	16	18.5	5.1	PB1001A0
AS-16	16	22	4.5	5.5	17	19.5	5.2	PB1002A0
AS-18	18	26	6.3	7.8	19	23	7	PB1003A0
AS-20	20	28	5.5	7	21	23	6.2	PB1004A0
AS-22	22	30	6.3	7.8	23	26	7	PB1005A0
AS-25	25	33	5.8	7.8	26	29	6.5	PB1006A0
AS-28A	28	36	6.2	7.8	29	32	7	PB1007A0
AS-28	28	37	7.3	8.5	29	32	8	PB1008A0
AS-30	30	40	6.2	7.8				
AS-32	32	42	6.2	7.8	33.5	37	7	PB1009A0
AS-35	35	45	6.3	8.5	36.5	40	7	PB1010A0
AS-36	36	46	6.2	7.8	37.5	41	7	PB1011A0
AS-40	40	50	6.2	7.8	41.5	45	7	PB1012A0
AS-45	45	55	6.3	8.3				
AS-50	50	60	6.2	7.8	51.5	55	7	PB1013A0
AS-55	55	67	6.6	8.3				