



The inner surface of the cylinder should be honed (GH) or polished (RLB) to 0.4~3.2 μm R_{max}(0.1~0.8 μm R_a).

Model	φ D	φ d	h	H	KVK Part number
PPZ-12	12	7	2	2.5	PD1001D0
PPZ-16	16	9	2.1	2.5	PD1002D0
PPZ-20	20	13	2.1	2.5	PD1003D0
PPZ-25	25	18	2.1	2.5	PD1004D0
PPZ-28	28	19	2.5	3	PD1005D0
PPZ-30	30	21	2.5	3	PD1006D0
PPZ-32	32	21	2.5	3	PD1030D0
PPZ-32	32	23	2.5	3	PD1007D0
PPZ-40	40	31	2.5	3	PD1008D0
PPZ-50	50	41	2.5	3	PD1009D0
PPZ-62	62	45	4.4	5	PD1031D0
PPZ-63	63	51	3.4	4	PD1026D0
PPZ-66	66	50	4.4	5	PD1032D0
PPZ-80	80	68	3.4	4	PD1027D0
PPZ-86	86	71	3.4	4	PD1033D0
PPZ-100	100	88	3.4	4	PD1028D0
PPZ-100	100	88	4.5	5	PD1034D0
PPZ-110	110	95	4.4	5	PD1035D0
PPZ-125	125	110	4.4	5	PD1029D0
PPZ-125	125	110	5.5	6	PD1036D0
PPZ-140	140	125	4.4	5	PD1037D0