Technical Data Sheet (TDS)

PODI-2015

Hetrun



Information	
	This product is a transfer adhesive for the head of toilet roll paper.
– Product feature	It has a very good balance of initial adhesion and "dry peeling" performance. The adhesive is slow to dry and has a long initial adhesion maintenance time. It has wide applicability to the production of toilet roll paper
- Apply process	It can be used to directly open the barrel for mixing, and is suitable for roller scraping and other gluing systems; It has the characteristics of wide applicability of the substrate, fast operation speed, no dirt and easy cleaning.
– Operation	Add water or raw rubber as needed. Due to different paper and machines, the proportion of customers is different. It is suggested that the ratio of mixing water is 1:2
Laws and regulations	All ingredients are in compliance with FDA Regulation 21 CFR 175.105 "Adhesive".
Physical parameters	
- Appearance	White or turquoise translucent liquid
– Sugar content	4.0-10.0BX
– Viscosity	10000-40000cps (5#/10rpm/27 $^{\circ}\rm{C}$)
Packing	50kg/barrel, 1000kg/barrel
Storage condition	It is stored in a dry and cool place above 6 ° C, and the shortest effective period is half a year.
Cautions	 Mixing with other products is prohibited; Cover tightly after application to avoid excessive evaporation and drying; Follow the first-in first-out principle when using.
Headquator Rm 502-503, Bld 3, Zhaoshan Plaza, Xingnan Rd 348, Pany District Tel: 020-39116768 Fax: 020-39111477 Email: Service@hetrun.com	



Update: 2022-1-12/Kelly Hetrun Industry Group Ltd

Headquator

Rm 502-503, Bld 3, Zhaoshang Plaza, Xingnan Rd 348, Panyu District Tel: 020-39116768 Fax: 020-39111477 Email: Service@hetrun.com

NanSha Plant

No. 6, Rd Shengping, No.83 of Rd Beilong, Dagang Town, Nansha Distric Tel: 020-39116768 Fax: 020-39111477 Email: Service@hetrun.com

HangZhou Office

Rm 2618, Frid Plaza, Xiasha Economic and Technological Development Zone Tel: 020-39116708 Fax: 020-39111477 Email: Service@hetrun.com