

1. Product description

Type-C Connectors described in this Technical Specification, Can be implemented in the Type-C interface, Support the DP-Alt notebook through the HDMI interface output computer display content, Maximum resolution supported:3840*2160/30HZ, 4K, Downward compatible resolution;You can charge your laptop or mobile phone by PD port And also realize the laptop with USB type-C port to USB3.0A*1 USB2.0A*1connecting.

Product Description	This is a USB C docking station, support USB C to HDMI, support USB3.0A,USB2.0A devices connected at the same time; At the same time, the mobile phone can be charged through an external Type-C port charger to power the mobile hard disk
USB-C uplink port x1	Used to connect with computer,USB3.0 male plug,Cable length is 112mm
	Support USB3.0 and down compatible USB2.0/1.1, up to 5Gbps transfer rate.
	When host computer supplying the power, output power is 5V/1.5AMax;When PD charging, output power is 20V/3.25A max
USB3.0-A download portx1	Used to extend the connection of USB devices, such as U disk/mouse/keyboard/mobile hard disk, etc
	Support USB3.0 and downward compatible with USB2.0/1.1, the highest transmission rate of 5Gbps
	Output power :5V/900mA 5V/2AMAX, (Type C interface 5V2A power supply)
USB2.0-A download portx1	Used to extend the connection of USB devices, such as U disk/mouse/keyboard/mobile hard disk, etc
	Support USB2.0/1.1 maximum transmission rate 480BPS output power :5V/900mA,5V/2AMAX, (Type C interface 5V2A power supply)
HDMIx1	For connecting the display by the DP cable , output the display content of the computer
	Support for Reproduction and Extended Display Features
	Maximum support resolution 3840*2160/30HZ, 4K, downward compatible resolution
Downlink USB C PD interface x 1	For power supply of products and mobile phone charging mobile hard disk, input power 20V/3.25A .
LED indicator light x 1	Green, The corresponding indicator light is always on after the host computer does not reach the USB device

2. Interface specifications:

Uplink USB-C 3.0 plug X 1

Downlink Interface:

HDMI port X 1

USB-C PD port x 1

USB-A 3.0 X 1

USB-A 2.0 X 1

supporting agreement: Usb Type-C,Usb PD3.0,HDMI2.0

3. Power adapter support

29W: output: 14.5V/2A(PD) 5.2V/2.4A

45W: output: 15V/3A, 12V/3A, 5V/2A

65W: output: 20V/3.25A , 15V/3A, 12V/2A, 5V/2A

4. Product Specification

Complete machine	Overall Product Size	84.8*31.6*10mm
	Weight	/
	Power consumption	1.1W
	Working temperature	0° C~ +40° C,
	Surface temperature	Working: ≤50C

5. Certification requirements

Meet the CCC/FCC/CE/CB safety test standard about USB C docking station

