



Product Data Sheet

Hi-gloss Paper/Rubber Based Permanent/ White Glassine

HF18A0822

Facestock

Hi-gloss paper

A white wood free paper with one side coated.

Color	White	
Basic Weight	75 (± 3)g/m ²	ISO-536
Thickness	86 (± 3) μ	ISO-534

Adhesive

Rubber based permanent

A rubber based hotmelt permanent adhesive providing excellent tack and adhesion to a wide variety of substrates including apolar surfaces.

Initial Tack	15 N/25mm	FTM9
Peel adhesion 90°	8 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-5 °C to 70°C	

Liner

One side siliconised glassine

Color	white	
Basic Weight	60 (± 2)g/m ²	ISO-536
Thickness	50 (± 2) μ	ISO-534

Application

Suitable for general purposes including promotional and identification labels which require multicolor print.

Printing Methods

Provides very good printability on most conventional printing technologies including water-based and UV flexo, UV letterpress. Good die-cutting and stripping properties.

Shelf life

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
 - Temperature 23 \pm 2°C .
 - Humidity 50 \pm 5%.
 - Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.