



Product Data Sheet

Woodfree Paper/Water Based Permanent/ Yellow Glassine

92C1427

Facestock			Application
Woodfree paper			Suitable for general purposes including address, blank and logistic labels.
A white wood free uncoated paper with non-glare surface.			
Color	White		
Basic Weight	$70 (\pm 2)g/m^2$	ISO-536	
Thickness	84 (±2)μ	ISO-534	Printing Methods
<u>Adhesive</u>			<u>Frinding Methods</u>
Water based permanent A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105, recommend on dry and non fatty foodstuffs.			Provides very good printability on most conventional printing technologies including water-based and UV flexo, UV letterpress. Good die-cutting and stripping properties.
Initial Tack	8 N/25mm	FTM9	
Peel adhesion 90°	6 N/25mm	FTM1	
Min.Appl.Temp.	+5 °C		<u>Shelf life</u>
Service Temp.	-20 °C to 120°C		1 ways if stored at following condition.
<u>Liner</u>			 1 year if stored at following condition: Store in a cool and dry place, and keep the material in original packaging when not used. Temperature 23±2°C.
One side siliconised yellow glassine			• Humidity 50 ±5%.
Color	yellow		Keep away from direct sunlight.
Basic Weight	$60(\pm 2)g/m^{2}$	ISO-536	
Thickness	50 (±2)μ	ISO-534	
			I

• The above data has been typically tested in our own labortary but it does not represent as guarantee of all purpose. In order to ensure the correct usge of our products, further testing on the corresponding substrates to verify the result is always recommended.