



Product Data Sheet

Synthetic Paper/Rubber Based Permanent/ White Glassine HA18E1922

Facestock

White Synthetic Paper

A matt, white, plain Polypropylene (PP) film with printable coating for water based ink.

Color	Matt White	
Basic Weight	66 (±3)g/m ²	ISO-536
Thickness	100 (±3)μ	ISO-534

Adhesive

Rubber based permanent

A rubber based hotmelt permanent adhesive providing excellent tack and adhesion to a wide variety of substrates including apolar surfaces.

Initial Tack	10 N/25mm	FTM9
Peel adhesion 90°	8 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-5 °C to 70°C	

Liner

One side siliconised glassine

Color	White	
Basic Weight	60 (±2)g/m ²	ISO-536
Thickness	50 (±3)μ	ISO-534

Application

Suitable for water based inkjet printing, suitable for wide range of purposes including promotional identification labels.

Printing Methods

Designed for water based inkjet printing machines. Good ink anchorage and water resistance.

Shelf life

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
 - Temperature 23±2°C .
 - Humidity 50±5%.
 - Keep away from direct sunlight.

- The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.