



## Product Data Sheet

## 40u Transparent PVC/Water Based Permanent/ Art paper

## 71D0206

Facestock			Application
40u Transparent PVC			Suitable for industrial and chemical
A transparent polyvinyl chloride film.			applications, it is mainly used in electronics, machinery, batteries, and outdoor products, with good durability.
Color	White		
Basic Weight	56 (±3)g/m²	ISO-536	
Thickness	40(±2)μ	ISO-534	
			Printing Methods
<u>Adhesive</u>			
Water based permanent A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105, recommend on dry and non fatty foodstuffs.			Provides very good printability on most conventional printing technologies including UV flexo, UV letterpress and UV offset.
Initial Tack	8 N/25mm	FTM9	
Peel adhesion 90°	6 N/25mm	FTM1	
Min.Appl.Temp.	+5 °C		<u>Shelf life</u>
Service Temp.	-20 °C to 120°C		
1			1 year if stored at following condition:
Liner			<ul> <li>Store in a cool and dry place, and keep the material in original packaging when not used.</li> <li>Torm protume 22+280</li> </ul>
One cide art nener			<ul> <li>Temperature 23±2°C.</li> <li>Humidity 50 ±5%.</li> </ul>
<b>One side art paper</b> Color	White		5
	White $1(9(15)\pi/m^2)$	150 526	• Keep away from direct sunlight.
Basic Weight Thickness	168 (±5)g/m <sup>2</sup>	ISO-536 ISO-534	
I IIIUKIIUSS	165 (±5)μ	130-334	

• The above data has been typically tested in our own labortary but it does not represent as guarantee of all purpose. In order to ensure the correct usge of our products, further testing on the corresponding substrates to verify the result is always recommended.