



## **Product Data Sheet**

### **Woodfree Paper/Rubber Based Permanent/ Yellow Paper**

**HF16C1402**

#### **Facestock**

##### **Woodfree paper**

A white wood free uncoated paper with non-glare surface.

Color	White	
Basic Weight	70 ( $\pm 2$ )g/m <sup>2</sup>	ISO-536
Thickness	84 ( $\pm 3$ ) $\mu$	ISO-534

#### **Adhesive**

##### **Rubber based permanent**

A rubber based hotmelt permanent adhesive providing excellent tack and adhesion to a wide variety of substrates including apolar surfaces.

Initial Tack	12 N/25mm	FTM9
Peel adhesion 90°	7 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-5 °C to 70°C	

#### **Liner**

##### **One side siliconised yellow paper**

Color	Yellow	
Basic Weight	85 ( $\pm 5$ )g/m <sup>2</sup>	ISO-536
Thickness	104 ( $\pm 5$ ) $\mu$	ISO-534

#### **Application**

Suitable for general purposes including address, blank and logistic labels.

#### **Printing Methods**

Provides very good printability on most conventional printing technologies including water-based and UV flexo, UV letterpress. Good die-cutting and stripping properties.

#### **Shelf life**

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
  - Temperature 23 $\pm$ 2°C .
  - Humidity 50  $\pm$ 5%.
  - Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.