



# **Product Data Sheet**

# Semigloss Paper/Water Based Permanent/y ellow Glassine

92B1027

## **Facestock**

#### Semigloss paper

A white wood free paper with one side coated.

Color White

Basic Weight 80  $(\pm 2)$ g/m<sup>2</sup> ISO-536 Thickness 68  $(\pm 2)$ µ ISO-534

### **Adhesive**

#### Water based permanent

A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105, recommend on dry and non fatty foodstuffs.

Initial Tack 8 N/25mm FTM9 Peel adhesion 90° 6 N/25mm FTM1

Min.Appl.Temp. +5 °C

Service Temp. -20 °C to 120°C

### Liner

### One side siliconised glassine

Color yellow

 $\begin{array}{lll} Basic \ Weight & 60\ (\pm 2)g/m^2 & ISO-536 \\ Thickness & 50(\pm 2)\mu & ISO-534 \end{array}$ 

## **Application**

Suitable for general purposes including promotional and identification labels which require multicolor print.

## **Printing Methods**

Provides very good printability on most conventional printing technologies including water-based and UV flexo, UV letterpress. Good die-cutting and stripping properties.

### **Shelf life**

1 year if stored at following condition:

- Store in a cool and dry place, and keep the material in original packaging when not used.
- Temperature 23±2°C.
- Humidity 50 ±5%.
- Keep away from direct sunlight.

• The above data has been typically tested in our own labortary but it does not represent as guarantee of all purpose. In order to ensure the correct usge of our products, further testing on the corresponding substrates to verify the result is always recommended.