



Product Data Sheet

Transparent PE (TC)/Water Based Permanent/ White Glassine 71QL0222

Facestock

Transparent PE

A transparent polyethylene film with printable coating.

Color	/	
Basic Weight	70 (± 2)g/m ²	ISO-536
Thickness	78 (± 2) μ	ISO-534

Adhesive

Water based permanent

A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105, recommend on dry and non fatty foodstuffs.

Initial Tack	8 N/25mm	FTM9
Peel adhesion 90°	6 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-10 °C to 80°C	

Liner

One side siliconised glassine

Color	White	
Basic Weight	60 (± 2)g/m ²	ISO-536
Thickness	50 (± 2) μ	ISO-534

Application

This material mainly use in home and personal care product. Due to its flexibility the product is especially suitable for squeezable bottles and other flexible containers.

Printing Methods

Provides very good printability on most conventional printing technologies including UV flexo, UV letterpress and UV offset.

Shelf life

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
 - Temperature 23 \pm 2°C .
 - Humidity 50 \pm 5%.
 - Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.