



## **Product Data Sheet**

**100u Bright White PVC/Water Based Permanent/ Art paper**

**71D1725**

### **Facestock**

#### **Bright White PVC**

A bright white polyvinyl chloride film.

Color	White	
Basic Weight	130 (±2)g/m <sup>2</sup>	ISO-536
Thickness	95(±5)μ	ISO-534

### **Adhesive**

#### **Water based permanent**

A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105, recommend on dry and non fatty foodstuffs.

Initial Tack	8 N/25mm	FTM9
Peel adhesion 90°	6 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-20 °C to 120°C	

### **Liner**

#### **One side art paper**

Color	White	
Basic Weight	135 (±5)g/m <sup>2</sup>	ISO-536
Thickness	135 (±5)μ	ISO-534

### **Application**

Suitable for industrial and chemical applications, it is mainly used in electronics, machinery, batteries, and outdoor products, with good durability.

### **Printing Methods**

Provides very good printability on most conventional printing technologies including UV flexo, UV letterpress and UV offset.

### **Shelf life**

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
  - Temperature 23±2°C.
  - Humidity 50 ±5%.
  - Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.