



## Product Data Sheet

### **Synthetic Paper/Rubber Based Permanent/Yellow Glassine HA18E1927**

#### **Facestock**

##### **White Synthetic Paper**

A matt, white, plain Polypropylene (PP) film with printable coating for water based ink.

Color	Matt White	
Basic Weight	66 ( $\pm 3$ )g/m <sup>2</sup>	ISO-536
Thickness	100 ( $\pm 3$ ) $\mu$	ISO-534

#### **Adhesive**

##### **Rubber based permanent**

A rubber based hotmelt permanent adhesive providing excellent tack and adhesion to a wide variety of substrates including apolar surfaces.

Initial Tack	10 N/25mm	FTM9
Peel adhesion 90°	8 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-5 °C to 70°C	

#### **Liner**

##### **One side siliconised glassine**

Color	Yellow	
Basic Weight	60 ( $\pm 2$ )g/m <sup>2</sup>	ISO-536
Thickness	50 ( $\pm 3$ ) $\mu$	ISO-534

#### **Application**

Suitable for water based inkjet printing, suitable for wide range of purposes including promotional identification labels.

#### **Printing Methods**

Designed for water based inkjet printing machines. Good ink anchorage and water resistance.

#### **Shelf life**

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
  - Temperature 23 $\pm$ 2°C .
  - Humidity 50 $\pm$ 5%.
  - Keep away from direct sunlight.

- The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.